

# Solid Tantalum Surface Mount Chip Capacitors

## TANTAMOUNT<sup>®</sup>, Molded Case, Standard Industrial Grade



### PERFORMANCE/ELECTRICAL CHARACTERISTICS

[www.vishay.com/doc?40088](http://www.vishay.com/doc?40088)

**Operating Temperature:** - 55 °C to + 125 °C  
(above 85 °C, voltage derating is required)

**Capacitance Range:** 0.10 µF to 1000 µF

**Capacitance Tolerance:** ± 5 %, ± 10 %, ± 20 %

**100 % Surge Current Tested (D and E Case Codes)**

**Voltage Rating:** 4 V<sub>DC</sub> to 63 V<sub>DC</sub>

### FEATURES

- Molded case available in six case codes
- Terminations: 100 % matte tin, standard, tin/lead available
- Compatible with “High Volume” automatic pick and place equipment
- Meets IEC specification QC300801/US0001 and EIA535BAAC mechanical and performance requirements
- Moisture sensitivity level 1
- Optical character recognition qualified
- Compliant terminations
- Material categorization: For definitions of compliance please see [www.vishay.com/doc?99912](http://www.vishay.com/doc?99912)



**RoHS\***  
COMPLIANT

### Note

\* Lead (Pb)-containing terminations are not RoHS-compliant. Exemptions may apply.

### APPLICATIONS

- Industrial
- Telecom infrastructure
- General purpose

### ORDERING INFORMATION

| 293D<br>TYPE | 107<br>CAPACITANCE   | X9<br>CAPACITANCE TOLERANCE                              | 010<br>DC VOLTAGE RATING AT + 85 °C  | D<br>CASE CODE                   | 2WE3<br>TERMINATION AND PACKAGING  |
|--------------|--|--|--|----------------------------------|--|
|              | This is expressed in picofarads. The first two digits are the significant figures. The third is the number of zeros to follow. | X0 = ± 20 %<br>X9 = ± 10 %<br>X5 = ± 5 % (special order) | This is expressed in V. To complete the three-digit block, zeros precede the voltage rating. A decimal point is indicated by an “R” (6R3 = 6.3 V). | See Ratings and Case Codes table | 2TE3: Matte tin, 7" (178 mm) reel<br>2WE3: Matte tin, 13" (330 mm) reel<br>8T: Tin/lead, 7" (178 mm) reel<br>8W: Tin/lead, 13" (330 mm) reel |

### Notes

- We reserve the right to supply higher voltage ratings and tighter capacitance tolerance capacitors in the same case size. Voltage substitutions will be marked with the higher voltage rating.
- We reserve the right to supply better series with more extensive screening.
- Dry pack is available per request, contact regional marketing.

### DIMENSIONS in inches [millimeters]



| CASE CODE | EIA SIZE | L                             | W                             | H                             | P                              | T <sub>w</sub>                | T <sub>H</sub> (MIN.) |
|-----------|----------|-------------------------------|-------------------------------|-------------------------------|--------------------------------|-------------------------------|-----------------------|
| A         | 3216-18  | 0.126 ± 0.008<br>[3.2 ± 0.20] | 0.063 ± 0.008<br>[1.6 ± 0.20] | 0.063 ± 0.008<br>[1.6 ± 0.20] | 0.031 ± 0.012<br>[0.80 ± 0.30] | 0.047 ± 0.004<br>[1.2 ± 0.10] | 0.028<br>[0.70]       |
| B         | 3528-21  | 0.138 ± 0.008<br>[3.5 ± 0.20] | 0.110 ± 0.008<br>[2.8 ± 0.20] | 0.075 ± 0.008<br>[1.9 ± 0.20] | 0.031 ± 0.012<br>[0.80 ± 0.30] | 0.087 ± 0.004<br>[2.2 ± 0.10] | 0.028<br>[0.70]       |
| C         | 6032-28  | 0.236 ± 0.012<br>[6.0 ± 0.30] | 0.126 ± 0.012<br>[3.2 ± 0.30] | 0.098 ± 0.012<br>[2.5 ± 0.30] | 0.051 ± 0.012<br>[1.3 ± 0.30]  | 0.087 ± 0.004<br>[2.2 ± 0.10] | 0.039<br>[1.0]        |
| D         | 7343-31  | 0.287 ± 0.012<br>[7.3 ± 0.30] | 0.169 ± 0.012<br>[4.3 ± 0.30] | 0.110 ± 0.012<br>[2.8 ± 0.30] | 0.051 ± 0.012<br>[1.3 ± 0.30]  | 0.094 ± 0.004<br>[2.4 ± 0.10] | 0.039<br>[1.0]        |
| E         | 7343-43  | 0.287 ± 0.012<br>[7.3 ± 0.30] | 0.169 ± 0.012<br>[4.3 ± 0.30] | 0.157 ± 0.012<br>[4.0 ± 0.30] | 0.051 ± 0.012<br>[1.3 ± 0.30]  | 0.094 ± 0.004<br>[2.4 ± 0.10] | 0.039<br>[1.0]        |
| V         | 7343-20  | 0.287 ± 0.012<br>[7.3 ± 0.30] | 0.169 ± 0.012<br>[4.3 ± 0.30] | 0.079 max<br>[2.0 max]        | 0.051 ± 0.012<br>[1.3 ± 0.30]  | 0.094 ± 0.004<br>[2.4 ± 0.10] | 0.039<br>[1.0]        |

| RATINGS AND CASE CODES |         |         |           |         |       |         |       |       |      |
|------------------------|---------|---------|-----------|---------|-------|---------|-------|-------|------|
| μF                     | 4 V     | 6.3 V   | 10 V      | 16 V    | 20 V  | 25 V    | 35 V  | 50 V  | 63 V |
| 0.10                   |         |         |           |         |       | A       | A     | A     |      |
| 0.15                   |         |         |           |         |       |         | A     | A/B   |      |
| 0.22                   |         |         |           |         |       |         | A     | A/B   |      |
| 0.33                   |         |         |           |         |       | A       | A     | A/B   |      |
| 0.47                   |         |         | A         |         | A     | A       | A/B   | A/B/C |      |
| 0.68                   |         |         |           | A       | A     | A       | A/B   | B/C   |      |
| 1.0                    |         |         | A         | A       | A/B   | A/B     | A/B   | B/C   |      |
| 1.5                    |         | A       | A         | A/B     | A/B   | A/B     | B/C   | B/C/D |      |
| 2.2                    | A       | A       | A/B       | A/B     | A/B   | A/B/C   | B/C   | B/C/D |      |
| 3.3                    | A       | A/B     | A/B       | A/B     | A/B/C | A/B/C   | B/C/D | C/D   |      |
| 4.7                    | A/B     | A/B     | A/B/C     | A/B/C   | A/B/C | A/B/C/D | B/C/D | C/D/E | D    |
| 6.8                    | A/B     | A/B     | A/B/C     | A/B/C   | A/B/C | B/C/D   | C/D   | D/E   |      |
| 10                     | A/B     | A/B/C   | A/B/C     | A/B/C/D | B/C/D | B/C/D   | C/D   | D/E   | E    |
| 15                     | A/B/C   | A/B/C   | A/B/C     | B/C     | B/C/D | B/C/D   | D/E   | E     |      |
| 22                     | A/B/C   | A/B/C   | A/B/C/D   | B/C/D   | B/C/D | C/D/E/V | D/E   |       |      |
| 33                     | A/B/C   | A/B/C   | B/C/D     | B/C/D   | C/D   | D/E     |       |       |      |
| 47                     | A/B/C   | A/B/C/D | B/C/D     | C/D/E   | D/E   | D/E     |       |       |      |
| 68                     | B/C/D   | B/C/D   | B/C/D/E/V | D/E     | D/E   | E       |       |       |      |
| 100                    | A/B/C/D | B/C/D/E | B/C/D/E/V | D/E/V   | D/E   |         |       |       |      |
| 120                    | D       | D       | E         |         |       |         |       |       |      |
| 150                    | B/C/D   | C/D/E   | C/D/E     | D/E     |       |         |       |       |      |
| 220                    | B/C/D/E | C/D/E   | D/E/V     | E       |       |         |       |       |      |
| 330                    | D/E     | D/E     | D/E       |         |       |         |       |       |      |
| 470                    | D/E     | D/E     | E         |         |       |         |       |       |      |
| 680                    | D/E     | E       |           |         |       |         |       |       |      |
| 1000                   | E       | E       |           |         |       |         |       |       |      |

| MARKING              |                              |             |                                   |
|----------------------|------------------------------|-------------|-----------------------------------|
| <p><b>A Case</b></p> | <b>“A” CASE VOLTAGE CODE</b> |             | <p><b>B, C, D, E, V Cases</b></p> |
|                      | <b>VOLTS</b>                 | <b>CODE</b> |                                   |
|                      | 4.0                          | G           |                                   |
|                      | 6.3                          | J           |                                   |
|                      | 10                           | A           |                                   |
|                      | 16                           | C           |                                   |
|                      | 20                           | D           |                                   |
| 25                   | E                            |             |                                   |
| 35                   | V                            |             |                                   |
| 50                   | T                            |             |                                   |

**Marking**

Capacitor marking includes an anode (+) polarity band, capacitance in microfarads and the voltage rating. “A” Case capacitors use a letter code for the voltage and EIA capacitance code.

The Vishay Sprague® trademark is included if space permits. Capacitors rated at 6.3 V are marked 6 V.

A manufacturing date code is marked on all capacitors.

Capacitors may bear a different marking scheme if a part with more extensive screening is substituted. These would include “R” for low ESR series (TR3) or “P” for professional series (TP3).

Call the factory for further explanation.



| STANDARD RATINGS   |           |                   |  |  |   |  |
|--|-----------|-------------------|--|--|---|--|
| CAPACITANCE<br>( $\mu$ F)  | CASE CODE | PART NUMBER       | MAX. DC<br>LEAKAGE<br>AT + 25 °C<br>( $\mu$ A) | MAX. DF<br>AT + 25 °C<br>120 Hz<br>(%) | MAX. ESR<br>AT + 25 °C<br>100 kHz<br>( $\Omega$ ) | MAX. RIPPLE<br>100 kHz<br>$I_{RMS}$<br>(A) |
| <b>4 V<sub>DC</sub> AT + 85 °C; 2.7 V<sub>DC</sub> AT + 125 °C</b> |           |                   |  |  |   |  |
| 2.2  | A         | 293D225(1)004A(2) | 0.5  | 6                                      | 7.60  | 0.10                                       |
| 3.3  | A         | 293D335(1)004A(2) | 0.5  | 6                                      | 7.60  | 0.10                                       |
| 4.7  | A         | 293D475(1)004A(2) | 0.5  | 6                                      | 6.30  | 0.11                                       |
| 4.7  | B         | 293D475(1)004B(2) | 0.5  | 6                                      | 7.00  | 0.11                                       |
| 6.8  | A         | 293D685(1)004A(2) | 0.5  | 6                                      | 5.50  | 0.12                                       |
| 6.8  | B         | 293D685(1)004B(2) | 0.5  | 6                                      | 3.40  | 0.16                                       |
| 10   | A         | 293D106(1)004A(2) | 0.5  | 6                                      | 5.10  | 0.12                                       |
| 10   | B         | 293D106(1)004B(2) | 0.5  | 6                                      | 3.50  | 0.16                                       |
| 15   | A         | 293D156(1)004A(2) | 0.6  | 6                                      | 3.40  | 0.15                                       |
| 15   | B         | 293D156(1)004B(2) | 0.6  | 6                                      | 2.90  | 0.17                                       |
| 15   | C         | 293D156(1)004C(2) | 0.6  | 6                                      | 2.80  | 0.20                                       |
| 22   | A         | 293D226(1)004A(2) | 0.9  | 6                                      | 2.90  | 0.16                                       |
| 22   | B         | 293D226(1)004B(2) | 0.9  | 6                                      | 2.50  | 0.18                                       |
| 22   | C         | 293D226(1)004C(2) | 0.9  | 6                                      | 1.80  | 0.25                                       |
| 33   | A         | 293D336(1)004A(2) | 1.3  | 6                                      | 2.90  | 0.16                                       |
| 33   | B         | 293D336(1)004B(2) | 1.3  | 6                                      | 2.00  | 0.21                                       |
| 33   | C         | 293D336(1)004C(2) | 1.3  | 6                                      | 1.80  | 0.25                                       |
| 47   | A         | 293D476(1)004A(2) | 1.9  | 14                                     | 2.50  | 0.17                                       |
| 47   | B         | 293D476(1)004B(2) | 1.9  | 6                                      | 1.90  | 0.21                                       |
| 47   | C         | 293D476(1)004C(2) | 1.9  | 6                                      | 1.80  | 0.25                                       |
| 68   | B         | 293D686(1)004B(2) | 2.7  | 6                                      | 1.90  | 0.21                                       |
| 68   | C         | 293D686(1)004C(2) | 2.7  | 6                                      | 1.40  | 0.28                                       |
| 68   | D         | 293D686(1)004D(2) | 2.7  | 6                                      | 0.80  | 0.43                                       |
| 100  | A         | 293D107X0004A(2)  | 10.0   | 30                                     | 2.50  | 0.22                                       |
| 100  | B         | 293D107(1)004B(2) | 4.0  | 8                                      | 1.80  | 0.22                                       |
| 100  | C         | 293D107(1)004C(2) | 4.0  | 6                                      | 0.80  | 0.37                                       |
| 100  | D         | 293D107(1)004D(2) | 4.0  | 6                                      | 0.70  | 0.46                                       |
| 120  | D         | 293D127(1)004D(2) | 4.8  | 6                                      | 0.60  | 0.51                                       |
| 150  | B         | 293D157(1)004B(2) | 6.0  | 14                                     | 1.60  | 0.23                                       |
| 150  | C         | 293D157(1)004C(2) | 6.0  | 12                                     | 0.70  | 0.40                                       |
| 150  | D         | 293D157(1)004D(2) | 6.0  | 8                                      | 0.60  | 0.50                                       |
| 220  | B         | 293D227X0004B(2)  | 8.8  | 18                                     | 1.50  | 0.24                                       |
| 220  | C         | 293D227(1)004C(2) | 8.8  | 8                                      | 0.70  | 0.40                                       |
| 220  | D         | 293D227(1)004D(2) | 8.8  | 8                                      | 0.60  | 0.50                                       |
| 220  | E         | 293D227(1)004E(2) | 8.8  | 8                                      | 0.50  | 0.57                                       |
| 330  | D         | 293D337(1)004D(2) | 13.2   | 8                                      | 0.60  | 0.50                                       |
| 330  | E         | 293D337(1)004E(2) | 13.2   | 8                                      | 0.50  | 0.57                                       |
| 470  | D         | 293D477(1)004D(2) | 18.8   | 10                                     | 0.60  | 0.50                                       |
| 470  | E         | 293D477(1)004E(2) | 18.8   | 10                                     | 0.50  | 0.57                                       |
| 680  | D         | 293D687X0004D(2)  | 27.2   | 25                                     | 0.20  | 0.87                                       |
| 680  | E         | 293D687(1)004E(2) | 27.2   | 12                                     | 0.50  | 0.57                                       |
| 1000   | E         | 293D108X0004E(2)  | 40.0   | 20                                     | 0.50  | 0.57                                       |

Note

- Part number definitions:
  - (1) Tolerance: X0, X9
  - (2) Terminations and packaging: 2TE3, 2WE3, 8T, 8W
  - (3) Lead (Pb)-free terminations and packaging codes: 2TE3, 2WE3



| STANDARD RATINGS   |           |                   |  |  |   |  |
|--|-----------|-------------------|--|--|---|--|
| CAPACITANCE<br>( $\mu$ F)  | CASE CODE | PART NUMBER       | MAX. DC<br>LEAKAGE<br>AT + 25 °C<br>( $\mu$ A) | MAX. DF<br>AT + 25 °C<br>120 Hz<br>(%) | MAX. ESR<br>AT + 25 °C<br>100 kHz<br>( $\Omega$ ) | MAX. RIPPLE<br>100 kHz<br>$I_{RMS}$<br>(A) |
| <b>6.3 V<sub>DC</sub> AT + 85 °C; 4 V<sub>DC</sub> AT 125 °C</b> |           |                   |  |  |   |  |
| 1.5  | A         | 293D155(1)6R3A(2) | 0.5  | 6                                      | 2.90  | 0.16                                       |
| 2.2  | A         | 293D225(1)6R3A(2) | 0.5  | 6                                      | 7.60  | 0.10                                       |
| 3.3  | A         | 293D335(1)6R3A(2) | 0.5  | 6                                      | 6.30  | 0.11                                       |
| 3.3  | B         | 293D335(1)6R3B(2) | 0.5  | 6                                      | 5.50  | 0.12                                       |
| 4.7  | A         | 293D475(1)6R3A(2) | 0.5  | 6                                      | 5.50  | 0.12                                       |
| 4.7  | B         | 293D475(1)6R3B(2) | 0.5  | 6                                      | 4.40  | 0.14                                       |
| 6.8  | A         | 293D685(1)6R3A(2) | 0.5  | 6                                      | 5.00  | 0.12                                       |
| 6.8  | B         | 293D685(1)6R3B(2) | 0.5  | 6                                      | 3.40  | 0.16                                       |
| 10   | A         | 293D106(1)6R3A(2) | 0.6  | 6                                      | 3.40  | 0.15                                       |
| 10   | B         | 293D106(1)6R3B(2) | 0.6  | 6                                      | 2.90  | 0.17                                       |
| 10   | C         | 293D106(1)6R3C(2) | 0.6  | 6                                      | 3.00  | 0.19                                       |
| 15   | A         | 293D156(1)6R3A(2) | 0.9  | 6                                      | 2.90  | 0.16                                       |
| 15   | B         | 293D156(1)6R3B(2) | 0.9  | 6                                      | 2.50  | 0.18                                       |
| 15   | C         | 293D156(1)6R3C(2) | 0.9  | 6                                      | 1.80  | 0.25                                       |
| 22   | A         | 293D226(1)6R3A(2) | 1.3  | 6                                      | 2.90  | 0.16                                       |
| 22   | B         | 293D226(1)6R3B(2) | 1.3  | 6                                      | 2.00  | 0.21                                       |
| 22   | C         | 293D226(1)6R3C(2) | 1.3  | 6                                      | 1.80  | 0.25                                       |
| 33   | A         | 293D336(1)6R3A(2) | 2.0  | 14                                     | 2.50  | 0.17                                       |
| 33   | B         | 293D336(1)6R3B(2) | 2.0  | 6                                      | 1.90  | 0.21                                       |
| 33   | C         | 293D336(1)6R3C(2) | 2.0  | 6                                      | 1.50  | 0.27                                       |
| 47   | A         | 293D476(1)6R3A(2) | 2.8  | 12                                     | 1.60  | 0.22                                       |
| 47   | B         | 293D476(1)6R3B(2) | 2.8  | 6                                      | 1.90  | 0.21                                       |
| 47   | C         | 293D476(1)6R3C(2) | 2.8  | 6                                      | 1.40  | 0.28                                       |
| 47   | D         | 293D476(1)6R3D(2) | 2.8  | 6                                      | 0.80  | 0.43                                       |
| 68   | B         | 293D686(1)6R3B(2) | 4.1  | 6                                      | 1.80  | 0.22                                       |
| 68   | C         | 293D686(1)6R3C(2) | 4.1  | 6                                      | 0.80  | 0.37                                       |
| 68   | D         | 293D686(1)6R3D(2) | 4.1  | 6                                      | 0.70  | 0.46                                       |
| 100  | B         | 293D107(1)6R3B(2) | 6.0  | 15                                     | 1.70  | 0.22                                       |
| 100  | C         | 293D107(1)6R3C(2) | 6.0  | 6                                      | 0.80  | 0.37                                       |
| 100  | D         | 293D107(1)6R3D(2) | 6.0  | 6                                      | 0.70  | 0.46                                       |
| 100  | E         | 293D107(1)6R3E(2) | 6.0  | 8                                      | 0.70  | 0.49                                       |
| 120  | D         | 293D127(1)6R3D(2) | 6.3  | 8                                      | 0.70  | 0.46                                       |
| 150  | C         | 293D157(1)6R3C(2) | 9.0  | 8                                      | 0.70  | 0.40                                       |
| 150  | D         | 293D157(1)6R3D(2) | 9.0  | 8                                      | 0.60  | 0.50                                       |
| 150  | E         | 293D157(1)6R3E(2) | 9.0  | 8                                      | 0.50  | 0.57                                       |
| 220  | C         | 293D227(1)6R3C(2) | 13.9   | 14                                     | 0.70  | 0.39                                       |
| 220  | D         | 293D227(1)6R3D(2) | 13.2   | 8                                      | 0.60  | 0.50                                       |
| 220  | E         | 293D227(1)6R3E(2) | 13.2   | 8                                      | 0.50  | 0.57                                       |
| 330  | D         | 293D337(1)6R3D(2) | 19.8   | 8                                      | 0.60  | 0.50                                       |
| 330  | E         | 293D337(1)6R3E(2) | 19.8   | 8                                      | 0.50  | 0.57                                       |
| 470  | D         | 293D477(1)6R3D(2) | 28.2   | 14                                     | 0.50  | 0.55                                       |
| 470  | E         | 293E477(1)6R3E(2) | 28.2   | 10                                     | 1.50  | 0.57                                       |
| 680  | E         | 293D687(1)6R3E(2) | 42.8   | 20                                     | 0.50  | 0.57                                       |
| 1000   | E         | 293D108X06R3E(2)  | 63.0   | 30                                     | 0.40  | 0.64                                       |

**Note**

- Part number definitions:
  - Tolerance: X0, X9
  - Terminations and packaging: 2TE3, 2WE3, 8T, 8W
  - Lead (Pb)-free terminations and packaging codes: 2TE3, 2WE3



| STANDARD RATINGS  |           |                   |  |  |   |  |
|---|-----------|-------------------|--|--|---|--|
| CAPACITANCE<br>( $\mu$ F)                                       | CASE CODE | PART NUMBER       | MAX. DC<br>LEAKAGE<br>AT + 25 °C<br>( $\mu$ A) | MAX. DF<br>AT + 25 °C<br>120 Hz<br>(%) | MAX. ESR<br>AT + 25 °C<br>100 kHz<br>( $\Omega$ ) | MAX. RIPPLE<br>100 kHz<br>$I_{RMS}$<br>(A) |
| <b>10 V<sub>DC</sub> AT + 85 °C; 7 V<sub>DC</sub> AT 125 °C</b> |           |                   |  |  |   |  |
| 0.47  | A         | 293D474(1)010A(2) | 0.5  | 4                                      | 14.00   | 0.07                                       |
| 1.0   | A         | 293D105(1)010A(2) | 0.5  | 4                                      | 9.60  | 0.09                                       |
| 1.5   | A         | 293D155(1)010A(2) | 0.5  | 6                                      | 8.00  | 0.10                                       |
| 2.2   | A         | 293D225(1)010A(2) | 0.5  | 6                                      | 6.30  | 0.11                                       |
| 2.2   | B         | 293D225(1)010B(2) | 0.5  | 6                                      | 4.60  | 0.14                                       |
| 3.3   | A         | 293D335(1)010A(2) | 0.5  | 6                                      | 5.50  | 0.12                                       |
| 3.3   | B         | 293D335(1)010B(2) | 0.5  | 6                                      | 5.50  | 0.12                                       |
| 4.7   | A         | 293D475(1)010A(2) | 0.5  | 6                                      | 5.00  | 0.12                                       |
| 4.7   | B         | 293D475(1)010B(2) | 0.5  | 6                                      | 3.40  | 0.16                                       |
| 4.7   | C         | 293D475(1)010C(2) | 0.5  | 6                                      | 2.30  | 0.22                                       |
| 6.8   | A         | 293D685(1)010A(2) | 0.7  | 6                                      | 4.20  | 0.13                                       |
| 6.8   | B         | 293D685(1)010B(2) | 0.7  | 6                                      | 2.90  | 0.17                                       |
| 6.8   | C         | 293D685(1)010C(2) | 0.7  | 6                                      | 1.90  | 0.24                                       |
| 10  | A         | 293D106(1)010A(2) | 1.0  | 6                                      | 3.40  | 0.15                                       |
| 10  | B         | 293D106(1)010B(2) | 1.0  | 6                                      | 2.50  | 0.18                                       |
| 10  | C         | 293D106(1)010C(2) | 1.0  | 6                                      | 1.80  | 0.25                                       |
| 15  | A         | 293D156(1)010A(2) | 1.5  | 6                                      | 2.90  | 0.16                                       |
| 15  | B         | 293D156(1)010B(2) | 1.5  | 6                                      | 2.00  | 0.21                                       |
| 15  | C         | 293D156(1)010C(2) | 1.5  | 6                                      | 1.80  | 0.25                                       |
| 22  | A         | 293D226(1)010A(2) | 2.2  | 8                                      | 2.50  | 0.17                                       |
| 22  | B         | 293D226(1)010B(2) | 2.2  | 6                                      | 1.90  | 0.21                                       |
| 22  | C         | 293D226(1)010C(2) | 2.2  | 6                                      | 1.50  | 0.27                                       |
| 22  | D         | 293D226(1)010D(2) | 2.2  | 6                                      | 1.50  | 0.32                                       |
| 33  | B         | 293D336(1)010B(2) | 3.3  | 6                                      | 1.90  | 0.21                                       |
| 33  | C         | 293D336(1)010C(2) | 3.3  | 6                                      | 1.40  | 0.28                                       |
| 33  | D         | 293D336(1)010D(2) | 3.3  | 6                                      | 0.80  | 0.43                                       |
| 47  | B         | 293D476(1)010B(2) | 4.7  | 6                                      | 1.80  | 0.22                                       |
| 47  | C         | 293D476(1)010C(2) | 4.7  | 6                                      | 1.10  | 0.32                                       |
| 47  | D         | 293D476(1)010D(2) | 4.7  | 6                                      | 0.70  | 0.46                                       |
| 68  | B         | 293D686(1)010B(2) | 6.8  | 14                                     | 1.80  | 0.22                                       |
| 68  | C         | 293D686(1)010C(2) | 6.8  | 6                                      | 1.00  | 0.33                                       |
| 68  | D         | 293D686(1)010D(2) | 6.8  | 6                                      | 0.70  | 0.46                                       |
| 68  | E         | 293D686(1)010E(2) | 6.8  | 6                                      | 0.80  | 0.45                                       |
| 68  | V         | 293D686(1)010V(3) | 6.8  | 6                                      | 0.70  | 0.42                                       |
| 100   | B         | 293D107X0010B(2)  | 10.0   | 25                                     | 2.50  | 0.18                                       |
| 100   | C         | 293D107(1)010C(2) | 10.0   | 8                                      | 0.90  | 0.35                                       |
| 100   | D         | 293D107(1)010D(2) | 10.0   | 8                                      | 0.60  | 0.50                                       |
| 100   | E         | 293D107(1)010E(2) | 10.0   | 8                                      | 0.70  | 0.49                                       |
| 100   | V         | 293D107(1)010V(3) | 10.0   | 8                                      | 0.70  | 0.42                                       |
| 120   | E         | 293D127(1)010E(2) | 12.0   | 6                                      | 1.00  | 0.41                                       |
| 150   | C         | 293D157X0010C(2)  | 15.0   | 20                                     | 0.90  | 0.35                                       |
| 150   | D         | 293D157(1)010D(2) | 15.0   | 8                                      | 0.60  | 0.50                                       |
| 150   | E         | 293D157(1)010E(2) | 15.0   | 8                                      | 0.50  | 0.57                                       |
| 220   | D         | 293D227(1)010D(2) | 22.0   | 8                                      | 0.60  | 0.50                                       |

**Note**

- Part number definitions:
  - Tolerance: X0, X9
  - Terminations and packaging: 2TE3, 2WE3, 8T, 8W
  - Lead (Pb)-free terminations and packaging codes: 2TE3, 2WE3



| STANDARD RATINGS   |           |                   |  |  |   |  |
|--|-----------|-------------------|--|--|---|--|
| CAPACITANCE<br>( $\mu$ F)  | CASE CODE | PART NUMBER       | MAX. DC<br>LEAKAGE<br>AT + 25 °C<br>( $\mu$ A) | MAX. DF<br>AT + 25 °C<br>120 Hz<br>(%) | MAX. ESR<br>AT + 25 °C<br>100 kHz<br>( $\Omega$ ) | MAX. RIPPLE<br>100 kHz<br>$I_{RMS}$<br>(A) |
| <b>10 V<sub>DC</sub> AT + 85 °C; 7 V<sub>DC</sub> AT 125 °C</b>    |           |                   |  |  |   |  |
| 220  | E         | 293D227(1)010E(2) | 22.0   | 8                                      | 0.50  | 0.57                                       |
| 220  | V         | 293D227(1)010V(3) | 30.0   | 12                                     | 0.50  | 0.50                                       |
| 330  | D         | 293D337(1)010D(2) | 33.0   | 15                                     | 0.50  | 0.57                                       |
| 330  | E         | 293D337(1)010E(2) | 33.0   | 10                                     | 0.50  | 0.57                                       |
| 470  | E         | 293D477(1)010E(2) | 47.0   | 15                                     | 0.50  | 0.57                                       |
| <b>16 V<sub>DC</sub> AT + 85 °C; 10 V<sub>DC</sub> AT + 125 °C</b> |           |                   |  |  |   |  |
| 0.68   | A         | 293D684(1)016A(2) | 0.5  | 4                                      | 10.40   | 0.08                                       |
| 1.0  | A         | 293D105(1)016A(2) | 0.5  | 4                                      | 9.30  | 0.09                                       |
| 1.5  | A         | 293D155(1)016A(2) | 0.5  | 6                                      | 6.70  | 0.11                                       |
| 1.5  | B         | 293D155(1)016B(2) | 0.5  | 6                                      | 6.40  | 0.12                                       |
| 2.2  | A         | 293D225(1)016A(2) | 0.5  | 6                                      | 5.90  | 0.11                                       |
| 2.2  | B         | 293D225(1)016B(2) | 0.5  | 6                                      | 4.60  | 0.14                                       |
| 3.3  | A         | 293D335(1)016A(2) | 0.5  | 6                                      | 5.00  | 0.12                                       |
| 3.3  | B         | 293D335(1)016B(2) | 0.5  | 6                                      | 3.50  | 0.16                                       |
| 4.7  | A         | 293D475(1)016A(2) | 0.8  | 6                                      | 5.00  | 0.12                                       |
| 4.7  | B         | 293D475(1)016B(2) | 0.8  | 6                                      | 2.90  | 0.17                                       |
| 4.7  | C         | 293D475(1)016C(2) | 0.8  | 6                                      | 2.90  | 0.19                                       |
| 6.8  | A         | 293D685(1)016A(2) | 1.1  | 6                                      | 4.20  | 0.13                                       |
| 6.8  | B         | 293D685(1)016B(2) | 1.1  | 6                                      | 2.50  | 0.18                                       |
| 6.8  | C         | 293D685(1)016C(2) | 1.1  | 6                                      | 1.90  | 0.24                                       |
| 10   | A         | 293D106(1)016A(2) | 1.6  | 6                                      | 3.00  | 0.16                                       |
| 10   | B         | 293D106(1)016B(2) | 1.6  | 6                                      | 2.00  | 0.21                                       |
| 10   | C         | 293D106(1)016C(2) | 1.6  | 6                                      | 1.80  | 0.25                                       |
| 10   | D         | 293D106(1)016D(2) | 2.5  | 6                                      | 1.20  | 0.35                                       |
| 15   | B         | 293D156(1)016B(2) | 2.4  | 6                                      | 2.00  | 0.21                                       |
| 15   | C         | 293D156(1)016C(2) | 2.4  | 6                                      | 1.50  | 0.27                                       |
| 22   | B         | 293D226(1)016B(2) | 3.5  | 6                                      | 1.90  | 0.21                                       |
| 22   | C         | 293D226(1)016C(2) | 3.5  | 6                                      | 1.40  | 0.28                                       |
| 22   | D         | 293D226(1)016D(2) | 3.5  | 6                                      | 0.80  | 0.43                                       |
| 33   | B         | 293D336(1)016B(2) | 5.3  | 6                                      | 1.80  | 0.22                                       |
| 33   | C         | 293D336(1)016C(2) | 5.3  | 6                                      | 1.10  | 0.32                                       |
| 33   | D         | 293D336(1)016D(2) | 5.3  | 6                                      | 0.70  | 0.46                                       |
| 47   | C         | 293D476(1)016C(2) | 7.5  | 6                                      | 1.00  | 0.33                                       |
| 47   | D         | 293D476(1)016D(2) | 7.5  | 6                                      | 0.70  | 0.46                                       |
| 47   | E         | 293D476(1)016E(2) | 7.5  | 6                                      | 0.80  | 0.45                                       |
| 68   | D         | 293D686(1)016D(2) | 10.9   | 6                                      | 0.60  | 0.50                                       |
| 68   | E         | 293D686(1)016E(2) | 10.9   | 6                                      | 0.80  | 0.45                                       |
| 100  | D         | 293D107(1)016D(2) | 16.0   | 8                                      | 0.60  | 0.50                                       |
| 100  | E         | 293D107(1)016E(2) | 16.0   | 8                                      | 0.60  | 0.52                                       |
| 100  | V         | 293D107(1)16V(3)  | 16.0   | 10                                     | 0.40  | 0.56                                       |
| 150  | D         | 293D157(1)016D(2) | 24.0   | 8                                      | 0.60  | 0.50                                       |
| 150  | E         | 293D157(1)016E(2) | 24.0   | 8                                      | 0.50  | 0.57                                       |
| 220  | E         | 293D227(1)016E(2) | 35.2   | 14                                     | 0.50  | 0.57                                       |

**Note**

- Part number definitions:
  - Tolerance: X0, X9
  - Terminations and packaging: 2TE3, 2WE3, 8T, 8W
  - Lead (Pb)-free terminations and packaging codes: 2TE3, 2WE3



| STANDARD RATINGS   |           |                   |  |  |   |  |
|--|-----------|-------------------|--|--|---|--|
| CAPACITANCE<br>( $\mu$ F)  | CASE CODE | PART NUMBER       | MAX. DC<br>LEAKAGE<br>AT + 25 °C<br>( $\mu$ A) | MAX. DF<br>AT + 25 °C<br>120 Hz<br>(%) | MAX. ESR<br>AT + 25 °C<br>100 kHz<br>( $\Omega$ ) | MAX. RIPPLE<br>100 kHz<br>$I_{RMS}$<br>(A) |
| <b>20 V<sub>DC</sub> AT + 85 °C; 13 V<sub>DC</sub> AT + 125 °C</b> |           |                   |  |  |   |  |
| 0.47   | A         | 293D474(1)020A(2) | 0.5  | 4                                      | 14.00   | 0.07                                       |
| 0.68   | A         | 293D684(1)020A(2) | 0.5  | 4                                      | 10.00   | 0.09                                       |
| 1.0  | A         | 293D105(1)020A(2) | 0.5  | 4                                      | 8.40  | 0.09                                       |
| 1.0  | B         | 293D105(1)020B(2) | 0.5  | 4                                      | 9.00  | 0.10                                       |
| 1.5  | A         | 293D155(1)020A(2) | 0.5  | 6                                      | 6.30  | 0.11                                       |
| 1.5  | B         | 293D155(1)020B(2) | 0.5  | 4.8                                    | 5.60  | 0.12                                       |
| 2.2  | A         | 293D225(1)020A(2) | 0.5  | 6                                      | 5.90  | 0.11                                       |
| 2.2  | B         | 293D225(1)020B(2) | 0.5  | 6                                      | 3.50  | 0.16                                       |
| 3.3  | A         | 293D335(1)020A(2) | 0.7  | 6                                      | 5.90  | 0.11                                       |
| 3.3  | B         | 293D335(1)020B(2) | 0.7  | 6                                      | 3.00  | 0.17                                       |
| 3.3  | C         | 293D335(1)020C(2) | 0.8  | 6                                      | 2.30  | 0.22                                       |
| 4.7  | A         | 293D475(1)020A(2) | 0.9  | 6                                      | 5.00  | 0.12                                       |
| 4.7  | B         | 293D475(1)020B(2) | 0.9  | 6                                      | 2.90  | 0.17                                       |
| 4.7  | C         | 293D475(1)020C(2) | 0.9  | 6                                      | 2.30  | 0.22                                       |
| 6.8  | A         | 293D685(1)020A(2) | 1.4  | 6                                      | 4.50  | 0.13                                       |
| 6.8  | B         | 293D685(1)020B(2) | 1.4  | 6                                      | 2.50  | 0.18                                       |
| 6.8  | C         | 293D685(1)020C(2) | 1.4  | 6                                      | 1.90  | 0.24                                       |
| 10   | B         | 293D106(1)020B(2) | 2.0  | 6                                      | 2.10  | 0.20                                       |
| 10   | C         | 293D106(1)020C(2) | 2.0  | 6                                      | 1.70  | 0.25                                       |
| 10   | D         | 293D106(1)020D(2) | 2.0  | 6                                      | 1.00  | 0.38                                       |
| 15   | B         | 293D156(1)020B(2) | 3.0  | 6                                      | 2.30  | 0.19                                       |
| 15   | C         | 293D156(1)020C(2) | 3.0  | 6                                      | 1.50  | 0.27                                       |
| 15   | D         | 293D156(1)020D(2) | 3.0  | 6                                      | 0.90  | 0.41                                       |
| 22   | B         | 293D226(1)020B(2) | 4.4  | 6                                      | 2.10  | 0.20                                       |
| 22   | C         | 293D226(1)020C(2) | 4.4  | 6                                      | 1.10  | 0.32                                       |
| 22   | D         | 293D226(1)020D(2) | 4.4  | 6                                      | 0.70  | 0.46                                       |
| 33   | C         | 293D336(1)020C(2) | 6.6  | 6                                      | 1.00  | 0.33                                       |
| 33   | D         | 293D336(1)020D(2) | 6.6  | 6                                      | 0.70  | 0.46                                       |
| 47   | D         | 293D476(1)020D(2) | 9.4  | 6                                      | 0.70  | 0.46                                       |
| 47   | E         | 293D476(1)020E(2) | 9.4  | 6                                      | 0.60  | 0.52                                       |
| 68   | D         | 293D686(1)020D(2) | 13.6   | 6                                      | 0.70  | 0.46                                       |
| 68   | E         | 293D686(1)020E(2) | 13.6   | 6                                      | 0.60  | 0.52                                       |
| 100  | D         | 293D107(1)020D(2) | 20.0   | 8                                      | 0.60  | 0.50                                       |
| 100  | E         | 293D107(1)020E(2) | 20.0   | 8                                      | 0.50  | 0.57                                       |
| <b>25 V<sub>DC</sub> AT + 85 °C; 17 V<sub>DC</sub> AT + 125 °C</b> |           |                   |  |  |   |  |
| 0.10   | A         | 293D104(1)025A(2) | 0.5  | 4                                      | 20.00   | 0.06                                       |
| 0.33   | A         | 293D334(1)025A(2) | 0.5  | 4                                      | 13.00   | 0.08                                       |
| 0.47   | A         | 293D474(1)025A(2) | 0.5  | 4                                      | 12.00   | 0.08                                       |
| 0.68   | A         | 293D684(1)025A(2) | 0.5  | 4                                      | 8.40  | 0.09                                       |
| 1.0  | A         | 293D105(1)025A(2) | 0.5  | 4                                      | 7.60  | 0.10                                       |
| 1.0  | B         | 293D105(1)025B(2) | 0.5  | 4                                      | 5.00  | 0.13                                       |
| 1.5  | A         | 293D155(1)025A(2) | 0.5  | 6                                      | 6.70  | 0.11                                       |
| 1.5  | B         | 293D155(1)025B(2) | 0.5  | 6                                      | 4.60  | 0.14                                       |
| 2.2  | A         | 293D225(1)025A(2) | 0.6  | 6                                      | 6.30  | 0.11                                       |

**Note**

- Part number definitions:
  - Tolerance: X0, X9
  - Terminations and packaging: 2TE3, 2WE3, 8T, 8W
  - Lead (Pb)-free terminations and packaging codes: 2TE3, 2WE3



| STANDARD RATINGS   |           |                   |   |  |   |   |
|--|-----------|-------------------|---|--|---|---|
| CAPACITANCE<br>( $\mu\text{F}$ )                                   | CASE CODE | PART NUMBER       | MAX. DC<br>LEAKAGE<br>AT + 25 °C<br>( $\mu\text{A}$ ) | MAX. DF<br>AT + 25 °C<br>120 Hz<br>(%) | MAX. ESR<br>AT + 25 °C<br>100 kHz<br>( $\Omega$ ) | MAX. RIPPLE<br>100 kHz<br>$I_{\text{RMS}}$<br>(A) |
| <b>25 V<sub>DC</sub> AT + 85 °C; 17 V<sub>DC</sub> AT + 125 °C</b> |           |                   |   |  |   |   |
| 2.2  | B         | 293D225(1)025B(2) | 0.6   | 6                                      | 3.80  | 0.15  |
| 2.2  | C         | 293D225(1)025C(2) | 0.6   | 6                                      | 3.20  | 0.19  |
| 3.3  | A         | 293D335(1)025A(2) | 0.8   | 6                                      | 6.00  | 0.14  |
| 3.3  | B         | 293D335(1)025B(2) | 0.8   | 6                                      | 3.10  | 0.17  |
| 3.3  | C         | 293D335(1)025C(2) | 0.8   | 6                                      | 2.30  | 0.22  |
| 4.7  | A         | 293D475(1)025A(2) | 1.2   | 6                                      | 5.50  | 0.12  |
| 4.7  | B         | 293D475(1)025B(2) | 1.2   | 6                                      | 2.80  | 0.17  |
| 4.7  | C         | 293D475(1)025C(2) | 1.2   | 6                                      | 2.00  | 0.24  |
| 4.7  | D         | 293D475(1)025D(2) | 1.2   | 6                                      | 1.30  | 0.34  |
| 6.8  | B         | 293D685(1)025B(2) | 1.7   | 6                                      | 2.40  | 0.19  |
| 6.8  | C         | 293D685(1)025C(2) | 1.7   | 6                                      | 1.70  | 0.25  |
| 6.8  | D         | 293D685(1)025D(2) | 1.7   | 6                                      | 1.10  | 0.37  |
| 10   | B         | 293D106(1)025B(2) | 2.5   | 6                                      | 2.30  | 0.19  |
| 10   | C         | 293D106(1)025C(2) | 2.5   | 6                                      | 1.50  | 0.27  |
| 10   | D         | 293D106(1)025D(2) | 2.5   | 6                                      | 1.00  | 0.39  |
| 15   | B         | 293D156(1)025B(2) | 3.8   | 6                                      | 2.20  | 0.20  |
| 15   | C         | 293D156(1)025C(2) | 3.8   | 6                                      | 1.20  | 0.30  |
| 15   | D         | 293D156(1)025D(2) | 3.8   | 6                                      | 0.80  | 0.43  |
| 22   | C         | 293D226(1)025C(2) | 5.5   | 6                                      | 1.20  | 0.30  |
| 22   | D         | 293D226(1)025D(2) | 5.5   | 6                                      | 0.70  | 0.46  |
| 22   | E         | 293D226(1)025E(2) | 5.5   | 6                                      | 0.80  | 0.45  |
| 22   | V         | 293D226(1)025V(3) | 5.5   | 6                                      | 0.70  | 0.42  |
| 33   | D         | 293D336(1)025D(2) | 8.3   | 6                                      | 0.70  | 0.46  |
| 33   | E         | 293D336(1)025E(2) | 8.3   | 6                                      | 0.60  | 0.52  |
| 47   | D         | 293D476(1)025D(2) | 11.8  | 8                                      | 0.70  | 0.46  |
| 47   | E         | 293D476(1)025E(2) | 11.8  | 6                                      | 0.60  | 0.52  |
| 68   | E         | 293D686(1)025E(2) | 17.0  | 8                                      | 0.60  | 0.52  |
| <b>35 V<sub>DC</sub> AT + 85 °C; 23 V<sub>DC</sub> AT + 125 °C</b> |           |                   |   |  |   |   |
| 0.10   | A         | 293D104(1)035A(2) | 0.5   | 4                                      | 20.00   | 0.06  |
| 0.15   | A         | 293D154(1)035A(2) | 0.5   | 4                                      | 18.00   | 0.07  |
| 0.22   | A         | 293D224(1)035A(2) | 0.5   | 4                                      | 15.00   | 0.07  |
| 0.33   | A         | 293D334(1)035A(2) | 0.5   | 4                                      | 13.00   | 0.08  |
| 0.47   | A         | 293D474(1)035A(2) | 0.5   | 4                                      | 10.00   | 0.09  |
| 0.47   | B         | 293D474(1)035B(2) | 0.5   | 4                                      | 8.00  | 0.10  |
| 0.68   | A         | 293D684(1)035A(2) | 0.5   | 4                                      | 7.60  | 0.10  |
| 0.68   | B         | 293D684(1)035B(2) | 0.5   | 4                                      | 6.50  | 0.11  |
| 1.0  | A         | 293D105(1)035A(2) | 0.5   | 4                                      | 7.50  | 0.10  |
| 1.0  | B         | 293D105(1)035B(2) | 0.5   | 4                                      | 5.00  | 0.13  |
| 1.5  | B         | 293D155(1)035B(2) | 0.5   | 6                                      | 4.20  | 0.14  |
| 1.5  | C         | 293D155(1)035C(2) | 0.5   | 6                                      | 3.80  | 0.17  |
| 2.2  | B         | 293D225(1)035B(2) | 0.8   | 6                                      | 3.80  | 0.15  |
| 2.2  | C         | 293D225(1)035C(2) | 0.8   | 6                                      | 2.90  | 0.20  |
| 3.3  | B         | 293D335(1)035B(2) | 1.2   | 6                                      | 3.50  | 0.16  |
| 3.3  | C         | 293D335(1)035C(2) | 1.2   | 6                                      | 2.10  | 0.23  |
| 3.3  | D         | 293D335(1)035D(2) | 1.2   | 6                                      | 1.70  | 0.30  |

**Note**

- Part number definitions:
  - Tolerance: X0, X9
  - Terminations and packaging: 2TE3, 2WE3, 8T, 8W
  - Lead (Pb)-free terminations and packaging codes: 2TE3, 2WE3






| STANDARD RATINGS   |           |                   |   |  |   |   |
|--|-----------|-------------------|---|--|---|---|
| CAPACITANCE<br>( $\mu\text{F}$ )                                   | CASE CODE | PART NUMBER       | MAX. DC<br>LEAKAGE<br>AT + 25 °C<br>( $\mu\text{A}$ ) | MAX. DF<br>AT + 25 °C<br>120 Hz<br>(%) | MAX. ESR<br>AT + 25 °C<br>100 kHz<br>( $\Omega$ ) | MAX. RIPPLE<br>100 kHz<br>$I_{\text{RMS}}$<br>(A) |
| <b>35 V<sub>DC</sub> AT + 85 °C; 23 V<sub>DC</sub> AT + 125 °C</b> |           |                   |   |  |   |   |
| 4.7  | B         | 293D475(1)035B(2) | 1.7   | 6                                      | 3.10  | 0.17  |
| 4.7  | C         | 293D475(1)035C(2) | 1.6   | 6                                      | 1.90  | 0.24  |
| 4.7  | D         | 293D475(1)035D(2) | 1.6   | 6                                      | 1.30  | 0.34  |
| 6.8  | C         | 293D685(1)035C(2) | 2.4   | 6                                      | 1.80  | 0.25  |
| 6.8  | D         | 293D685(1)035D(2) | 2.4   | 6                                      | 1.10  | 0.37  |
| 10   | C         | 293D106(1)035C(2) | 3.5   | 6                                      | 1.60  | 0.26  |
| 10   | D         | 293D106(1)035D(2) | 3.5   | 6                                      | 0.80  | 0.43  |
| 15   | D         | 293D156(1)035D(2) | 5.3   | 6                                      | 0.70  | 0.46  |
| 15   | E         | 293D156(1)035E(2) | 5.3   | 6                                      | 0.70  | 0.49  |
| 22   | D         | 293D226(1)035D(2) | 7.7   | 6                                      | 0.60  | 0.50  |
| 22   | E         | 293D226(1)035E(2) | 7.7   | 6                                      | 0.60  | 0.57  |
| <b>50 V<sub>DC</sub> AT + 85 °C; 33 V<sub>DC</sub> AT + 125 °C</b> |           |                   |   |  |   |   |
| 0.10   | A         | 293D104(1)050A(2) | 0.5   | 4                                      | 19.00   | 0.06  |
| 0.15   | A         | 293D154(1)050A(2) | 0.5   | 4                                      | 17.00   | 0.07  |
| 0.15   | B         | 293D154(1)050B(2) | 0.5   | 4                                      | 14.00   | 0.08  |
| 0.22   | A         | 293D224(1)050A(2) | 0.5   | 4                                      | 15.00   | 0.07  |
| 0.22   | B         | 293D224(1)050B(2) | 0.5   | 4                                      | 12.00   | 0.08  |
| 0.33   | A         | 293D334(1)050A(2) | 0.5   | 4                                      | 14.00   | 0.07  |
| 0.33   | B         | 293D334(1)050B(2) | 0.5   | 4                                      | 10.00   | 0.09  |
| 0.47   | A         | 293D474(1)050A(2) | 0.5   | 4                                      | 12.00   | 0.08  |
| 0.47   | B         | 293D474(1)050B(2) | 0.5   | 4                                      | 8.40  | 0.10  |
| 0.47   | C         | 293D474(1)050C(2) | 0.5   | 4                                      | 6.70  | 0.13  |
| 0.68   | B         | 293D684(1)050B(2) | 0.5   | 4                                      | 7.60  | 0.11  |
| 0.68   | C         | 293D684(1)050C(2) | 0.5   | 4                                      | 5.90  | 0.14  |
| 1.0  | B         | 293D105(1)050B(2) | 0.5   | 4                                      | 6.70  | 0.11  |
| 1.0  | C         | 293D105(1)050C(2) | 0.5   | 4                                      | 4.60  | 0.16  |
| 1.5  | B         | 293D155(1)050B(2) | 0.8   | 6                                      | 6.00  | 0.12  |
| 1.5  | C         | 293D155(1)050C(2) | 0.8   | 6                                      | 3.40  | 0.18  |
| 1.5  | D         | 293D155(1)050D(2) | 0.8   | 6                                      | 2.90  | 0.23  |
| 2.2  | B         | 293D225(1)050B(2) | 1.1   | 6                                      | 3.50  | 0.16  |
| 2.2  | C         | 293D225(1)050C(2) | 1.1   | 6                                      | 2.90  | 0.20  |
| 2.2  | D         | 293D225(1)050D(2) | 1.1   | 6                                      | 2.10  | 0.27  |
| 3.3  | C         | 293D335(1)050C(2) | 1.7   | 6                                      | 2.50  | 0.21  |
| 3.3  | D         | 293D335(1)050D(2) | 1.7   | 6                                      | 1.70  | 0.30  |
| 4.7  | C         | 293D475(1)050C(2) | 2.4   | 6                                      | 1.50  | 0.27  |
| 4.7  | D         | 293D475(1)050D(2) | 2.4   | 6                                      | 1.20  | 0.37  |
| 4.7  | E         | 293D475(1)050E(2) | 2.4   | 6                                      | 1.10  | 0.34  |
| 6.8  | D         | 293D685(1)050D(2) | 3.4   | 6                                      | 0.90  | 0.41  |
| 6.8  | E         | 293D685(1)050E(2) | 3.4   | 6                                      | 0.90  | 0.43  |
| 10   | D         | 293D106(1)050D(2) | 5.0   | 6                                      | 0.80  | 0.43  |
| 10   | E         | 293D106(1)050E(2) | 5.0   | 6                                      | 0.80  | 0.45  |
| 15   | E         | 293D156(1)050E(2) | 7.5   | 6                                      | 0.80  | 0.45  |
| <b>63 V<sub>DC</sub> AT + 85 °C; 40 V<sub>DC</sub> AT + 125 °C</b> |           |                   |   |  |   |   |
| 4.7  | D         | 293D475(1)063D(2) | 3.0   | 6                                      | 1.10  | 0.37  |
| 10   | E         | 293D106(1)063E(2) | 6.3   | 6                                      | 1.00  | 0.41  |

**Note**

- Part number definitions:
  - Tolerance: X0, X9
  - Terminations and packaging: 2TE3, 2WE3, 8T, 8W
  - Lead (Pb)-free terminations and packaging codes: 2TE3, 2WE3



| <b>RECOMMENDED VOLTAGE DERATING GUIDELINES</b> (for temperatures below + 85 °C) |                   |
|---|-------------------|
| <b>STANDARD CONDITIONS. FOR EXAMPLE: OUTPUT FILTERS</b>                         |                   |
| Capacitor Voltage Rating  | Operating Voltage |
| 4.0   | 2.5               |
| 6.3   | 3.6               |
| 10  | 6.0               |
| 16  | 10                |
| 20  | 12                |
| 25  | 15                |
| 35  | 24                |
| 50  | 28                |
| 63  | 36                |
| <b>SEVERE CONDITIONS. FOR EXAMPLE: INPUT FILTERS</b>                            |                   |
| Capacitor Voltage Rating  | Operating Voltage |
| 4.0   | 2.5               |
| 6.3   | 3.3               |
| 10  | 5.0               |
| 16  | 8.0               |
| 20  | 10                |
| 25  | 12                |
| 35  | 15                |
| 50  | 24                |
| 63  | 31                |





| POWER DISSIPATION |  |
|-------------------|--|
| CASE CODE         | MAXIMUM PERMISSIBLE POWER DISSIPATION AT + 25 °C (W) IN FREE AIR |
| A                 | 0.075  |
| B                 | 0.085  |
| C                 | 0.110  |
| D                 | 0.150  |
| E                 | 0.165  |
| V                 | 0.125  |

| STANDARD PACKAGING QUANTITY |                |          |
|-----------------------------|----------------|----------|
| CASE CODE                   | UNITS PER REEL |          |
|                             | 7" REEL        | 13" REEL |
| A                           | 2000           | 9000     |
| B                           | 2000           | 8000     |
| C                           | 500            | 3000     |
| D                           | 500            | 2500     |
| E                           | 400            | 1500     |
| V                           | 1000           | 5000     |

| PRODUCT INFORMATION                  |  |
|--------------------------------------|--|
| Guide for Molded Tantalum Capacitors | <a href="http://www.vishay.com/doc?40074">www.vishay.com/doc?40074</a> |
| Pad Dimensions                       |  |
| Packaging Dimensions                 |  |
| Moisture Sensitivity                 | <a href="http://www.vishay.com/doc?40135">www.vishay.com/doc?40135</a> |
| SELECTOR GUIDES                      |  |
| Solid Tantalum Selector Guide        | <a href="http://www.vishay.com/doc?49053">www.vishay.com/doc?49053</a> |
| Solid Tantalum Chip Capacitors       | <a href="http://www.vishay.com/doc?40091">www.vishay.com/doc?40091</a> |
| FAQ                                  |  |
| Frequently Asked Questions           | <a href="http://www.vishay.com/doc?40110">www.vishay.com/doc?40110</a> |



## Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

## Material Category Policy

**Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as RoHS-Compliant fulfill the definitions and restrictions defined under Directive 2011/65/EU of The European Parliament and of the Council of June 8, 2011 on the restriction of the use of certain hazardous substances in electrical and electronic equipment (EEE) - recast, unless otherwise specified as non-compliant.**

**Please note that some Vishay documentation may still make reference to RoHS Directive 2002/95/EC. We confirm that all the products identified as being compliant to Directive 2002/95/EC conform to Directive 2011/65/EU.**

**Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as Halogen-Free follow Halogen-Free requirements as per JEDEC JS709A standards. Please note that some Vishay documentation may still make reference to the IEC 61249-2-21 definition. We confirm that all the products identified as being compliant to IEC 61249-2-21 conform to JEDEC JS709A standards.**