


DATA SHEET



BZX84 series Voltage regulator diodes

Product data sheet
Supersedes data of 1999 May 18

2003 Apr 10

Voltage regulator diodes

BZX84 series

FEATURES

- Total power dissipation: max. 250 mW
- Three tolerance series: $\pm 1\%$, $\pm 2\%$ and approx. $\pm 5\%$
- Working voltage range: nom. 2.4 to 75 V (E24 range)
- Non-repetitive peak reverse power dissipation: max. 40 W.

APPLICATIONS

- General regulation functions.


DESCRIPTION

Low-power voltage regulator diodes in small SOT23 plastic SMD packages.

The diodes are available in the normalized E24 $\pm 1\%$ (BZX84-A), $\pm 2\%$ (BZX84-B) and approx. $\pm 5\%$ (BZX84-C) tolerance range. The series consists of 37 types with nominal working voltages from 2.4 to 75 V.

PINNING

| PIN | DESCRIPTION |
|-----|---------------|
| 1 | anode |
| 2 | not connected |
| 3 | cathode |



Voltage regulator diodes

BZX84 series

MARKING

| TYPE NUMBER | MARKING CODE ⁽¹⁾ | TYPE NUMBER | MARKING CODE ⁽¹⁾ | TYPE NUMBER | MARKING CODE ⁽¹⁾ | TYPE NUMBER | MARKING CODE ⁽¹⁾ |
|--|-----------------------------|-------------|-----------------------------|-------------|-----------------------------|-------------|-----------------------------|
| Marking codes for BZX84-A2V4 to BZX84-A75 | | | | | | | |
| BZX84-A2V4 | Y50 or *50 | BZX84-A6V2 | Y60 or *60 | BZX84-A16 | Y70 | BZX84-A43 | Y80 or *C5 |
| BZX84-A2V7 | Y51 or *51 | BZX84-A6V8 | Y61 or *61 | BZX84-A18 | Y71 | BZX84-A47 | Y81 |
| BZX84-A3V0 | Y52 or *52 | BZX84-A7V5 | Y62 or *62 | BZX84-A20 | Y72 or *C2 | BZX84-A51 | Y82 or *C6 |
| BZX84-A3V3 | Y53 | BZX84-A8V2 | Y63 or *63 | BZX84-A22 | Y73 | BZX84-A56 | Y83 |
| BZX84-A3V6 | Y54 or *C1 | BZX84-A9V1 | Y64 or *64 | BZX84-A24 | Y74 | BZX84-A62 | Y84 |
| BZX84-A3V9 | Y55 or *55 | BZX84-A10 | Y65 or *65 | BZX84-A27 | Y75 or *75 | BZX84-A68 | Y85 |
| BZX84-A4V3 | Y56 or *56 | BZX84-A11 | Y66 or *04 | BZX84-A30 | Y76 | BZX84-A75 | Y86 or *86 |
| BZX84-A4V7 | Y57 or *57 | BZX84-A12 | Y67 or *67 | BZX84-A33 | Y77 | – | – |
| BZX84-A5V1 | Y58 or *58 | BZX84-A13 | Y68 or *C0 | BZX84-A36 | Y78 or *C3 | – | – |
| BZX84-A5V6 | Y59 or *59 | BZX84-A15 | Y69 or *69 | BZX84-A39 | Y79 or *C4 | – | – |
| Marking codes for BZX84-B2V4 to BZX84-B75 | | | | | | | |
| BZX84-B2V4 | Z50 or *Z0 | BZX84-B6V2 | Z60 or *R5 | BZX84-B16 | Z70 or *70 | BZX84-B43 | Z80 or *S5 |
| BZX84-B2V7 | Z51 or *Z1 | BZX84-B6V8 | Z61 or *R6 | BZX84-B18 | Z71 or *71 | BZX84-B47 | Z81 or *S6 |
| BZX84-B3V0 | Z52 or *S1 | BZX84-B7V5 | Z62 or *R8 | BZX84-B20 | Z72 or *72 | BZX84-B51 | Z82 or *S9 |
| BZX84-B3V3 | Z53 or *S2 | BZX84-B8V2 | Z63 or *R9 | BZX84-B22 | Z73 or *73 | BZX84-B56 | Z83 or *R0 |
| BZX84-B3V6 | Z54 or *S3 | BZX84-B9V1 | Z64 or *T1 | BZX84-B24 | Z74 or *74 | BZX84-B62 | Z84 or *R3 |
| BZX84-B3V9 | Z55 or *S4 | BZX84-B10 | Z65 or *66 | BZX84-B27 | Z75 or *Z5 | BZX84-B68 | Z85 or *R4 |
| BZX84-B4V3 | Z56 or *S7 | BZX84-B11 | Z66 or *Z6 | BZX84-B30 | Z76 or *Z4 | BZX84-B75 | Z86 or *R7 |
| BZX84-B4V7 | Z57 or *S8 | BZX84-B12 | Z67 or *Z7 | BZX84-B33 | Z77 or *Y1 | – | – |
| BZX84-B5V1 | Z58 or *R1 | BZX84-B13 | Z68 or *Z8 | BZX84-B36 | Z78 or *Y2 | – | – |
| BZX84-B5V6 | Z59 or *R2 | BZX84-B15 | Z69 or *Z9 | BZX84-B39 | Z79 or *S0 | – | – |
| Marking codes for BZX84-C2V4 to BZX84-C75 | | | | | | | |
| BZX84-C2V4 | Z11 or *T3 | BZX84-C6V2 | Z4* | BZX84-C16 | Y5* | BZX84-C43 | Y15 or *B4 |
| BZX84-C2V7 | Z12 or *T4 | BZX84-C6V8 | Z5* | BZX84-C18 | Y6* | BZX84-C47 | Y16 or *B5 |
| BZX84-C3V0 | Z13 or *T9 | BZX84-C7V5 | Z6* | BZX84-C20 | Y7* | BZX84-C51 | Y17 or *B7 |
| BZX84-C3V3 | Z14 or *B1 | BZX84-C8V2 | Z7* | BZX84-C22 | Y8* | BZX84-C56 | Y18 or *B8 |
| BZX84-C3V6 | Z15 or *B2 | BZX84-C9V1 | Z8* | BZX84-C24 | Y9* | BZX84-C62 | Y19 or *B9 |
| BZX84-C3V9 | Z16 or *B3 | BZX84-C10 | Z9* | BZX84-C27 | Y10 or *T2 | BZX84-C68 | Y20 or *B0 |
| BZX84-C4V3 | Z17 or *B6 | BZX84-C11 | Y1* | BZX84-C30 | Y11 or *T5 | BZX84-C75 | Y21 or *A1 |
| BZX84-C4V7 | Z1* | BZX84-C12 | Y2* | BZX84-C33 | Y12 or *T6 | – | – |
| BZX84-C5V1 | Z2* | BZX84-C13 | Y3* | BZX84-C36 | Y13 or *T7 | – | – |
| BZX84-C5V6 | Z3* | BZX84-C15 | Y4* | BZX84-C39 | Y14 or *T8 | – | – |

Note

- * = p : Made in Hong Kong.
* = t : Made in Malaysia.
* = W : Made in China.

Voltage regulator diodes

BZX84 series

LIMITING VALUES

In accordance with the Absolute Maximum Rating System (IEC 60134).

| SYMBOL | PARAMETER | CONDITIONS | MIN. | MAX. | UNIT |
|-----------|---|---|--------------------|------|------------------|
| I_F | continuous forward current | | – | 200 | mA |
| I_{ZSM} | non-repetitive peak reverse current | $t_p = 100 \mu\text{s}$; square wave; $T_j = 25 \text{ }^\circ\text{C}$ prior to surge | see Tables 1 and 2 | | |
| P_{tot} | total power dissipation | $T_{amb} = 25 \text{ }^\circ\text{C}$; note 1 | – | 250 | mW |
| P_{ZSM} | non-repetitive peak reverse power dissipation | $t_p = 100 \mu\text{s}$; square wave; $T_j = 25 \text{ }^\circ\text{C}$ prior to surge; see Fig.2 | – | 40 | W |
| T_{stg} | storage temperature | | –65 | +150 | $^\circ\text{C}$ |
| T_j | junction temperature | | –65 | +150 | $^\circ\text{C}$ |

Note

1. Device mounted on an FR4 printed circuit-board.

ELECTRICAL CHARACTERISTICS**Total BZX84-A and B and C series** $T_j = 25 \text{ }^\circ\text{C}$ unless otherwise specified.

| SYMBOL | PARAMETER | CONDITIONS | MAX. | UNIT |
|---------------------|---------------------|-----------------------------------|------|---------------|
| V_F | forward voltage | $I_F = 10 \text{ mA}$; see Fig.3 | 0.9 | V |
| I_R | reverse current | | | |
| | BZX84-A/B/C2V4 | $V_R = 1 \text{ V}$ | 50 | μA |
| | BZX84-A/B/C2V7 | $V_R = 1 \text{ V}$ | 20 | μA |
| | BZX84-A/B/C3V0 | $V_R = 1 \text{ V}$ | 10 | μA |
| | BZX84-A/B/C3V3 | $V_R = 1 \text{ V}$ | 5 | μA |
| | BZX84-A/B/C3V6 | $V_R = 1 \text{ V}$ | 5 | μA |
| | BZX84-A/B/C3V9 | $V_R = 1 \text{ V}$ | 3 | μA |
| | BZX84-A/B/C4V3 | $V_R = 1 \text{ V}$ | 3 | μA |
| | BZX84-A/B/C4V7 | $V_R = 2 \text{ V}$ | 3 | μA |
| | BZX84-A/B/C5V1 | $V_R = 2 \text{ V}$ | 2 | μA |
| | BZX84-A/B/C5V6 | $V_R = 2 \text{ V}$ | 1 | μA |
| | BZX84-A/B/C6V2 | $V_R = 4 \text{ V}$ | 3 | μA |
| | BZX84-A/B/C6V8 | $V_R = 4 \text{ V}$ | 2 | μA |
| | BZX84-A/B/C7V5 | $V_R = 5 \text{ V}$ | 1 | μA |
| | BZX84-A/B/C8V2 | $V_R = 5 \text{ V}$ | 700 | nA |
| | BZX84-A/B/C9V1 | $V_R = 6 \text{ V}$ | 500 | nA |
| | BZX84-A/B/C10 | $V_R = 7 \text{ V}$ | 200 | nA |
| BZX84-A/B/C11 | $V_R = 8 \text{ V}$ | 100 | nA | |
| BZX84-A/B/C12 | $V_R = 8 \text{ V}$ | 100 | nA | |
| BZX84-A/B/C13 | $V_R = 8 \text{ V}$ | 100 | nA | |
| BZX84-A/B/C15 to 75 | $V_R = 0.7V_{Znom}$ | 50 | nA | |

Voltage regulator diodes

BZX84 series

Table 1 Per type BZX84-A/B/C2V4 to A/B/C24 $T_j = 25\text{ °C}$ unless otherwise specified.

| BZX84- Axxx Bxxx Cxxx | WORKING VOLTAGE V_z (V) at $I_{ztest} = 5\text{ mA}$ | | | | | | DIFFERENTIAL RESISTANCE r_{dif} (Ω) | | | | TEMP. COEFF. S_z (mV/K) at $I_{ztest} = 5\text{ mA}$ (see Figs 4 and 5) | | | DIODE CAP. C_d (pF) at $f = 1\text{ MHz}$; $V_R = 0\text{ V}$ | NON-REPETITIVE PEAK REVERSE CURRENT I_{zSM} (A) at $t_p = 100\text{ }\mu\text{s}$; $T_{amb} = 25\text{ °C}$ |
|--------------------------------|--|-------|--------------------|-------|-------------------------------|------|--|------|---------------------------------|------|--|------|------|---|---|
| | Tol. $\pm 1\%$ (A) | | Tol. $\pm 2\%$ (B) | | Tol. approx. $\pm 5\%$ (C) | | at $I_{ztest} = 1\text{ mA}$ | | at $I_{ztest} = 5\text{ mA}$ | | MIN. | TYP. | MAX. | MAX. | MAX. |
| | MIN. | MAX. | MIN. | MAX. | MIN. | MAX. | TYP. | MAX. | TYP. | MAX. | | | | | |
| 2V4 | 2.37 | 2.43 | 2.35 | 2.45 | 2.2 | 2.6 | 275 | 600 | 70 | 100 | -3.5 | -1.6 | 0 | 450 | 6.0 |
| 2V7 | 2.67 | 2.73 | 2.65 | 2.75 | 2.5 | 2.9 | 300 | 600 | 75 | 100 | -3.5 | -2.0 | 0 | 450 | 6.0 |
| 3V0 | 2.97 | 3.03 | 2.94 | 3.06 | 2.8 | 3.2 | 325 | 600 | 80 | 95 | -3.5 | -2.1 | 0 | 450 | 6.0 |
| 3V3 | 3.26 | 3.34 | 3.23 | 3.37 | 3.1 | 3.5 | 350 | 600 | 85 | 95 | -3.5 | -2.4 | 0 | 450 | 6.0 |
| 3V6 | 3.56 | 3.64 | 3.53 | 3.67 | 3.4 | 3.8 | 375 | 600 | 85 | 90 | -3.5 | -2.4 | 0 | 450 | 6.0 |
| 3V9 | 3.86 | 3.94 | 3.82 | 3.98 | 3.7 | 4.1 | 400 | 600 | 85 | 90 | -3.5 | -2.5 | 0 | 450 | 6.0 |
| 4V3 | 4.25 | 4.35 | 4.21 | 4.39 | 4.0 | 4.6 | 410 | 600 | 80 | 90 | -3.5 | -2.5 | 0 | 450 | 6.0 |
| 4V7 | 4.65 | 4.75 | 4.61 | 4.79 | 4.4 | 5.0 | 425 | 500 | 50 | 80 | -3.5 | -1.4 | 0.2 | 300 | 6.0 |
| 5V1 | 5.04 | 5.16 | 5.00 | 5.20 | 4.8 | 5.4 | 400 | 480 | 40 | 60 | -2.7 | -0.8 | 1.2 | 300 | 6.0 |
| 5V6 | 5.54 | 5.66 | 5.49 | 5.71 | 5.2 | 6.0 | 80 | 400 | 15 | 40 | -2.0 | 1.2 | 2.5 | 300 | 6.0 |
| 6V2 | 6.13 | 6.27 | 6.08 | 6.32 | 5.8 | 6.6 | 40 | 150 | 6 | 10 | 0.4 | 2.3 | 3.7 | 200 | 6.0 |
| 6V8 | 6.73 | 6.87 | 6.66 | 6.94 | 6.4 | 7.2 | 30 | 80 | 6 | 15 | 1.2 | 3.0 | 4.5 | 200 | 6.0 |
| 7V5 | 7.42 | 7.58 | 7.35 | 7.65 | 7.0 | 7.9 | 30 | 80 | 6 | 15 | 2.5 | 4.0 | 5.3 | 150 | 4.0 |
| 8V2 | 8.11 | 8.29 | 8.04 | 8.36 | 7.7 | 8.7 | 40 | 80 | 6 | 15 | 3.2 | 4.6 | 6.2 | 150 | 4.0 |
| 9V1 | 9.00 | 9.20 | 8.92 | 9.28 | 8.5 | 9.6 | 40 | 100 | 6 | 15 | 3.8 | 5.5 | 7.0 | 150 | 3.0 |
| 10 | 9.90 | 10.10 | 9.80 | 10.20 | 9.4 | 10.6 | 50 | 150 | 8 | 20 | 4.5 | 6.4 | 8.0 | 90 | 3.0 |
| 11 | 10.80 | 11.11 | 10.80 | 11.20 | 10.4 | 11.6 | 50 | 150 | 10 | 20 | 5.4 | 7.4 | 9.0 | 85 | 2.5 |
| 12 | 11.88 | 12.12 | 11.80 | 12.20 | 11.4 | 12.7 | 50 | 150 | 10 | 25 | 6.0 | 8.4 | 10.0 | 85 | 2.5 |
| 13 | 12.87 | 13.13 | 12.70 | 13.30 | 12.4 | 14.1 | 50 | 170 | 10 | 30 | 7.0 | 9.4 | 11.0 | 80 | 2.5 |
| 15 | 14.85 | 15.15 | 14.70 | 15.30 | 13.8 | 15.6 | 50 | 200 | 10 | 30 | 9.2 | 11.4 | 13.0 | 75 | 2.0 |
| 16 | 15.84 | 16.16 | 15.70 | 16.30 | 15.3 | 17.1 | 50 | 200 | 10 | 40 | 10.4 | 12.4 | 14.0 | 75 | 1.5 |
| 18 | 17.82 | 18.18 | 17.60 | 18.40 | 16.8 | 19.1 | 50 | 225 | 10 | 45 | 12.4 | 14.4 | 16.0 | 70 | 1.5 |
| 20 | 19.80 | 20.20 | 19.60 | 20.40 | 18.8 | 21.2 | 60 | 225 | 15 | 55 | 14.4 | 16.4 | 18.0 | 60 | 1.5 |
| 22 | 21.78 | 22.22 | 21.60 | 22.40 | 20.8 | 23.3 | 60 | 250 | 20 | 55 | 16.4 | 18.4 | 20.0 | 60 | 1.25 |
| 24 | 23.76 | 24.24 | 23.50 | 24.50 | 22.8 | 25.6 | 60 | 250 | 25 | 70 | 18.4 | 20.4 | 22.0 | 55 | 1.25 |

Voltage regulator diodes

BZX84 series

Table 2 Per type BZX84-A/B/C27 to A/B/C75 $T_j = 25\text{ °C}$ unless otherwise specified.

| BZX84- Axxx Bxxx Cxxx | WORKING VOLTAGE V_z (V) at $I_{ztest} = 2\text{ mA}$ | | | | | | DIFFERENTIAL RESISTANCE r_{dif} (Ω) | | | | TEMP. COEFF. S_z (mV/K) at $I_{ztest} = 2\text{ mA}$ (see Figs 4 and 5) | | | DIODE CAP. C_d (pF) at $f = 1\text{ MHz}$; $V_R = 0\text{ V}$ | NON-REPETITIVE PEAK REVERSE CURRENT I_{zSM} (A) at $t_p = 100\text{ }\mu\text{s}$; $T_{amb} = 25\text{ °C}$ |
|--------------------------------|--|-------|--------------------|-------|-------------------------------|------|--|------|---------------------------------|------|--|------|------|---|---|
| | Tol. $\pm 1\%$ (A) | | Tol. $\pm 2\%$ (B) | | Tol. approx. $\pm 5\%$ (C) | | at $I_{ztest} = 0.5\text{ mA}$ | | at $I_{ztest} = 2\text{ mA}$ | | MIN. | TYP. | MAX. | MAX. | MAX. |
| | MIN. | MAX. | MIN. | MAX. | MIN. | MAX. | TYP. | MAX. | TYP. | MAX. | MIN. | TYP. | MAX. | MAX. | MAX. |
| 27 | 26.73 | 27.27 | 26.50 | 27.50 | 25.1 | 28.9 | 65 | 300 | 25 | 80 | 21.4 | 23.4 | 25.3 | 50 | 1.0 |
| 30 | 29.70 | 30.30 | 29.40 | 30.60 | 28.0 | 32.0 | 70 | 300 | 30 | 80 | 24.4 | 26.6 | 29.4 | 50 | 1.0 |
| 33 | 32.67 | 33.33 | 32.30 | 33.70 | 31.0 | 35.0 | 75 | 325 | 35 | 80 | 27.4 | 29.7 | 33.4 | 45 | 0.9 |
| 36 | 35.64 | 36.36 | 35.30 | 36.70 | 34.0 | 38.0 | 80 | 350 | 35 | 90 | 30.4 | 33.0 | 37.4 | 45 | 0.8 |
| 39 | 38.61 | 39.39 | 38.20 | 39.80 | 37.0 | 41.0 | 80 | 350 | 40 | 130 | 33.4 | 36.4 | 41.2 | 45 | 0.7 |
| 43 | 42.57 | 43.43 | 42.10 | 43.90 | 40.0 | 46.0 | 85 | 375 | 45 | 150 | 37.6 | 41.2 | 46.6 | 40 | 0.6 |
| 47 | 46.53 | 47.47 | 46.10 | 47.90 | 44.0 | 50.0 | 85 | 375 | 50 | 170 | 42.0 | 46.1 | 51.8 | 40 | 0.5 |
| 51 | 50.49 | 51.51 | 50.00 | 52.00 | 48.0 | 54.0 | 90 | 400 | 60 | 180 | 46.6 | 51.0 | 57.2 | 40 | 0.4 |
| 56 | 55.44 | 56.56 | 54.90 | 57.10 | 52.0 | 60.0 | 100 | 425 | 70 | 200 | 52.2 | 57.0 | 63.8 | 40 | 0.3 |
| 62 | 61.38 | 62.62 | 60.80 | 63.20 | 58.0 | 66.0 | 120 | 450 | 80 | 215 | 58.8 | 64.4 | 71.6 | 35 | 0.3 |
| 68 | 67.32 | 68.68 | 66.60 | 69.40 | 64.0 | 72.0 | 150 | 475 | 90 | 240 | 65.6 | 71.7 | 79.8 | 35 | 0.25 |
| 75 | 74.25 | 75.75 | 73.50 | 76.50 | 70.0 | 79.0 | 170 | 500 | 95 | 255 | 73.4 | 80.2 | 88.6 | 35 | 0.2 |

Voltage regulator diodes

BZX84 series

THERMAL CHARACTERISTICS

| SYMBOL | PARAMETER | CONDITIONS | VALUE | UNIT |
|----------------|---|-------------------|--------------|-------------|
| $R_{th\ j-tp}$ | thermal resistance from junction to tie-point | | 330 | K/W |
| $R_{th\ j-a}$ | thermal resistance from junction to ambient | note 1 | 500 | K/W |





Note

1. Device mounted on an FR4 printed circuit-board.

Voltage regulator diodes

BZX84 series

GRAPHICAL DATA




Voltage regulator diodes

BZX84 series

PACKAGE OUTLINE

Plastic surface mounted package; 3 leads

SOT23



DIMENSIONS (mm are the original dimensions)

| UNIT | A | A ₁ max. | b _p | c | D | E | e | e ₁ | H _E | L _p | Q | v | w |
|------|------------|------------------------|----------------|--------------|------------|------------|-----|----------------|----------------|----------------|--------------|-----|-----|
| mm | 1.1 0.9 | 0.1 | 0.48 0.38 | 0.15 0.09 | 3.0 2.8 | 1.4 1.2 | 1.9 | 0.95 | 2.5 2.1 | 0.45 0.15 | 0.55 0.45 | 0.2 | 0.1 |

| OUTLINE VERSION | REFERENCES | | | EUROPEAN PROJECTION | ISSUE DATE |
|-----------------|------------|----------|------|---------------------|----------------------|
| | IEC | JEDEC | EIAJ | | |
| SOT23 | | TO-236AB | | | 97-02-28 99-09-13 |

Voltage regulator diodes

BZX84 series

DATA SHEET STATUS

| DOCUMENT STATUS ⁽¹⁾ | PRODUCT STATUS ⁽²⁾ | DEFINITION |
|--------------------------------|-------------------------------|---|
| Objective data sheet | Development | This document contains data from the objective specification for product development. |
| Preliminary data sheet | Qualification | This document contains data from the preliminary specification. |
| Product data sheet | Production | This document contains the product specification. |

Notes

1. Please consult the most recently issued document before initiating or completing a design.
2. The product status of device(s) described in this document may have changed since this document was published and may differ in case of multiple devices. The latest product status information is available on the Internet at URL <http://www.nxp.com>.

DISCLAIMERS

General — Information in this document is believed to be accurate and reliable. However, NXP Semiconductors does not give any representations or warranties, expressed or implied, as to the accuracy or completeness of such information and shall have no liability for the consequences of use of such information.

Right to make changes — NXP Semiconductors reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.

Suitability for use — NXP Semiconductors products are not designed, authorized or warranted to be suitable for use in medical, military, aircraft, space or life support equipment, nor in applications where failure or malfunction of an NXP Semiconductors product can reasonably be expected to result in personal injury, death or severe property or environmental damage. NXP Semiconductors accepts no liability for inclusion and/or use of NXP Semiconductors products in such equipment or applications and therefore such inclusion and/or use is at the customer's own risk.

Applications — Applications that are described herein for any of these products are for illustrative purposes only. NXP Semiconductors makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.

Limiting values — Stress above one or more limiting values (as defined in the Absolute Maximum Ratings

System of IEC 60134) may cause permanent damage to the device. Limiting values are stress ratings only and operation of the device at these or any other conditions above those given in the Characteristics sections of this document is not implied. Exposure to limiting values for extended periods may affect device reliability.

Terms and conditions of sale — NXP Semiconductors products are sold subject to the general terms and conditions of commercial sale, as published at <http://www.nxp.com/profile/terms>, including those pertaining to warranty, intellectual property rights infringement and limitation of liability, unless explicitly otherwise agreed to in writing by NXP Semiconductors. In case of any inconsistency or conflict between information in this document and such terms and conditions, the latter will prevail.

No offer to sell or license — Nothing in this document may be interpreted or construed as an offer to sell products that is open for acceptance or the grant, conveyance or implication of any license under any copyrights, patents or other industrial or intellectual property rights.

Export control — This document as well as the item(s) described herein may be subject to export control regulations. Export might require a prior authorization from national authorities.

Quick reference data — The Quick reference data is an extract of the product data given in the Limiting values and Characteristics sections of this document, and as such is not complete, exhaustive or legally binding.

NXP Semiconductors

Customer notification

This data sheet was changed to reflect the new company name NXP Semiconductors. No changes were made to the content, except for the legal definitions and disclaimers.

Contact information

For additional information please visit: **<http://www.nxp.com>**

For sales offices addresses send e-mail to: **salesaddresses@nxp.com**

© NXP B.V. 2009

All rights are reserved. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner.

The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice. No liability will be accepted by the publisher for any consequence of its use. Publication thereof does not convey nor imply any license under patent- or other industrial or intellectual property rights.

Printed in The Netherlands

613514/03/pp11

Date of release: 2003 Apr 10

Document order number: 9397 750 10959

