PSA PASSIVE SYSTEM ALLIANCE
Walsin Technology Corporation

WALSIN
WALSIN ALWAYS AROUND YOU

www.passivecomponent.com

2013 Multilayer Ceramic Capacitors

Product catalog

華新科技股份有限公司
Walsin Technology Corporation

Product Portfolio

Multilayer Ceramic Capacitors (MLCC)

Chip-Resistor

Disc Capacitors

RF Device and High Frequency Inductors

Varistors and SMD-Varistors

IEC-63 Nominal Resistance / Capacitance

E1	100																							
E3	100								220								470							
E6	100				150				220				330				470				680			
E12	100		120		150		180		220		270		330		390		470		560		680		820	
E24	100	110	120	130	150	160	180	200	220	240	270	300	330	360	390	430	470	510	560	620	680	750	820	910
E96	100	102	121	124	147	150	178	182	215	221	261	267	316	324	383	392	464	475	562	576	681	698	825	845
	105	107	127	130	154	158	187	191	226	232	274	280	332	340	402	412	487	499	590	604	715	732	866	887
	110	113	133	137	162	165	196	200	237	243	287	294	348	357	422	432	511	523	619	634	750	768	909	931
	115	118	140	143	169	174	205	210	249	255	301	309	365	374	442	453	536	549	649	665	787	806	953	976

E6: $\sqrt[6]{10} \fallingdotseq 1.46$ E12: $\sqrt[12]{10} \fallingdotseq 1.21$
E1 series resistance: 1Ω, 10Ω, 100Ω, 1000Ω, 10000Ω, 100000Ω

"Vector Graphics by VectorOpenStock.com"

INDEX

Subject **Page**

Quick Product Informationa 1
How To Order and Packaging Dimension/Quantity 2
The Outlines and External Dimensions of Capacitors 3
General Purpose Caps (6.3V~100V) 4
0201 Size Caps (0201 series) 9
Middle & High Voltage Caps (200V~3kV) 10
High Q & Low ESR Caps (HH series) 13
Microwave Caps (RF series) 15
Soft Termination Capacitors (SH series) 17
Open-mode Design Caps (OP series) 21
Capacitor Arrays (0612/ 0508 series) 23
Low Profile Caps (TT series) 24
Low Inductance Caps (0612 series) 25
Safety Certificated Caps X1/Y2 (S2 series) 26
Safety Certificated Caps X2/Y3 (S3 series) 27
Low Distortion Caps (LD series) 28
Automotive Caps Without AEC-Q200 Certification (MG series) 29
Appendix | : Reliability Test Conditions and Requirements 32
Appendix || : General Information 35

*The specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
*This catalog has only typical specifications because there is no space for detailed specifications. Therefore, please approve our product specifications or transact the approval sheet for product specifications before ordering.

■ QUICK PRODUCT INFORMATION

Series	Dielectric	Size	Capacitance	Rated voltage	Page
General Purpose Caps (6.3V~100V)	NPO	0402, 0603, 0805, 1206, 1210, 1812	0.5pF~0.039μF	10V, 16V, 25V, 50V, 100V	5
	X7R	0402, 0603, 0805, 1206, 1210, 1812	100pF~47μF	6.3V, 10V, 16V, 25V, 50V, 100V	
	X5R	0402, 0603, 0805, 1206,1210	0.027μF~100μF	6.3V, 10V, 16V, 25V,50V	
	Y5V	0402, 0603, 0805, 1206, 1210, 1812	0.01μF~100μF	6.3V, 10V, 16V, 25V, 50V, 100V	
0201 Size Caps (0201 series)	NPO	0201	0.3pF~100pF	16V, 25V, 50V	9
	X7R	0201	100pF~0.01μF	6.3V, 10V, 16V, 25V, 50V	
	X5R	0201	1000pF~0.47μF	6.3V, 10V, 16V, 25V, 50V	
Middle & High Voltage Caps (200V~3kV)	NPO	0603, 0805, 1206, 1210, 1808, 1812	0.5pF~6800pF	200V, 250V, 500V, 630V, 1kV, 2kV, 3kV	11
	X7R	0805, 1206, 1210, 1808, 1812	100pF~1μF	200V, 250V, 500V, 630V, 1kV, 2kV, 3kV	
	Y5V	0805, 1206, 1210,1812	0.01μF~0.68μF	200V, 250V	
High Q & Low ESR Caps (HH series)	NPO	0402, 0603,0805	0.5pF~3300pF	16V, 25V, 50V, 100V, 200V, 250V, 500V, 630V	14
Microwave Caps (RF series)	NPO	0201, 0402,0603,0805	0.1pF~100pF	6.3V, 10V, 25V, 50V,100V,250V	16
Soft Termination Capacitors (SH series)	NPO	0603,1206,1210,1808	0.5pF~220pF	10V,16V,25V,50V,100V,200V,250V,500V, 630V,1KV,3KV	18
	X7R	0603, 0805, 1206, 1210, 1808, 1812	100pF~1μF	10V,16V,25V,50V,100V,200V,250V,500V, 630V, 1kV,2kV, 3kV	
Open-mode Design Caps (OP series)	X7R	0805, 1206, 1210, 1812	100pF~1μF	100V, 200V, 250V, 500V	22
Capacitor Arrays (0612/ 0508 series)	NPO	0508 (4x0402), 0612 (4x0603)	10pF~470pF	25V, 50V	23
	X7R	0508 (4x0402), 0612 (4x0603)	180pF~0.1μF	10V, 16V, 25V, 50V	
	Y5V	0612 (4x0603)	0.01μF~0.1μF	16V, 50V	
Low Profile Caps (TT series)	X5R	0603, 0805, 1206, 1210	0.22μF~22μF	6.3V, 10V, 16V, 25V,50V	24
	Y5V	0805, 1206, 1210	1μF~10μF	10V, 16V, 25V, 50V	
Low Inductance Caps (0612 series)	X7R	0612	0.01μF~0.15μF	50V	25
Safety Certificated Caps X1/Y2 (S2 series)	NPO	1808	10pF~150pF	250Vac	26
	X7R	1808, 1812, 2211	100pF~2200pF	250Vac	
Safety Certificated Caps X2/Y3 (S3 series)	NPO	1808	3.9pF~680pF	250Vac	27
	X7R	1808, 1812	180pF~2700pF	250Vac	
Low Distortion Caps (LD series)	X7R / X7E	1206	150pF~0.1μF	100V, 200V, 250V, 350V, 500V, 630V	28
Automotive Caps Without AEC-Q200 Certification (MG series)	NPO	0402, 0603, 0805, 1206, 1210, 1812	0.5pF~0.033μF	10V,16V,25V,50V,100V,200V,250V	29
	X7R	0402, 0603, 0805, 1206, 1210, 1812	100pF~2.2μF	10V,16V,25V,50V,100V,200V,250V	
	X5R	0402, 0603, 0805, 1206, 1210	0.056μF~10μF	6.3V,10V,16V,25V	

■ HOW TO ORDER

Type of MLCC	0805		B	104	K	500	C	T
General Purpose MLCC Middle & High Voltage MLCC 0201 size MLCC	**Size** Inch (mm) : 0201 (0603), 0402 (1005), 0603 (1608), 0805 (2012), 1206 (3216), 1210 (3225), 1808 (4520), 1812 (4532)		**Dielectric** N=NP0 B=X7R D=X7E X=X5R F=Y5V	**Capacitance** Two significant digits followed by no. of zeros. And R is in place of decimal point. R47=0.47pF 0R5=0.5pF 1R0=1pF 100=10pF 101=100pF 102=1000pF 103=0.01uF 104=0.1uF 105=1uF 106=10uF 107=100uF	**Tolerance** A= ±0.05pF B= ±0.1pF C= ±0.25pF D= ±0.5pF F= ±1% G= ±2% J= ±5% K= ±10% M= ±20% Z=-20/+80%	**Rated voltage** Two significant digits followed by no. of zeros. And R is in place of decimal point. 4R0=4 Vdc 6R3=6.3 Vdc 100=10 Vdc 160=16 Vdc 250=25 Vdc 500=50 Vdc 101=100 Vdc 201=200 Vdc 251=250 Vdc 501=500 Vdc 631=630 Vdc 102=1k Vdc 202=2k Vdc 302=3k Vdc 502=5k Vdc	**Termination** L=Ag/Ni/Sn C=Cu/Ni/Sn Termination	**Packaging** B=Bulk C=Bulk cassette T=7" reeled Q=10" reeled G=13" reeled
Low Inductance MLCC	0612 (1632)							
High Q / Low ESR MLCC Microwave MLCC Low Profile MLCC Open Mode MLCC Safety Certificated MLCC Low Distortion MLCC Automotive MLCC	**RF** **Series** HH=High Q/ Low ESR RF=Microwave TT=Low profile OP=Open-mode design S2=X1/Y2 safety class S3=X2/Y3 safety class LD= Low distortion MG=Automotive Cap. without AEC-Q200	**03** **Size** Inch : 03=0201 15=0402 18=0603 21=0805 12=0508 31=1206 32=1210 42=1808 43=1812 52=2211					L=Ag/Ni/Sn C=Cu/Ni/Sn P=Cu/Polymer Ag/Ni/Sn	
Soft Termination MLCC	SH=Soft termination						C=Cu/Polymer Ag/Ni/Sn	
Cap Arrays MLCC	**Y** **Type** Y=Capacitor array	**4 C** **Cap. Nr.** 4C=4xCap	**3** **Termination pitch** 3=0.03 inch 2=0.02 inch				C=Cu/Ni/Sn	

* The packaging code per each size of reel, please refer to following table "packaging style and quantity".

■ PACKAGING STYLE AND QUANTITY

Size	Thickness (mm)/Symbol		Paper tape		Plastic tape	
			7" reel	13" reel	7" reel	13" reel
0201 (0603)	0.30±0.03	L	15,000	70,000	-	-
0402 (1005)	0.50±0.05	N	10,000	50,000	-	-
	0.50+0.02/-0.05	Q	10,000	50,000	-	-
	0.50±0.20	E	10,000	-	-	-
0603 (1608)	0.50±0.10	H	4,000	-	-	-
	0.80±0.07	S	4,000	15,000	-	-
	0.80+0.15/-0.10	X	4,000	15,000	-	-
0805 (2012)	0.50±0.10	H	4,000	15,000	-	-
	0.60±0.10	A	4,000	15,000	-	-
	0.80±0.10	B	4,000	15,000	-	-
	0.85±0.10	T	4,000	15,000	-	-
	1.25±0.10	D	-	-	3,000	10,000
	1.25±0.20	I	-	-	3,000	10,000
1206 (3216)	0.80±0.10	B	4,000	15,000	-	-
	0.85±0.10	T	4,000	15,000	-	-
	0.95±0.10	C	-	-	3,000	10,000
	1.15±0.15	J	-	-	3,000	10,000
	1.25±0.10	D	-	-	3,000	10,000
	1.60±0.20	G	-	-	2,000	10,000
	1.60+0.30/-0.10	P	-	-	2,000	9,000
1210 (3225)	0.85±0.10	T	-	-	4,000	10,000
	0.95±0.10	C	-	-	3,000	10,000
	1.25±0.10	D	-	-	3,000	10,000
	1.60±0.20	G	-	-	2,000	-
	2.00±0.20	K	-	-	1,000	6,000
	2.50±0.30	M	-	-	1,000	6,000
1808 (4520)	1.25±0.10	D	-	-	2,000	10,000
	1.10±0.15	F	-	-	2,000	10,000
	1.60±0.20	G	-	-	2,000	8,000
	2.00±0.20	K	-	-	1,000	6,000
1812 (4532)	1.25±0.10	D	-	-	1,000	5,000
	1.60±0.20	G	-	-	1,000	-
	2.00±0.20	K	-	-	1,000	-
	2.50±0.30	M	-	-	500	3,000
	2.80±0.30	U	-	-	500	-

Unit: pieces

The Outlines and External Dimensions of Capacitor

■ SINGLE CHIP CAPACITORS

Size Inch (mm)	L (mm)	W (mm)	T (mm)/Symbol		SolderingMethod *	MB (mm)
0201 (0603)	0.6±0.03	0.3±0.03	0.3±0.03	L	R	0.15±0.05
0402 (1005)	1.00±0.05	0.50±0.05	0.50±0.05	N	R	0.25+0.05/-0.10
			0.50+0.02/-0.05	Q	R	
	1.00±0.20	0.50±0.20	0.50±0.20	E	R	
0603 (1608)	1.60±0.10	0.80±0.10	0.80±0.07	S	R / W	0.40±0.15
	1.60+0.15/-0.10	0.80+0.15/-0.10	0.50±0.10	H	R / W	
			0.80+0.15/-0.10	X	R / W	
	1.60±0.20#1	0.80±0.20#1	0.80±0.20#1			
0805 (2012)	2.00±0.15	1.25±0.10	0.50±0.10	H	R / W	0.50±0.20
			0.60±0.10	A	R / W	
			0.80±0.10	B	R / W	
			1.25±0.10	D	R	
	2.00±0.20	1.25±0.20	0.85±0.10	T	R / W	
			1.25±0.20	I	R	
1206 (3216)	3.20±0.15	1.60±0.15	0.80±0.10	B	R / W	0.60±0.20 (0.5±0.25)***
			0.95±0.10	C	R	
			1.25±0.10	D	R	
	3.20±0.20		1.15±0.15	J	R	
		1.60±0.20	1.60±0.20	G	R	
			0.85±0.10	T	R / W	
	3.20 +0.30/-0.10	1.60 +0.30/0.10	1.60+0.30/-0.10	P	R	
1210 (3225)	3.20±0.30	2.50±0.20	0.95±0.10	C	R	0.75±0.25
			0.85±0.10	T	R	
			1.25±0.10	D	R	
	3.20±0.40	2.50±0.30	1.60±0.20	G	R	
			2.00±0.20	K	R	
			2.50±0.30	M	R	
1808 (4520)	4.50±0.40 (4.5+0.5/-0.3)**	2.03±0.25	1.25±0.10	D	R	0.75±0.25 (0.5±0.25)***
			1.40±0.15	F	R	
			1.60±0.20	G	R	
			2.00±0.20	K	R	
1812 (4532)	4.50±0.40 (4.5+0.5/-0.3)**	3.20±0.30	1.25±0.10	D	R	0.75±0.25 (0.5±0.25)***
			1.60±0.20	G	R	
			2.00±0.20	K	R	
		3.20±0.40	2.50±0.30	M	R	
			2.80±0.30	U	R	

* R = Reflow soldering process ; W = Wave soldering process.

** For 1808_200~3kV, 1812_200V~3kV and safety certificated products.

*** For 1206_1000V ~3kV, 1808_200~3kV, 1812_200~3kV and safety certificated products.

#1 : For 0603/X5R/6.3V/Cap≥10μF products.

Soft termination product please refer to individual sheet for detail.

■ Capacitor Arrays

Size Inch (mm)	L (mm)	W (mm)	T (mm)/ Symbol		S (mm)	BW (mm)	P (mm)
0603 x 4 (0612 (1632)	3.20±0.15	1.60±0.15	0.80±0.10	B	0.30±0.20	0.40±0.15	0.80±0.15
0402 x 4 (0508 (1220)	2.00±0.15	1.25±0.15	0.85±0.10	T	0.20±0.10	0.25±0.10	0.50±0.10

Reflow soldering process only.

■ Low Inductance Capacitors / RF series

Size Inch (mm)	L (mm)	W (mm)	T (mm)/Symbol		Ta min. (mm)	Tb min. (mm)
0612 (1632)	3.20±0.15	1.60±0.15	0.80±0.10	B	0.5	0.13
0508 (1220)	2.00±0.15	1.25±0.15	0.85±0.10	T	0.38	0.13

Reflow soldering process only.

■ FEATURES

* A wide selection of sizes is available (0402 to 1812).
* High capacitance in given case size.
* Capacitor with lead-free termination (pure Tin).

■ GENERAL ELECTRICAL DATA

Dielectric	NP0	X7R	X5R	Y5V
Size	0402, 0603, 0805, 1206, 1210, 1812			
Capacitance range	0.5pF to 0.039μF	100pF to 47μF	0.027μF to 100μF	0.01μF to 100μF
Capacitance tolerance	Cap≤5pF: B (±0.1pF), C (±0.25pF) 5pF<Cap<10pF: C (±0.25pF), D (±0.5pF) Cap≥10pF: F (±1%), G (±2%), J (±5%),K (±10%)	J (±5%), K (±10%), M (±20%)	K (±10%), M (±20%)	M (±20%), Z (-20/+80%)
Rated voltage (WVDC)	10V, 16V, 25V, 50V, 100V	6.3V, 10V, 16V, 25V, 50V, 100V		
Insulation resistance at Ur	≥10GΩ or RxC≥500Ω-F whichever is less			
Operating temperature	-55 to +125°C		-55 to +85°C	-25 to +85°C
Capacitance characteristic	±30ppm	±15%	±15%	+30/-80%
Termination	Ni/Sn (lead-free termination)			

■ EXPLANATION OF PART NUMBERS

1206	F	104	Z	500	C	T
Size (Inch (mm)) 1206 (3216)	**Dielectric** F=Y5V	**Capacitance** 104=10x10^4=100nF	**Tolerance** Z=-20/+80%	**Rated voltage** 500=50 VDC	**Termination** C=Cu/Ni/Sn	**Packaging style** T=7" reeled

Please refer to page 2 " How to order" for more information.

■ ELECTRICAL CHARACTERISTICS

1) Frequency characteristics

2) Capacitance Change - Typical aging rate

3) Temperature characteristics of capacitance (TCC)

4) DC Bias characteristics

■ CAPACITANCE RANGE

NP0 Dielectric

Dielectric		NP0																												
Size		0402					0603					0805					1206					1210					1812		
Rated Voltage (VDC)		10	16	25	50	100	10	16	25	50	100	10	16	25	50	100	10	16	25	50	100	10	16	25	50	100	16	50	100
capacitance	0.5pF (0R5)		N			N		S			S	A		A		A													
	0.6pF (0R6)		N			N		S			S	A		A		A													
	0.7pF (0R7)		N			N		S			S	A		A		A													
	0.8pF (0R8)		N			N		S			S	A		A		A													
	0.9pF (0R9)		N			N		S			S	A		A		A													
	1.0pF (1R0)		N			N		S			S	A		A		A													
	1.2pF (1R2)		N			N		S			S	A		A		A	B		B		B								
	1.5pF (1R5)		N			N		S			S	A		A		A	B		B		B								
	1.8pF (1R8)		N			N		S			S	A		A		A	B		B		B								
	2.2pF (2R2)		N			N		S			S	A		A		A	B		B		B								
	2.7pF (2R7)		N			N		S			S	A		A		A	B		B		B								
	3.3pF (3R3)		N			N		S			S	A		A		A	B		B		B								
	3.9pF (3R9)		N			N		S			S	A		A		A	B		B		B								
	4.7pF (4R7)		N			N		S			S	A		A		A	B		B		B								
	5.6pF (5R6)		N			N		S			S	A		A		A	B		B		B								
	6.8pF (6R8)		N			N		S			S	A		A		A	B		B		B								
	8.2pF (8R2)		N			N		S			S	A		A		A	B		B		B								
	10pF (100)		N			N		S			S	A		A		A	B		B		B	C		C		C	D		D
	12pF (120)		N			N		S			S	A		A		A	B		B		B	C		C		C	D		D
	15pF (150)		N			N		S			S	A		A		A	B		B		B	C		C		C	D		D
	18pF (180		N			N		S			S	A		A		A	B		B		B	C		C		C	D		D
	22pF (220)		N			N		S			S	A		A		A	B		B		B	C		C		C	D		D
	27pF (270)		N			N		S			S	A		A		A	B		B		B	C		C		C	D		D
	33pF (330)		N			N		S			S	A		A		A	B		B		B	C		C		C	D		D
	39pF (390)		N			N		S			S	A		A		A	B		B		B	C		C		C	D		D
	47pF (470)		N			N		S			S	A		A		A	B		B		B	C		C		C	D		D
	56pF (560)		N			N		S			S	A		A		A	B		B		B	C		C		C	D		D
	68pF (680)		N			N		S			S	A		A		A	B		B		B	C		C		C	D		D
	82pF (820)		N			N		S			S	A		A		A	B		B		B	C		C		C	D		D
	100pF (101)		N			N		S			S	A		A		A	B		B		B	C		C		C	D		D
	120pF (121)		N			N		S			S	A		A		A	B		B		B	C		C		C	D		D
	150pF (151)		N			N		S			S	A		A		A	B		B		B	C		C		C	D		D
	180pF (181)		N			N		S			S	A		A		A	B		B		B	C		C		C	D		D
	220pF (221)		N			N		S			S	A		A		A	B		B		B	C		C		C	D		D
	270pF (271)		N					S			S	A		A		A	B		B		B	C		C		C	D		D
	330pF (331)		N					S			S	A		A		A	B		B		B	C		C		C	D		D
	390pF (391)		N					S			S	B		B		B	B		B		B	C		C		C	D		D
	470pF (471)		N					S			S	B		B		B	B		B		B	C		C		C	D		D
	560pF (561)		N					S			S	B		B		B	B		B		B	C		C		C	D		D
	680pF (681)		N					S			S	B		B		B	B		B		B	C		C		C	D		D
	820pF (821)		N					S			S	B		B		B	B		B		B	C		C		C	D		D
	1,000pF (102)		N					S			S	B		B		B	B		B		B	C		C		C	D		D
	1,200pF (122)							X				B		B		B	B		B		B	C		C		C	D		D
	1,500pF (152)							X				B		B		B	B		B		B	C		C		C	D		D
	1,800pF (182)							X				B		B		B	B		B		B	C		C		C	D		D
	2,200pF (222)							X				B		B		B	B		B		B	C		C		C	D		D
	2,700pF (272)							X				D		D		D	B		B		B	C		C		C	D		D
	3,300pF (332)							X				D		D		D	B		B		B	C		C		C	D		D
	3,900pF (392)											D		D		D	B		B		B	C		C		C	D		D
	4,700pF (472)											D		D		D	B		B		B	C		C		C	D		D
	5,600pF (562)											D		D			B		B		B	C		C		C	D		D
	6,800pF (682)											D		D			C		C		C	C		C		C	D		D
	8,200pF (822)											D		D			D		D		D	C		C		C	D		D
	0.010uF (103)											D		D			D		D		D	C		C		C	D		D
	0.012uF (123)																D^					C		D		D	D		D
	0.015uF (153)																D^					C		D		D	D		D
	0.018uF (183)																D^										D		D
	0.022uF (223)																D^										D		D
	0.027uF (273)																D^										D		D
	0.033uF (333)																D^										D		D
	0.039uF (393)																G^												

1. The letter in cell is expressed the symbol of product thickness.
2. The letter in cell with "^" mark is expressed product with Ag/Ni/Sn terminations.
3. For more information about products with special capacitance or other data, please contact WTC local representative.

X7R Dielectric

Dielectric	X7R																																
Size	0402				0603						0805						1206						1210					1812				
Rated Voltage (VDC)	10	16	25	50	6.3	10	16	25	50	100	6.3	10	16	25	50	100	6.3	10	16	25	50	100	10	16	25	50	100	10	16	25	50	100
capacitance																																	
100pF (101)	N		N	N		S	S	S	S	S		B	B	B	B	B																	
120pF (121)	N		N	N		S	S	S	S	S		B	B	B	B	B																	
150pF (151)	N		N	N		S	S	S	S	S		B	B	B	B	B		B	B	B	B	B											
180pF (181)	N		N	N		S	S	S	S	S		B	B	B	B	B		B	B	B	B	B											
220pF (221)	N		N	N		S	S	S	S	S		B	B	B	B	B		B	B	B	B	B											
270pF (271)	N		N	N		S	S	S	S	S		B	B	B	B	B		B	B	B	B	B											
330pF (331)	N		N	N		S	S	S	S	S		B	B	B	B	B		B	B	B	B	B											
390pF (391)	N		N	N		S	S	S	S	S		B	B	B	B	B		B	B	B	B	B											
470pF (471)	N		N	N		S	S	S	S	S		B	B	B	B	B		B	B	B	B	B											
560pF (561)	N		N	N		S	S	S	S	S		B	B	B	B	B		B	B	B	B	B											
680pF (681)	N		N	N		S	S	S	S	S		B	B	B	B	B		B	B	B	B	B											
820pF (821)	N		N	N		S	S	S	S	S		B	B	B	B	B		B	B	B	B	B											
1,000pF (102)	N		N	N		S	S	S	S	S		B	B	B	B	B		B	B	B	B	B	C	C	C	C	C	D	D	D	D	D
1,200pF (122)	N		N	N		S	S	S	S	S		B	B	B	B	B		B	B	B	B	B	C	C	C	C	C	D	D	D	D	D
1,500pF (152)	N		N	N		S	S	S	S	S		B	B	B	B	B		B	B	B	B	B	C	C	C	C	C	D	D	D	D	D
1,800pF (182)	N		N	N		S	S	S	S	S		B	B	B	B	B		B	B	B	B	B	C	C	C	C	C	D	D	D	D	D
2,200pF (222)	N		N	N		S	S	S	S	S		B	B	B	B	B		B	B	B	B	B	C	C	C	C	C	D	D	D	D	D
2,700pF (272)	N		N	N		S	S	S	S	S		B	B	B	B	B		B	B	B	B	B	C	C	C	C	C	D	D	D	D	D
3,300pF (332)	N		N	N		S	S	S	S	S		B	B	B	B	B		B	B	B	B	B	C	C	C	C	C	D	D	D	D	D
3,900pF (392)	N		N	N		S	S	S	S	S		B	B	B	B	B		B	B	B	B	B	C	C	C	C	C	D	D	D	D	D
4,700pF (472)	N		N	N		S	S	S	S	S		B	B	B	B	B		B	B	B	B	B	C	C	C	C	C	D	D	D	D	D
5,600pF (562)	N		N	N		S	S	S	S	S		B	B	B	B	B		B	B	B	B	B	C	C	C	C	C	D	D	D	D	D
6,800pF (682)	N		N	N		S	S	S	S	S		B	B	B	B	B		B	B	B	B	B	C	C	C	C	C	D	D	D	D	D
8,200pF (822)	N		N	N		S	S	S	S	S		B	B	B	B	B		B	B	B	B	B	C	C	C	C	C	D	D	D	D	D
0.010uF (103)	N		N	N		S	S	S	S	S		B	B	B	B	B		B	B	B	B	B	C	C	C	C	C	D	D	D	D	D
0.012uF (123)	N		N			S	S	S	S			B	B	B	B	B		B	B	B	B	B	C	C	C	C	C	D	D	D	D	D
0.015uF (153)	N		N			S	S	S	S			B	B	B	B	B		B	B	B	B	B	C	C	C	C	C	D	D	D	D	D
0.018uF (183)	N		N			S	S	S	S			B	B	B	B	B		B	B	B	B	B	C	C	C	C	C	D	D	D	D	D
0.022uF (223)	N		N			S	S	S	S			B	B	B	B	B		B	B	B	B	B	C	C	C	C	C	D	D	D	D	D
0.027uF (273)	N		N			S	S	S	S			B	B	B	B	D		B	B	B	B	B	C	C	C	C	C	D	D	D	D	D
0.033uF (333)	N		N			S	S	S	X			B	B	B	B	D		B	B	B	B	B	C	C	C	C	C	D	D	D	D	D
0.039uF (393)	N		N			S	S	S	X			B	B	B	B	D		B	B	B	B	B	C	C	C	C	C	D	D	D	D	D
0.047uF (473)	N		N			S	S	S	X			B	B	B	B	D		B	B	B	B	B	C	C	C	C	C	D	D	D	D	D
0.056uF (563)	N					S	S	S	X			B	B	B	B	D		B	B	B	B	B	C	C	C	C	C	D	D	D	D	D
0.068uF (683)	N					S	S	S	X			B	B	B	B	D		B	B	B	B	B	C	C	C	C	C	D	D	D	D	D
0.082uF (823)	N					S	S	S	X			B	B	B	B	D		B	B	B	B	D	C	C	C	C	C	D	D	D	D	D
0.10uF (104)	N		N			S	S	S	X			B	B	B	B	D		B	B	B	B	D	C	C	C	C	C	D	D	D	D	D
0.12uF (124)						S	S	X				D	D	D	D			B	B	B	B	D	C	C	C	C	C	D	D	D	D	D
0.15uF (154)						S	S	X				D	D	D	D			C	C	C	C	G	C	C	C	C	D	D	D	D	D	D
0.18uF (184)						S	S	X				D	D	D	D			C	C	C	C	G	C	C	C	C	D	D	D	D	D	D
0.22uF (224)	N					S	S	X				D	D	D	D			C	C	C	C	G	C	C	C	C	D	D	D	D	D	D
0.27uF (274)					X	X	X	X				D	D	D	I			C	C	C	D	G	C	C	C	C	G	D	D	D	D	D
0.33uF (334)					X	X	X	X				D	D	D	I			C	C	C	D	G	C	C	C	D	G	D	D	D	D	D
0.39uF (394)					X	X	X	X				D	D	D	I			C	C	J	P	G	C	C	C	D	M	D	D	D	D	D
0.47uF (474)					X	X	X	X				D	D	D	I			J	J	J	P	G	C	C	C	D	M	D	D	D	D	K
0.56uF (564)					X	X	X					D	D	D				J	J	J	P	P	D	D	D	D	M	D	D	D	D	K
0.68uF (684)					X	X	X					D	D	D				J	J	J	P	P	D	D	D	D	K	D	D	D	K	K
0.82uF (824)					X	X	X					D	D	D				J	J	J	P	P	D	D	D	D	K	D	D	D	K	K
1.0uF (105)					X	X	X	X				D	D	D	I			J	J	J	P	P	D	D	D	D	K	D	D	D	K	K
1.5uF (155)												I	I	I			J	J	J	P							M					K
2.2uF (225)						X					I	I	I	I			J	J	J	P	P			K	G		M				M	M
3.3uF (335)																	P	P	P	P					G							
4.7uF (475)											I	I	I				P	P	P	P	P		K	K	K	M						
6.8uF (685)																																
10uF (106)											I	I					P	P	P	P			K	K	K	M						
22uF (226)																		P						M	M							
47uF (476)																							M									

1. The letter in cell is expressed the symbol of product thickness.
2. For more information about products with special capacitance or other data, please contact WTC local representative.

General Purpose Capacitors 6.3V~100V

Y5V Dielectric (0402, 0603, 0805 Size)

Dielectric		Y5V															
Size		0402					0603					0805					
Rated Voltage (VDC)		6.3	10	16	25	50	6.3	10	16	25	50	6.3	10	16	25	50	100
capacitance	0.010uF (103)		N	N	N	N		S	S	S	S		A	A	A	A	B
	0.015uF (153)		N	N	N	N		S	S	S	S		A	A	A	A	B
	0.022uF (223)		N	N	N	N		S	S	S	S		A	A	A	A	B
	0.033uF (333)		N	N	N	N		S	S	S	S		A	A	A	A	B
	0.047uF (473)		N	N	N			S	S	S	S		A	A	A	A	B
	0.068uF (683)		N	N	N			S	S	S	S		A	A	A	A	B
	0.10uF (104)		N	N	N			S	S	S	S		A	A	A	A	B
	0.15uF (154)		N	N				S	S	S	S		A	A	A	A	
	0.22uF (224)	N	N	N			S	S	S	S	S		A	A	A	A	
	0.33uF (334)	N	N	N				S	S	S			B	B	B	B	
	0.47uF (474)	N	N	N				S	S	X	S		B	B	B	B/D	
	0.68uF (684)	N						S	X				B	B	D	D	
	1.0uF (105)	N	N					S	X	X			B	B	D	D	
	1.5uF (155)							S					D	D			
	2.2uF (225)						S	S	X				D	D	I		
	3.3uF (335)												D	D			
	4.7uF (475)						X	X					D	D	I		
	6.8uF (685)												I				
	10uF (106)											I	I	I			
	22uF (226)											I					

Y5V Dielectric (1206, 1210, 1812 Size)

Dielectric		Y5V																		
Size		1206							1210							1812				
Rated Voltage (VDC)		6.3	10	16	25	35	50	100	6.3	10	16	25	35	50	100	10	16	25	50	100
capacitance	0.010uF (103)		B	B	B		B	B							C					D
	0.015uF (153)		B	B	B		B	B							C					D
	0.022uF (223)		B	B	B		B	B							C					D
	0.033uF (333)		B	B	B		B	B							C					D
	0.047uF (473)		B	B	B		B	B							C					D
	0.068uF (683)		B	B	B		B	B							C					D
	0.10uF (104)		B	B	B		B	B		C	C	C		C	C	D	D	D	D	D
	0.15uF (154)		B	B	B		B	C		C	C	C		C	C	D	D	D	D	D
	0.22uF (224)		B	B	B		B	C		C	C	C		C	C	D	D	D	D	D
	0.33uF (334)		B	B	B		B			C	C	C		C	C	D	D	D	D	D
	0.47uF (474)		B	B	B		B			C	C	C		C		D	D	D	D	D
	0.68uF (684)		B	B	B		B			C	C	C		C		D	D	D	D	D
	1.0uF (105)		C	C	C		C/D			C	C	C		C		D	D	D	D	D
	1.5uF (155)		C	C	C					C	C	C				D	D	D	D	
	2.2uF (225)		C	C	C		J			C	C	C		G		D	D	D	D	
	3.3uF (335)		J	J	J					C	C	C				D	D	D	D	
	4.7uF (475)		J	J	J	J	P			C	C	D		G		D	D	D	D	
	6.8uF (685)		J	J						C	C	D				D	D	D	D	
	10uF (106)		J	J	P					D	D	G	K			D	D	D		
	22uF (226)		P							K	K									
	47uF (476)	P							K	K							M			
	100uF (107)								M											

1. The letter in cell is expressed the symbol of product thickness.
2. For more information about products with special capacitance or other data, please contact WTC local representative.

X5R Dielectric

Dielectric		X5R																							
Size		0402				0603					0805					1206					1210				
Rated Voltage (VDC)		6.3	10	16	25	6.3	10	16	25	50	6.3	10	16	25	50	6.3	10	16	25	50	6.3	10	16	25	50
capacitance	0.027μF (273)			N																					
	0.033μF (333)			N																					
	0.039μF (393)			N																					
	0.047μF (473)			N																					
	0.056μF (563)		N	N																					
	0.068μF (683)		N	N																					
	0.082μF (823)	N	N	N																					
	0.10μF (104)	N	N	N	N																				
	0.15μF (154)	N	N	N	N																				
	0.22μF (224)	N	N	N	N			X	X																
	0.27uF (274)						X	X																	
	0.33μF (334)	N	N			X	X	X	X																
	0.39μF (394)						X	X																	
	0.47μF (474)	N	N				X	X	X																
	0.68μF (684)	N	N				X	X	X																
	0.82uF (824)					X	X	X																	
	1.0μF (105)	N	N	N		X	X	X	X	X		D	D	D	I										
	1.5μF (155)					X					I	I	I	I			J	J				K	K		
	2.2μF (225)	N	N			X	X	X	X		I	I	I	I			J	J	P			K	K		
	3.3μF (335)										I	I	I	I			P	P	P						
	4.7μF (475)	E				X	X	X			I	I	I	I		P	P	P	P	P		K	K	K	
	6.8uF (685)															P	P								
	10μF (106)	E				X					I	I	I	I		P	P	P	P		K	K	K	K	M
	22μF (226)					X						I				P	P	P			M	M	M	M	
	47μF (476)										I					P	P				M	M	M		
	100μF (107)															P					M	M			

1. The letter in cell is expressed the symbol of product thickness.
2. For more information about products with special capacitance or other data, please contact WTC local representative.

Ultra-Small Capacitors
0201 Series

■ FEATURES

* High capacitance in unit size.
* High precision dimensional tolerances.
* Suitable used in high-accuracy automatic mounting machine.

■ GENERAL ELECTRICAL DATA

Size	0201		
Dielectric	NP0	X7R	X5R
Capacitance	0.3pF to 100pF	100pF to 10nF	100pF to 0.47μF
Capacitance tolerance	Cap≤5pF: B (±0.1pF), C (±0.25pF) 5pF<Cap<10pF: C (±0.25pF),D(±0.5pF) Cap≥10pF:F (±1%),G (±2%),J (±5%),K(±10%)	J (±5%), K (±10%), M (±20%)	J (±5%),K (±10%), M (±20%)
Rated voltage (WVDC)	16V, 25V, 50V	6.3V, 10V, 16V, 25V, 50V	6.3V, 10V, 16V, 25V, 50V
Tan δ / Q	Cap<30pF, Q≥400+20C Cap≥30pF, Q≥1000	Ur=50V: ≤3.0% Ur=16V, 25V: ≤3.5% Ur=10V: ≤5.0% Ur=6.3V: ≤10%	Ur=50V: ≤3.0% Ur=16V, 25V: ≤3.5% Ur=10V: ≤5.0% Ur=6.3V: ≤10%
Insulation resistance at Ur	≥10GΩ	≥10GΩ or RxC≥500ΩxF whichever is less	
Operating temperature	-55 to +125°C		-55 to +85°C
Capacitance change	±30ppm	±15%	
Termination	Ni/Sn (lead-free termination)		

■ EXPLANATION OF PART NUMBERS

0201	N	100	J	250	L	T
Size (Inch (mm))	Dielectric	Capacitance	Tolerance	Rated voltage	Termination	Packaging style
0201 (0603)	N=NP0(C0G)	100=10x10^0=10pF	J=±5%	250=25 VDC	L=Ag/Ni/Sn	T=7" reeled

Please refer to page 2 " How to order" for more information.

■ CAPACITANCE RANGE

SIZE		0201									
DIELECTRIC		X7R					X5R				
RATED VOLTAGE (VDC)		6.3	10	16	25	50	6.3	10	16	25	50
Capacitance	100pF (101)			L	L	L			L	L	L
	120pF (121)			L	L	L			L	L	L
	150pF (151)			L	L	L			L	L	L
	180pF (181)			L	L	L			L	L	L
	220pF (221)			L	L	L			L	L	L
	270pF (271)			L	L	L			L	L	L
	330pF (331)			L	L	L			L	L	L
	390pF (391)			L	L	L			L	L	L
	470pF (471)			L	L	L			L	L	L
	560pF (561)			L	L	L			L	L	L
	680pF (681)			L	L	L			L	L	L
	820pF (821)			L	L	L			L	L	L
	1,000pF (102)	L	L	L	L	L			L	L	L
	1,500pF (152)	L	L	L				L	L		
	2,200pF (222)	L	L	L				L	L		
	3,300pF (332)	L	L	L				L	L		
	4,700pF (472)	L	L	L				L	L		
	6,800pF (682)	L	L					L			
	0.010μF (103)	L	L	L			L	L			
	0.015μF (153)						L	L			
	0.022μF (223)						L	L			
	0.033μF (333)						L	L			
	0.047μF (473)						L	L			
	0.068μF (683)						L	L			
	0.10μF (104)						L	L			
	0.22μF (224)						L				
	0.47μF (474)						L				

1. The letter in cell is expressed the symbol of product thickness.
2. The letter in cell with "^" mark is expressed product with Ag/Ni/Sn terminations.
3. For more information about products with special capacitance or other data, please contact WTC local representative.

SIZE		0201		
DIELECTRIC		NPO		
RATED VOLTAGE (VDC)		16	25	50
Capacitance	0.3pF (0R3)		L^	L^
	0.4pF (0R4)		L^	L^
	0.5pF (0R5)		L^	L^
	1.0pF (1R0)		L^	L^
	1.2pF (1R2)		L^	L^
	1.5pF (1R5)		L^	L^
	1.8pF (1R8)		L^	L^
	2.2pF (2R2)		L^	L^
	2.7pF (2R7)		L^	L^
	3.0pF (3R0)		L^	L^
	3.3pF (3R3)		L^	L^
	3.9pF (3R9)		L^	L^
	4.0pF(4R0)		L^	L^
	4.7pF (4R7)		L^	L^
	5.6pF (5R6)		L^	L^
	6.8pF (6R8)		L^	L^
	8.2pF (8R2)		L^	L^
	10pF (100)		L^	L^
	12pF (120)		L^	L^
	15pF (150)		L^	L^
	18pF (180)		L^	L^
	22pF (220)		L^	L^
	27pF (270)		L^	L^
	33pF (330)		L^	L^
	39pF (390)		L^	L^
	47pF (470)		L^	L^
	56pF (560)	L^	L^	
	68pF (680)	L^	L^	
	82pF (820)	L^	L^	
	100pF (101)	L^	L^	

■ FEATURES

* High voltage in a given case size.
* High stability and reliability.

■ GENERAL ELECTRICAL DATA

Dielectric	NP0	X7R	Y5V
Size	0603, 0805, 1206, 1210, 1808, 1812		0805, 1206, 1210, 1812
Capacitance	0.5pF to 6800pF	100pF to 1.0μF	0.01μF to 0.68μF
Capacitance tolerance	Cap≤5pF: C (±0.25pF) 5pF<Cap<10pF: D (±0.5pF) Cap≥10pF: J (±5%), K (±10%)	K (±10%), M (±20%)	Z (-20/+80%)
Rated voltage (WVDC)	200V to 3kV		200V, 250V
Q	Cap<30pF: Q≥400+20C Cap≥30pF: Q≥1000	≤2.5%	≤5%
Insulation resistance at Ur	Ur=200~630V: ≥10GΩ or RxC≥100Ω-F whichever is smaller Ur=1000~3000V: ≥10GΩ		
Dielectric strength	200~300V: ≥2 x WVDC 500~999V: ≥1.5 x WVDC 1000~3000V: ≥1.2 x WVDC		
Operating temperature	-55 to +125°C		-25 to +85°C
Capacitance characteristic	±30ppm	±15%	+30/-80%
Termination	Ni/Sn (lead-free termination)		

■ EXPLANATION OF PART NUMBERS

1808	N	100	J	202	C	T
Size (Inch (mm))	Dielectric	Capacitance	Tolerance	Rated voltage	Termination	Packaging style
1808 (4520)	N=NP0(C0G)	100=10x10^0=10pF	J=±5%	202=2000 VDC	C=Cu/Ni/Sn	T=7" reeled

Please refer to page 2 " How to order" for more information.

■ CAPACITANCE RANGE

Y5V Dielectric 200V to 250V

DIELECTRIC		Y5V							
SIZE		0805		1206		1210		1812	
RATED VOLTAGE (VDC)		200	250	200	250	200	250	200	250
Capacitance	0.010μF (103)	B	B	B	B	C	C	D	D
	0.015μF (153)	B	B	B	B	C	C	D	D
	0.022μF (223)	B	B	B	B	C	C	D	D
	0.033μF (333)	B	B	B	B	C	C	D	D
	0.047μF (473)	B	B	B	B	C	C	D	D
	0.068μF (683)	B	B	B	B	C	C	D	D
	0.10μF (104)			B	B	C	C	D	D
	0.15μF (154)			C	C	C	C	D	D
	0.22μF (224)							D	D
	0.33μF (334)							D	D
	0.47μF (474)							D	D
	0.68μF (684)							D	D

1. The letter in cell is expressed the symbol of product thickness.
2. For more information about products with special capacitance or other data, please contact WTC local representative.

NP0 Dielectric 200V to 3kV

DIELECTRIC		NP0																											
SIZE		0603		0805				1206						1210						1808					1812						
RATED VOLTAGE (VDC)		200	250	200	250	500	630	200	250	500	630	1000	2000	200	250	500	630	1000	2000	500	630	1000	2000	3000	200	250	500	630	1000	2000	3000
Capacitance	0.5pF (0R5)	S		A	A	A																									
	1.0pF (1R0)	S		A	A	A																									
	1.2pF (1R2)	S		A	A	A																									
	1.5pF (1R5)	S		A	A	A	B	B	B		B	B																			
	1.8pF (1R8)	S		A	A	A	B	B	B		B	B																			
	2.2pF (2R2)	S		A	A	A	B	B	B		B	B									D		D	D							
	2.7pF (2R7)	S		A	A	A	B	B	B		B	B									D		D	D							
	3.3pF (3R3)	S		A	A	A	B	B	B		B	B									D		D	D							
	3.9pF (3R9)	S		A	A	A	B	B	B		B	B									D		D	D							
	4.7pF (4R7)	S		A	A	A	B	B	B		B	B									D		D	D							
	5.6pF (5R6)	S		A	A	A	B	B	B		B	B									D		D	D							
	6.8pF (6R8)	S		A	A	A	B	B	B		B	B									D		D	D							
	8.2pF (8R2)	S		A	A	A	B	B	B		B	B									D		D	D							
	10pF (100)	S		A	A	A	B	B	B		B	B	C	C	C		C	C	C		D		D	D	D	D	D		D	D	D
	12pF (120)	S		A	A	A	B	B	B		B	B	C	C	C		C	C	C		D		D	D	D	D	D		D	D	D
	15pF (150)	S		A	A	A	B	B	B		B	B	C	C	C		C	C	C		D		D	D	D	D	D		D	D	D
	18pF (180)	S		A	A	A	B	B	B		B	B	C	C	C		C	C	C		D		D	D	D	D	D		D	D	D
	22pF (220)	S		A	A	A	B	B	B		B	B	C	C	C		C	C	C		D		D	D	D	D	D		D	D	D
	27pF (270)	S		A	A	A	B	B	B		B	B	C	C	C		C	C	C		D		D	D	D	D	D		D	D	D
	33pF (330)	S		A	A	A	B	B	B		B	C	C	C	C		C	C	C		D		D	D	D	D	D		D	D	D
	39pF (390)	S		A	A	A	B	B	B		B	C	C	C	C		C	C	C		D		D	D	D	D	D		D	D	D
	47pF (470)	S		A	A	A	B	B	B		C	C	C	C	C		C	C	C		D		D	D	D	D	D		D	D	D
	56pF (560)	S		A	A	A	B	B	B		C	D	C	C	C		C	C	D		D		D	D	D	D	D		D	D	D
	68pF (680)	S		A	A	A	B	B	B		C	D	C	C	C		C	C	D		D		D	D	D	D	D		D	D	D
	82pF (820)	S		A	A	B	B	B	B		D	D	C	C	C		C	C	D		D		D	D	D	D	D		D	D	D
	100pF (101)	S		A	B	B	B	B	B		D	D	C	C	C		D	D	D		D		D	K	D	D	D		D	D	D
	120pF (121)	S		A	B	D	B	B	B		D	G	C	C	C		D	D	D		D		D	K	D	D	D		D	D	D
	150pF (151)	S		B	D	D	B	B	B		D	G	C	C	C		D	G	D		K		K	D	D	D	D		D	D	D
	180pF (181)	S		B	D	D	B	B	B		G	G	C	C	C		D	G	D		K		K	D	D	D	D		D	D	K
	220pF (221)	S		D	D	D	B	B	B		G	G	C	C	C		G	G	D		K		K	D	D	D	D		D	D	K
	270pF (271)	X		D	D	D	B	C	C		G		C	C	C		G		K		K		K	D	D	D	D		D	K	K
	330pF (331)	X		D	D	D	B	C	C		G		C	C	C		G		K		K		K	D	D	D	D		D	K	K
	390pF (391)	X		D	D	D	B	C	C		G		C	C	C		G		K		K			D	D	D	D		D	K	K
	470pF (471)	X		D	D		C	C	C		G		C	C	C		G		K		K			D	D	D	K		K	K	K
	560pF (561)			D	D		C	D	D				C	C	C				K		K			D	D	D	K		K		
	680pF (681)			D	D		C	D	D				C	C	C				K		K			D	D	D	K		K		
	820pF (821)			D	D		C	G	G				C	C	C				K					D	D	D	K		K		
	1,000pF (102)			D			C	G	G				D	D	D				K					D	D	D	K		K		
	1,200pF (122)						C	G	G				D	D	D									D	D	D	K				
	1,500pF (152)						D	G	G				D	D	D									D	D	D	K				
	1,800pF (182)						D	G	G				D	D	D									D	D	D					
	2,200pF (222)						D	G	G				D	D										D	D	D					
	2,700pF (272)												D	D										D	D	D					
	3,300pF (332)												D	D										D	D	D					
	3,900pF (392)												D	D										D							
	4,700pF (472)																							D							
	5,600pF (562)																							D							
	6,800pF (682)																							D							

1. The letter in cell is expressed the symbol of product thickness.
2. The letter in cell with “^” mark is expressed product with Ag/Ni/Sn terminations.
3. For more information about products with special capacitance or other data, please contact WTC local representative.

X7R Dielectric 200V to 3kV

DIELECTRIC	X7R																										
SIZE	0805				1206						1210					1808					1812						
RATED VOLTAGE (VDC)	200	250	500	630	200	250	500	630	1000	2000	200	250	500	630	1000	500	630	1000	2000	3000	200	250	500	630	1000	2000	3000
Capacitance																											
100pF (101)	B		B																								
120pF (121)	B		B																								
150pF (151)	B		B		D		D		D	D							D		D	D							
180pF (181)	B		B		D		D		D	D							D		D	D							
220pF (221)	B		B		D		D		D	D							D		D	D							
270pF (271)	B		B		D		D		D	D							D		D	D					D	D	
330pF (331)	B		B		D		D		D	D							D		D	K					D	D	
390pF (391)	B		B		D		D		D	D							D		D	K					D	D	
470pF (471)	B		B		D		D		D	D							D		D	K					D	D	
560pF (561)	B		B		D		D		D	D							D		D	K					D	D	
680pF (681)	B		B		D		D		D	D							D		D	K					D	D	K
820pF (821)	B		B		D		D		D	G							D		D	K					D	D	K
1,000pF (102)	B		B		D		D		D	D/G	C		D		D		D		D	K	D		D		D	D	K
1,200pF (122)	B		B		D		D		D	G	C		D		D		D		K		D		D		D	D	
1,500pF (152)	B		B		D		D		D	G	C		D		D		D		K		D		D		D	D	
1,800pF (182)	B		B		D		D		D	G	C		D		D		D		K		D		D		D	D	
2,200pF (222)	B		B		D		D		D		C		D		D		D		K		D		D		D	D	
2,700pF (272)	B		B		D		D		D		C		D		D		D				D		D		D	D	
3,300pF (332)	B		B		D		D		D		C		D		D		D				D		D		D	K	
3,900pF (392)	B		B		D		D		D		C		D		G		D				D		D		D	K	
4,700pF (472)	B		D		D		D		D		C		D		G		D				D		D		D	K	
5,600pF (562)	D		D		D		D		D		C		D		G		K				D		D		D		
6,800pF (682)	D		D		D		D		D		C		D		G		K				D		D		D		
8,200pF (822)	D		D		D		D		D		C		D		G		K				D		D		D		
0.010μF (103)	D		D		D		D		D		C		D		G		K				D		D		D		
0.012μF (123)	D				D		D				C		D								D		D		K		
0.015μF (153)	D				D		D				C		D								D		D		K		
0.018μF (183)	D				D		D				C		D								D		D				
0.022μF (223)	D				D		G				C		D								D		D				
0.027μF (273)					D		G				C		G								D		D				
0.033μF (333)					G		G				C		G								D		D				
0.039μF (393)					G						C		G								D		D				
0.047μF (473)					G						D		G								D		D				
0.056μF (563)					G						D		G								D		K				
0.068μF (683)					G						G										D		K				
0.082μF (823)					G						G										D		K				
0.10μF (104)					G						G										D		K				
0.12μF (124)											G										D						
0.15μF (154)											M										K						
0.18μF (184)											M										K						
0.22μF (224)											M										K						
0.27μF (274)											M										K						
0.33μF (334)											M										K						
0.39μF (394)											M										K						
0.47μF (474)											M										K						
0.56μF (564)																					M						
0.68μF (684)																					M						
0.82μF (824)																					M						
1.00μF (105)																					M						

1. The letter in cell is expressed the symbol of product thickness.

2. The letter in cell with "^" mark is expressed product with Ag/Ni/Sn terminations.

3. For more information about products with special capacitance or other data, please contact WTC local representative.

High Q / Low ESR Capacitors
HH Series

■ FEATURES

* High Q and low ESR performance at high frequency.
* Quality improvement of telephone calls for low power loss and better performance.

■ GENERAL ELECTRICAL DATA

Dielectric	NP0
Size	0402, 0603,0805
Capacitance	0402: 0.5pF to 470pF(<0.5pF: on requested) 0603: 0.5pF to 3300pF 0805: 0.5pF to 150pF
Capacitance tolerance	Cap≤5pF: B (±0.1pF), C (±0.25pF) 5pF<Cap<10pF: C (±0.25pF), D (±0.5pF) Cap≥10pF: F (±1%), G (±2%), J (±5%)
Rated voltage (WVDC)	16V, 25V, 50V, 100V, 200V, 250V, 500V, 630V
Q	Cap<30pF: Q≥400+20C Cap≥30pF: Q≥1000
Insulation resistance at Ur	≥10GΩ
Operating temperature	-55 to +125°C
Capacitance change	±30ppm
Termination	Ni/Sn (lead-free termination)

■ EXPLANATION OF PART NUMBERS

HH	15	N	100	G	500	C	T
Series HH=High Q/ Low ESR	Size (Inch (mm)) 15=0402 (1005)	Dielectric N=NP0(C0G)	Capacitance $100=10x10^0=10pF$	Tolerance G=±2%	Rated voltage 500=50 VDC	Termination C=Cu/Ni/Sn	Packaging T=7" reeled

* Please refer to page 2 " How to order" for more information.

■ ELECTRICAL CHARACTERISTICS

Fig. 1 Q factor specification vs. Specific frequency 0402

Fig. 2 Q factor specification vs. Specific frequency 0603

■ CAPACITANCE RANGE

DIELECTRIC		NP0										
SIZE		0402			0603				0805			
RATED VOLTAGE (VDC)		16	25	50	16	25	50	100	50	100	200,250	500,630
Capacitance	0.5pF (0R5)	N^	N^	N^	S^	S^	S^	S^	B	B		
	0.6pF (0R6)	N^	N^	N^	S^	S^	S^	S^	B	B		
	0.7pF (0R7)	N^	N^	N^	S^	S^	S^	S^	B	B		
	0.8pF (0R8)	N^	N^	N^	S^	S^	S^	S^	B	B		
	0.9pF (0R9)	N^	N^	N^	S^	S^	S^	S^	B	B		
	1.0pF (1R0)	N^	N^	N^	S^	S^	S^	S^	B	B	B	B
	1.2pF (1R2)	N^	N^	N^	S^	S^	S^	S^	B	B	B	B
	1.5pF (1R5)	N^	N^	N^	S^	S^	S^	S^	B	B	B	B
	1.8pF (1R8)	N^	N^	N^	S^	S^	S^	S^	B	B	B	B
	2.2pF (2R2)	N^	N^	N^	S^	S^	S^	S^	B	B	B	B
	2.7pF (2R7)	N^	N^	N^	S^	S^	S^	S^	B	B	B	B
	3.3pF (3R3)	N^	N^	N^	S^	S^	S^	S^	B	B	B	B
	3.9pF (3R9)	N^	N^	N^	S^	S^	S^	S^	B	B	B	B
	4.7pF (4R7)	N^	N^	N^	S^	S^	S^	S^	B	B	B	B
	5.6pF (5R6)	N^	N^	N^	S^	S^	S^	S^	B	B	B	B
	6.8pF (6R8)	N^	N^	N^	S^	S^	S^	S^	B	B	B	B
	8.2pF (8R2)	N^	N^	N^	S^	S^	S^	S^	B	B	B	B
	10pF (100)	N	N	N	S	S	S	S	B	B	B	B
	12pF (120)	N	N	N	S	S	S	S	B	B	B	B
	15pF (150)	N	N	N	S	S	S	S	B	B	B	B
	18pF (180)	N	N	N	S	S	S	S	B	B	B	B
	22pF (220)	N	N	N	S	S	S	S	B	B	B	B
	27pF (270)	N	N	N	S	S	S	S	B	B	B	B
	33pF (330)	N	N	N	S	S	S	S	B	B	B	B
	39pF (390)	N	N	N	S	S	S	S	B	B	B	B
	47pF (470)	N	N	N	S	S	S	S	B	B	B	B
	56pF (560)	N	N	N	S	S	S	S	B	B	B	B
	68pF (680)	N	N	N	S	S	S	S	B	B	B	B
	82pF (820)	N	N	N	S	S	S	S	B	B	B	B
	100pF (101)	N	N	N	S	S	S	S	B	B	B	B
	120pF (121)	N	N	N	S	S	S	S	D	D	D	D
	150pF (151)	N	N	N	S	S	S	S	D	D	D	D
	180pF (181)	N	N	N	S	S	S	S			D	D
	220pF (221)	N	N	N	S	S	S	S			D	D
	270pF (271)	N	N	N	S	S	S	S			D	D
	330pF (331)	N	N	N	S	S	S	S			D	D
	390pF (391)	N	N	N	S	S	S	S			D	D
	470pF (471)	N	N	N	S	S	S	S				
	560pF (561)				S	S	S	S				
	680pF (681)				S	S	S	S				
	820pF (821)				S	S	S	S				
	1,000pF (102)				S	S	S	S				
	1,200pF (122)				X	X	X					
	1,500pF (152)				X	X	X					
	1,800pF (182)				X	X	X					
	2,200pF (222)				X	X	X					
	2,700pF (272)				X	X	X					
	3,300pF (332)				X	X	X					

1. The letter in cell is expressed the symbol of product thickness.
2. The letter in cell with "^" mark is expressed product with Ag/Ni/Sn terminations.
3. 0402, Capacitance <0.5pF: On request.
4. For more information about products with special capacitance or other data, please contact WTC local representative.

■ FEATURES

* Ultra high Q and low ESR performance at high frequency.
* Quality improvement of telephone calls for low power loss and better performance.

■ GENERAL ELECTRICAL DATA

Dielectric	NP0
Size	0201, 0402, 0603, 0805
Capacitance	0201: 0.1pF to 33pF; 0402: 0.1pF to 22pF; 0603: 0.3pF to 47pF; 0805: 0.3pF to 100pF
Capacitance tolerance	Cap≤5pF: A (±0.05pF), B (±0.1pF), C (±0.25pF) 5pF<Cap<10pF: B (±0.1pF), C (±0.25pF), D (±0.5pF) Cap≥10pF: F (±1%), G (±2%), J (±5%)
Rated voltage (WVDC)	6.3V, 10V, 25V, 50V, 100V, 250V
Q	Cap≥30pF, Q≥1000 Cap<30pF,Q≥400+20C
Insulation resistance at Ur	≥10GΩ
Operating temperature	-55 to +125°C
Capacitance change	±30ppm/°C; 0201Cap≥22pF, ±60ppm/°C
Termination	Ni/Sn (lead-free termination)

■ EXPLANATION OF PART NUMBERS

RF	15	N	100	G	500	C	T
Series RF=Microwave	Size (Inch (mm)) 15=0402 (1005)	Dielectric N=NP0	Capacitance $100=10x10^0=10pF$	Tolerance G=±2%	Rated voltage 500=50 VDC	Termination C=Cu/Ni/Sn	Packaging T=7" reeled

* Please refer to page 2 " How to order" for more information.

■ ELECTRICAL CHARACTERISTICS

Fig. 3 Self resonance frequency vs. Capacitance (0201 size)

Fig. 4 Self resonance frequency vs. Capacitance (0402 size)

■ CAPACITANCE RANGE

DIELECTRIC		NP0											
SIZE		0201				0402		0603			0805		
RATED VOLTAGE (VDC)		6.3	10	25	50	50	100	50	100	250	50	100	250
Capacitance	0.1pF (0R1)	L	L	L	L	N	N						
	0.2pF (0R2)	L	L	L	L	N	N						
	0.3pF (0R3)	L	L	L	L	N	N	S	S	S	T	T	T
	0.4pF (0R4)	L	L	L	L	N	N	S	S	S	T	T	T
	0.5pF (0R5)	L	L	L	L	N	N	S	S	S	T	T	T
	0.6pF (0R6)	L	L	L	L	N	N	S	S	S	T	T	T
	0.7pF (0R7)	L	L	L	L	N	N	S	S	S	T	T	T
	0.8pF (0R8)	L	L	L	L	N	N	S	S	S	T	T	T
	0.9pF (0R9)	L	L	L	L	N	N	S	S	S	T	T	T
	1.0pF (1R0)	L	L	L	L	N	N	S	S	S	T	T	T
	1.2pF (1R2)	L	L	L	L	N	N	S	S	S	T	T	T
	1.5pF (1R5)	L	L	L	L	N	N	S	S	S	T	T	T
	1.8pF (1R8)	L	L	L	L	N	N	S	S	S	T	T	T
	2.2pF (2R2)	L	L	L	L	N	N	S	S	S	T	T	T
	2.7pF (2R7)	L	L	L	L	N	N	S	S	S	T	T	T
	3.3pF (3R3)	L	L	L	L	N	N	S	S	S	T	T	T
	3.9pF (3R9)	L	L	L	L	N	N	S	S	S	T	T	T
	4.7pF (4R7)	L	L	L	L	N	N	S	S	S	T	T	T
	5.6pF (5R6)	L	L	L	L	N	N	S	S	S	T	T	T
	6.8pF (6R8)	L	L	L	L	N	N	S	S	S	T	T	T
	8.2pF (8R2)	L	L	L	L	N	N	S	S	S	T	T	T
	10pF (100)	L	L	L	L	N	N	S	S	S	T	T	T
	11pF (110)	L	L	L	L	N		S	S	S	T	T	T
	12pF (120)	L	L	L	L	N		S	S	S	T	T	T
	13pF (130)	L	L	L	L	N		S	S	S	T	T	T
	15pF (150)	L	L	L	L	N		S	S	S	T	T	T
	16pF (160)	L	L	L	L	N		S	S	S	T	T	T
	18pF (180)	L	L	L	L	N		S	S	S	T	T	T
	20pF (200)	L	L	L	L	N		S	S	S	T	T	T
	22pF (220)	L	L	L		N		S	S	S	T	T	T
	24pF (240)	L	L	L				S	S	S	T	T	T
	27pF (270)	L	L	L				S	S	S	T	T	T
	30pF (300)	L	L	L				S	S	S	T	T	T
	33pF (330)	L	L	L				S	S	S	T	T	T
	36pF (360)							S	S	S	T	T	T
	39pF (390)							S	S	S	T	T	T
	43pF (430)							S	S	S	T	T	T
	47pF (470)							S	S	S	T	T	T
	56pF (560)										T	T	T
	68pF (680)										T	T	T
	82pF (820)										T	T	T
	100pF (101)										T	T	T

1. The letter in cell is expressed the symbol of product thickness.
2. For more information about products with special capacitance or other data, please contact WTC local representative.

Soft Termination Capacitors
SH Series

■ FEATURES

* MLCC's terminations build a soft & flexible polymer layer to withstand high bending stress in SMT line.
* Available for any item in standard series range.

■ GENERAL ELECTRICAL DATA

Dielectric	NP0	X7R
Size	0603, 0805, 1206, 1210, 1808, 1812	
Capacitance range	0.5pF to 220pF	100pF to 1μF
Capacitance tolerance	Cap≤5pF: B (±0.1pF), C (±0.25pF) 5pF<Cap<10pF: C (±0.25pF), D (±0.5pF) Cap≥10pF: F (±1%), G (±2%), J (±5%), K (±10%)	J (±5%), K (±10%), M (±20%)
Rated voltage (WVDC)	10V, 16V, 25V, 50V, 100V, 200V, 250V, 500V, 630V, 1000V, 2000V, 3000V	
Insulation resistance at Ur	≥10GΩ or RxC≥500Ω-F whichever is less	
Operating temperature	-55 to +125°C	
Capacitance characteristic	±30ppm	±15%
Termination	Ni/Sn (lead-free termination)	

■ EXPLANATION OF PART NUMBERS

SH	31	N	100	D	501	C	T
Series	Size (Inch (mm))	Dielectric	Capacitance	Tolerance	Rated voltage	Termination	Packaging
SH=Soft termination	31=1206 (3216)	N=NP0(C0G)	$100=10x10^0=10pF$	D=±0.5pF	501=50 VDC	C=Cu/Ni/Sn	T=7" reeled

* Please refer to page 2 " How to order" for more information.

■ PACKAGING DIMENSION AND QUANTITY

Size	L(mm)	W(mm)	Thickness (mm)/Symbol		Paper tape		Plastic tape	
					7" reel	13" reel	7" reel	13" reel
0603 (1608)	1.60±0.20	0.80±0.10	0.80±0.07	S	4,000	15,000	-	-
	1.60+0.20/-0.10	0.80+0.15/-0.10	0.80+0.15/-0.10	X	4,000	15,000	-	-
0805 (2012)	2.00±0.20	1.25±0.10	0.60±0.10	A	4,000	15,000	-	-
			0.80±0.10	B	4,000	15,000	-	-
			1.25±0.10	D	-	-	3,000	10,000
	2.00+0.25/-0.2	1.25±0.20	1.25±0.20	I	-	-	3,000	10,000
1206 (3216)	3.20+0.4/-0.1	1.60±0.15	0.80±0.10	B	4,000	15,000	-	-
			0.95±0.10	C	-	-	3,000	10,000
			1.15±0.15	J	-	-	3,000	10,000
			1.25±0.10	D	-	-	3,000	10,000
	3.20+0.4/-0.1	1.60±0.20	1.60±0.20	G	-	-	2,000	10,000
	3.20+0.4/-0.1	1.60+0.30/-0.10	1.60+0.30/-0.10	P	-	-	2,000	9,000
1210 (3225)	3.20±0.40	2.50±0.20	0.95±0.10	C	-	-	3,000	10,000
			1.25±0.10	D	-	-	3,000	10,000
	3.20±0.50	2.50±0.30	1.60±0.20	G	-	-	2,000	10,000
			2.00±0.20	K	-	-	1,000	6,000
			2.50±0.30	M	-	-	1,000	6,000
1808 (4520)	4.50+0.60/-0.4	2.03±0.25	1.25±0.10	D	-	-	2,000	-
			2.00±0.20	K	-	-	1,000	-
1812 (4532)	4.50+0.60/-0.4	3.20±0.30	1.25±0.10	D	-	-	1,000	-
			2.00±0.20	K	-	-	1,000	-
		3.20±0.40	2.50±0.30	M	-	-	500	3,000

Unit: pieces

■ CAPACITANCE RANGE

DIELECTRIC		NP0										
SIZE		0603		0805		1206			1210			1808
RATED VOLTAGE (VDC)		25,50, 100	200, 250	10,16, 25,50, 100	200, 250	100,200, 250,500, 630	1000	2000	100,200, 250,500, 630	1000	2000	3000
Capacitance	0.5pF (0R5)	S	S	A	A							
	1.0pF (1R0)	S	S	A	A							
	1.2pF (1R2)	S	S	A	A							
	1.5pF (1R5)	S	S	A	A	B	B	B				
	1.8pF (1R8)	S	S	A	A	B	B	B				
	2.2pF (2R2)	S	S	A	A	B	B	B				D
	2.7pF (2R7)	S	S	A	A	B	B	B				D
	3.3pF (3R3)	S	S	A	A	B	B	B				D
	3.9pF (3R9)	S	S	A	A	B	B	B				D
	4.7pF (4R7)	S	S	A	A	B	B	B				D
	5.6pF (5R6)	S	S	A	A	B	B	B				D
	6.8pF (6R8)	S	S	A	A	B	B	B				D
	8.2pF (8R2)	S	S	A	A	B	B	B				D
	10pF (100)	S	S	A	A	B	B	B	C	C	C	D
	12pF (120)	S	S	A	A	B	B	B	C	C	C	D
	15pF (150)	S	S	A	A	B	B	B	C	C	C	D
	18pF (180)	S	S	A	A	B	B	B	C	C	C	D
	22pF (220)	S	S	A	A	B	B	B	C	C	C	D
	27pF (270)	S	S	A	A	B	B	B	C	C	C	D
	33pF (330)	S	S	A	A	B	B	C	C	C	C	D
	39pF (390)	S	S	A	A	B	B	C	C	C	C	D
	47pF (470)	S	S	A	A	B	C	C	C	C	C	D
	56pF (560)	S	S	A	A	B	C	D	C	C	D	D
	68pF (680)	S	S	A	A	B	C	D	C	C	D	D
	82pF (820)	S	S	A	A	B	D	D	C	C	D	D
	100pF (101)	S	S	A	A	B	D	D	C	D	D	K
	120pF (121)			A	A	B	D	G	C	D	D	
	150pF (151)			A	B	B	D	G	C	D	G	
	180pF (181)			A	B	B	G	G	C	D	G	
	220pF (221)			A	D	B	G	G	C	G	G	
	270pF (271)			A	D							
	330pF (331)			A	D							
	390pF (391)			B	D							
	470pF (471)			B	D							
	560pF (561)			B	D							
	680pF (681)			B	D							
	820pF (821)			B	D							
	1,000pF (102)			B	D							
	1,200pF (122)											
	1,500pF (152)											
	1,800pF (182)											
	2,200pF (222)											
	2,700pF (272)											
	3,300pF (332)											
	3,900pF (392)											
	4,700pF (472)											
	5,600pF (562)											
	6,800pF (682)											
	8,200pF (822)											

1. The letter in cell is expressed the symbol of product thickness.
2. For more information about products with special capacitance or other data, please contact WTC local representative.

X7R Dielectric 10V To 250V

DIELECTRIC		X7R																				
SIZE		0603				0805				1206					1210				1812			
RATED VOLTAGE (VDC)		10 16	25	50	100	10 16 25	50	100	200 250	10 16	25	50	100	200 250	10 16 25	50	100	200 250	10 16 25	50	100	200 250
Capacitance	100pF (101)	S	S	S	S	D	D	D	D													
	120pF (121)	S	S	S	S	D	D	D	D													
	150pF (151)	S	S	S	S	D	D	D	D	D	D	D	D	D								
	180pF (181)	S	S	S	S	D	D	D	D	D	D	D	D	D								
	220pF (221)	S	S	S	S	D	D	D	D	D	D	D	D	D								
	270pF (271)	S	S	S	S	D	D	D	D	D	D	D	D	D								
	330pF (331)	S	S	S	S	D	D	D	D	D	D	D	D	D								
	390pF (391)	S	S	S	S	D	D	D	D	D	D	D	D	D								
	470pF (471)	S	S	S	S	D	D	D	D	D	D	D	D	D								
	560pF (561)	S	S	S	S	D	D	D	D	D	D	D	D	D								
	680pF (681)	S	S	S	S	D	D	D	D	D	D	D	D	D								
	820pF (821)	S	S	S	S	D	D	D	D	D	D	D	D	D								
	1,000pF (102)	S	S	S	S	D	D	D	D	D	D	D	D	D	C	C	C	C	D	D	D	D
	1,200pF (122)	S	S	S	S	D	D	D	D	D	D	D	D	D	C	C	C	C	D	D	D	D
	1,500pF (152)	S	S	S	S	D	D	D	D	D	D	D	D	D	C	C	C	C	D	D	D	D
	1,800pF (182)	S	S	S	S	D	D	D	D	D	D	D	D	D	C	C	C	C	D	D	D	D
	2,200pF (222)	S	S	S	S	D	D	D	D	D	D	D	D	D	C	C	C	C	D	D	D	D
	2,700pF (272)	S	S	S	S	D	D	D	D	D	D	D	D	D	C	C	C	C	D	D	D	D
	3,300pF (332)	S	S	S	S	D	D	D	D	D	D	D	D	D	C	C	C	C	D	D	D	D
	3,900pF (392)	S	S	S	S	D	D	D	D	D	D	D	D	D	C	C	C	C	D	D	D	D
	4,700pF (472)	S	S	S	S	D	D	D	D	D	D	D	D	D	C	C	C	C	D	D	D	D
	5,600pF (562)	S	S	S	S	D	D	D	D	D	D	D	D	D	C	C	C	C	D	D	D	D
	6,800pF (682)	S	S	S	S	D	D	D	D	D	D	D	D	D	C	C	C	C	D	D	D	D
	8,200pF (822)	S	S	S	S	D	D	D	D	D	D	D	D	D	C	C	C	C	D	D	D	D
	0.010μF (103)	S	S	S	S	D	D	D	D	D	D	D	D	D	C	C	C	C	D	D	D	D
	0.012μF (123)	S	S	S		D	D	D	D	D	D	D	D	D	C	C	C	C	D	D	D	D
	0.015μF (153)	S	S	S		D	D	D	D	D	D	D	D	D	C	C	C	C	D	D	D	D
	0.018μF (183)	S	S	S		D	D	D	D	D	D	D	D	D	C	C	C	C	D	D	D	D
	0.022μF (223)	S	S	S		D	D	D	D	D	D	D	D	D	C	C	C	C	D	D	D	D
	0.027μF (273)	S	S	S		D	D	D		D	D	D	D	D	C	C	C	C	D	D	D	D
	0.033μF (333)	S	S	X		D	D	D		D	D	D	D	G	C	C	C	C	D	D	D	D
	0.039μF (393)	S	S	X		D	D	D		D	D	D	D	G	C	C	C	C	D	D	D	D
	0.047μF (473)	S	S	X		D	D	D		D	D	D	D	G	C	C	C	D	D	D	D	D
	0.056μF (563)	S	S	X		D	D	D		D	D	D	D	G	C	C	C	D	D	D	D	D
	0.068μF (683)	S	S	X		D	D	D		D	D	D	D	G	C	C	C	G	D	D	D	D
	0.082μF (823)	S	S	X		D	D	D		D	D	D	D	G	C	C	C	G	D	D	D	D
	0.10μF (104)	S	S	X		D	D	D		D	D	D	D	G	C	C	C	G	D	D	D	D
	0.12μF (124)	S	X			D	D			D	D	D	D		C	C	C	G	D	D	D	D
	0.15μF (154)	S	X			D	D			C	C	C	G		C	C	D	M	D	D	D	K
	0.18μF (184)	S	X			D	D			C	C	C	G		C	C	D	M	D	D	D	K
	0.22μF (224)	S	X			D	D			C	C	C	G		C	C	D	M	D	D	D	K
	0.27μF (274)	X	X			I				C	C	D			C	C	G	M	D	D	D	K
	0.33μF (334)	X	X			I				C	C	D			C	D	G	M	D	D	D	K
	0.39μF (394)	X	X			I				J	J	P			C	D	M	M	D	D	D	K
	0.47μF (474)	X	X			I				J	J	P			C	D	M	M	D	D	K	K
	0.56μF (564)	X				I				J	J	P			D	D	M		D	D	K	
	0.68μF (684)	X				I				J	J	P			D	D	K		D	K	K	
	0.82μF (824)					I				J	J	P			D	D	K		D	K	K	
	1.0μF (105)					I				J	J	P			D	D	K		D	K	K	
	1.5μF (155)									J	P											
	2.2μF (225)									J	P											
	3.3μF (335)									P	P											
	4.7μF (475)									P	P											

1. The letter in cell is expressed the symbol of product thickness.
2. For more information about products with special capacitance or other data, please contact WTC local representative

X7R Dielectric 500V To 3kV

DIELECTRIC		X7R															
SIZE		0805		1206				1210			1808			1812			
RATED VOLTAGE (VDC)		500	630	500	630	1000	2000	500	630	1000	500 630 1000	2000	3000	500 630	1000	2000	3000
Capacitance	100pF (101)	B	B														
	120pF (121)	B	B														
	150pF (151)	B	B	D	D	D	D				D	D	D				
	180pF (181)	B	B	D	D	D	D				D	D	D				
	220pF (221)	B	B	D	D	D	D				D	D	D				
	270pF (271)	B	B	D	D	D	D				D	D	D		D	D	
	330pF (331)	B	B	D	D	D	D				D	D	K		D	D	
	390pF (391)	B	B	D	D	D	D				D	D	K		D	D	
	470pF (471)	B	B	D	D	D	D				D	D	K		D	D	
	560pF (561)	B	B	D	D	D	D				D	D	K		D	D	
	680pF (681)	B	B	D	D	D	D				D	D	K		D	D	K
	820pF (821)	B	B	D	D	D	G				D	D	K		D	D	K
	1,000pF (102)	B	B	D	D	D	G	G	G	G	D	D	K	D	D	D	K
	1,200pF (122)	B	B	D	D	D		G	G	G	D	K		D	D	D	
	1,500pF (152)	B	B	D	D	D		G	G	G	D	K		D	D	D	
	1,800pF (182)	B	B	D	D	D		G	G	G	D	K		D	D	D	
	2,200pF (222)	B	B	D	D	D		G	G	G	D	K		D	D	D	
	2,700pF (272)	B	B	D	D	D		G	G	G	D			D	D	D	
	3,300pF (332)	B	B	D	D	D		G	G	G	D			D	D	K	
	3,900pF (392)	B	B	D	D	D		G	G	G	D			D	D	K	
	4,700pF (472)	D	D	D	D	D		G	G	G	D			D	D	K	
	5,600pF (562)	D	D	D	D	D		G	G	G	K			D	D		
	6,800pF (682)	D	D	D	D	D		G	G	G	K			D	D		
	8,200pF (822)	D	D	D	D	D		G	G	G	K			D	D		
	0.010μF (103)	D	D	D	D	D		G	G	G	K			D	D		
	0.012μF (123)			D	D			G	G					D	K		
	0.015μF (153)			D	D			G	G					D	K		
	0.018μF (183)			D	D			G	G					D			
	0.022μF (223)			G	G			G	G					D			
	0.027μF (273)			G	G			G	G					D			
	0.033μF (333)			G	G			G	G					D			
	0.039μF (393)							G	G					D			
	0.047μF (473)							G	G					D			
	0.056μF (563)							G	G					K			
	0.068μF (683)													K			
	0.082μF (823)													K			
	0.10μF (104)													K			
	0.12μF (124)																
	0.15μF (154)																
	0.18μF (184)																
	0.22μF (224)																
	0.27μF (274)																
	0.33μF (334)																
	0.39μF (394)																
	0.47μF (474)																
	0.56μF (564)																
	0.68μF (684)																
	0.82μF (824)																
	1.00μF (105)																

1. The letter in cell is expressed the symbol of product thickness.
2. For more information about products with special capacitance or other data, please contact WTC local representative

Open-Mode Design Capacitors
OP Series

■ FEATURES

* High voltage in a given case size.
* Circuit open during product cracking.
* High stability and reliability.

■ GENERAL ELECTRICAL DATA

Dielectric	X7R
Size	0805, 1206, 1210, 1812
Capacitance	100pF to 1μF
Capacitance tolerance	K (±10%), M (±20%)
Rated voltage (WVDC)	100V, 200V, 250V, 500V
Tan δ	≤2.5%
Insulation resistance at Ur	≥10GΩ or RxC≥500Ω-F whichever is smaller
Dielectric strength	100V: ≥2.5 x WVDC 200V and 250V: ≥2 x WVDC 500V: ≥1.5 x WVDC
Operating temperature	-55 to +125°C
Capacitance characteristic	±15%
Termination	Ni/Sn (lead-free termination)

■ EXPLANATION OF PART NUMBERS

OP	32	B	103	K	201	C	T
Series	Size (Inch (mm))	Dielectric	Capacitance	Tolerance	Rated voltage	Termination	Packaging
OP=Open-mode	32=1210 (3225)	B=X7R	$103=10x10^3=10nF$	K=±10%	201=200 VDC	C=Cu/Ni/Sn	T=7" reeled

* Please refer to page 2 " How to order" for more information.

■ INNER CONSTRUCTION OF OPEN-MODE DESIGN

Fig.5 Normal design ($CP<M_B$) – circuit leakage during cracking.

Fig. 6 Open-mode design ($CP>M_B$) – circuit open during cracking.

Fig. 7 Floating design (one kind of open-mode design) – circuit open during cracking.

■ CAPACITANCE RANGE

DIELECTRIC		X7R															
SIZE		0805				1206				1210				1812			
RATED VOLTAGE (VDC)		100	200	250	500	100	200	250	500	100	200	250	500	100	200	250	500
Capacitance	100pF (101)	B	B	B	B												
	120pF (121)	B	B	B	B												
	150pF (151)	B	B	B	B	B	D	D	D								
	180pF (181)	B	B	B	B	B	D	D	D								
	220pF (221)	B	B	B	B	B	D	D	D								
	270pF (271)	B	B	B	B	B	D	D	D								
	330pF (331)	B	B	B	B	B	D	D	D								
	390pF (391)	B	B	B	B	B	D	D	D								
	470pF (471)	B	B	B	B	B	D	D	D								
	560pF (561)	B	B	B	B	B	D	D	D								
	680pF (681)	B	B	B	B	B	D	D	D								
	820pF (821)	B	B	B	B	B	D	D	D								
	1,000pF (102)	B	B	B	B	B	D	D	D	C	C	C	D	D	D	D	D
	1,200pF (122)	B	B	B	B	B	D	D	D	C	C	C	D	D	D	D	D
	1,500pF (152)	B	B	B	B	B	D	D	D	C	C	C	D	D	D	D	D
	1,800pF (182)	B	B	B	B	B	D	D	D	C	C	C	D	D	D	D	D
	2,200pF (222)	B	B	B	B	B	D	D	D	C	C	C	D	D	D	D	D
	2,700pF (272)	B	B	B	B	B	D	D	D	C	C	C	D	D	D	D	D
	3,300pF (332)	B	B	B	B	B	D	D	D	C	C	C	D	D	D	D	D
	3,900pF (392)	B	B	B		B	D	D	D	C	C	C	D	D	D	D	D
	4,700pF (472)	B	B	B		B	D	D	D	C	C	C	D	D	D	D	D
	5,600pF (562)	B	D	D		B	D	D	D	C	C	C	D	D	D	D	D
	6,800pF (682)	B	D	D		B	D	D	D	C	C	C	D	D	D	D	D
	8,200pF (822)	B	D	D		B	D	D	D	C	C	C	D	D	D	D	D
	0.010μF (103)	B	D	D		B	D	D	D	C	C	C	D	D	D	D	D
	0.012μF (123)	B	D	D		B	D	D	D	C	C	C	D	D	D	D	D
	0.015μF (153)	B	D	D		B	D	D	D	C	C	C	D	D	D	D	D
	0.018μF (183)	B	D	D		B	D	D	D	C	C	C	D	D	D	D	D
	0.022μF (223)	B	D	D		B	D	D	G	C	C	C	D	D	D	D	D
	0.027μF (273)	D				B	D	D	G	C	C	C	D	D	D	D	D
	0.033μF (333)	D				B	G	G	G	C	C	C	G	D	D	D	D
	0.039μF (393)	D				B	G	G		C	C	C	G	D	D	D	D
	0.047μF (473)	D				B	G	G		C	D	D	G	D	D	D	D
	0.056μF (563)					B	G	G		C	D	D	G	D	D	D	K
	0.068μF (683)					B	G	G		C	G	G	G	D	D	D	K
	0.082μF (823)					D	G	G		C	G	G		D	D	D	K
	0.10μF (104)					D	G	G		C	G	G		D	D	D	K
	0.12μF (124)					D				C	G	G		D	D	D	
	0.15μF (154)					G				D	M	M		D	K	K	
	0.18μF (184)					G				D	M	M		D	K	K	
	0.22μF (224)					G				D	M	M		D	K	K	
	0.27μF (274)									G				D	K	K	
	0.33μF (334)									G				D	K	K	
	0.39μF (394)									M				D	K	K	
	0.47μF (474)									M				K	K	K	
	0.56μF (564)									M				K			
	0.68μF (684)													K			
	0.82μF (824)													K			
	1.0μF (105)													K			

1. The letter in cell is expressed the symbol of product thickness.
2. The letter in cell with "^" mark is expressed product with Ag/Ni/Sn terminations.
3. For more information about products with special capacitance or other data, please contact WTC local representative.

Capacitor Array Capacitors
Y4C3/Y4C2 Series

■ FEATURES

* High density mounting due to mounting space saving.
* Mounting cost saving.
* Increased throughput.

■ GENERAL ELECTRICAL DATA

Dielectric	NP0		X7R		Y5V
Size	4x0402	4x0603	4x0402	4x0603	4x0603
Capacitance*	10pF to 270pF	10pF to 470pF	1000pF to 100nF	180pF to 100nF	10nF to 100nF
Capacitance tolerance**	J (±5%), K (±10%)		K (±10%), M (±20%)		Z (-20/+80%)
Rated voltage (WVDC)	50V	25, 50V	10V, 16V, 25V, 50V	16V, 25V, 50V	16V, 50V
Q/Tan δ*	Cap<30pF: Q≥400+20C Cap≥30pF: Q≥1000		Ur=50V, ≤2.5% Ur=25V&16V, ≤3.5% Ur=10V, ≤5.0%		Ur=50V, ≤5% Ur=16V, ≤7%
Insulation resistance at Ur	≥10GΩ		≥10GΩ or RxC≥500ΩxF whichever is less		
Operating temperature	-55 to +125°C				-25 to +85°C
Capacitance characteristic	±30ppm		±15%		+30/-80%
Termination	Ni/Sn (lead-free termination)				

■ EXPLANATION OF PART NUMBERS

Y	4C	3	B	103	K	500	C	T
Series	Cap. Nr.	Termination pitch	Dielectric	Capacitance	Tolerance	Rated voltage	Termination	Packaging
Y=Capacitor array	4C=4xCap	3=0.03” pitch 2=0.02” pitch	B=X7R	103=10x10^3=10nF	K=±10%	500=50 VDC	C=Cu/Ni/Sn	T=7” reeled

* Please refer to page 2 “ How to order” for more information.

■ CAPACITANCE RANGE

SIZE		4 x 0402					4 x 0603						
DIELECTRIC		NP0	X7R				NP0		X7R			Y5V	
RATED VOLTAGE (VDC)		25,50	10	16	25	50	25	50	16	25	50	16	50
Capacitance	10pF (100)	T					B	B					
	15pF (150)	T					B	B					
	22pF (220)	T					B	B					
	33pF (330)	T					B	B					
	47pF (470)	T					B	B					
	68pF (680)	T					B	B					
	100pF (101)	T					B	B					
	150pF (151)	T					B	B					
	180pF (181)	T					B	B		B	B		
	220pF (221)	T					B	B		B	B		
	270pF (271)	T					B	B		B	B		
	330pF (331)						B	B		B	B		
	470pF (471)						B	B		B	B		
	6,80pF (681)									B	B		
	1,000pF (102)		T	T	T	T				B	B		
	1,500pF (152)		T	T	T	T				B	B		
	2,200pF (222)		T	T	T	T				B	B		
	3,300pF (332)		T	T	T	T				B	B		
	4,700pF (472)		T	T	T	T				B	B		
	6,800pF (682)		T	T	T	T				B	B		
	0.010μF (103)		T	T	T	T				B	B		B
	0.015μF (153)		T	T	T				B	B	B		B
	0.022μF (223)		T	T	T				B	B	B		B
	0.033μF (333)		T	T	T				B				B
	0.047μF (473)		T	T	T				B				B
	0.068μF (683)		T	T	T				B				B
	0.10μF (104)		T	T	T				B			B	B

1. The letter in cell is expressed the symbol of product thickness.
2. For more information about products with special capacitance or other data, please contact WTC local representative.

■ FEATURES

* Standard size with thin thickness.
* Small size with high capacitance.
* Capacitor with lead-free termination (pure Tin).

■ GENERAL ELECTRICAL DATA

Dielectric	X5R	Y5V
Size	0603, 0805, 1206, 1210	
Capacitance range	0.22μF to 22μF	1μF to 10μF
Capacitance tolerance	K (±10%), M (±20%)	Z (-20/+80%)
Rated voltage (WVDC)	6.3V, 10V, 16V, 25V, 50V	10V, 16V, 25V, 50V
Tan δ*	16V, 10V: ≤10.0% 6.3V: ≤15.0%	50V: ≤7% 25V: ≤9% 16V, 10V: ≤12.5%
Insulation resistance at Ur	RxC≥500ΩxF	
Operating temperature	-55 to +85°C	-25 to +85°C
Capacitance characteristic	±15%	+30/-80%
Termination	Ni/Sn (lead-free termination)	

■ EXPLANATION OF PART NUMBERS

TT	31	X	225	K	100	C	T
Series	Size (Inch (mm))	Dielectric	Capacitance	Tolerance	Rated voltage	Termination	Packaging
TT=Low profile	31=1206 (3216)	X=X5R	225=22x10^5=2.2μF	K=±10%	100=10 VDC	C=Cu/Ni/Sn	T=7" reeled

* Please refer to page 2 " How to order" for more information.

■ CAPACITANCE RANGE

Dielectric		X5R												
Size		0603		0805				1206					1210	
Rated voltage (VDC)		10	16	6.3	10	16	25	6.3	10	16	25	50	10	25
Capacitance	0.22uF (224)	H	H											
	1.0μF (105)	H	H		T	T	T		T	T	T			
	1.5μF (155)				T	T			T	T	T			
	2.2μF (225)			T	T	T	T		T	T	T	T		
	3.3μF (335)								T	T	T		T	
	4.7μF (475)			T	T	T	T		T	T	T		T	
	6.8μF (685)													
	10μF (106)			T	T			J	T		T			T
	22μF (226)			T				T						

Dielectric		Y5V									
Size		0805				1206				1210	
Rated voltage (VDC)		10	16	25	50	10	16	25	50	10	16
Capacitance	1.0μF (105)				T						
	1.5μF (155)										
	2.2μF (225)		T	T		T	T	T	T		
	3.3μF (335)	T									
	4.7μF (475)	T	T			T	T	T			
	6.8μF (685)					T					
	10μF (106)	T				T				T	
	22μF (226)										

1. The letter in cell is expressed the symbol of product thickness.
2. For more information about products with special capacitance or other data, please contact WTC local representative.

Low Inductance Capacitors 0612 Series

■ FEATURES

* Standard size with thin thickness.
* Small size with high capacitance.
* Capacitor with lead-free termination (pure Tin).
* MLCC with low ESL performance.

■ GENERAL ELECTRICAL DATA

Dielectric	X7R
Size	0612
Capacitance range	10nF to 150nF
Capacitance tolerance	K (±10%), M (±20%)
Rated voltage (WVDC)	50V
Tan δ*	≤2.5%
Insulation resistance at Ur	≥10GΩ or RxC≥500ΩxF whichever is less
Operating temperature	-55 to +125°C
Capacitance characteristic	±15%
Termination	Ni/Sn (lead-free termination)
ESL	500pH

■ EXPLANATION OF PART NUMBERS

0612	B	103	K	500	C	T
Size (Inch (mm))	Dielectric	Capacitance	Tolerance	Rated voltage	Termination	Packaging
0612(1632)	B=X7R	103=10x10^3=10nF	K=±10%	500=50 VDC	C=Cu/Ni/Sn	T=7" reeled

* Please refer to page 2 " How to order" for more information.

■ CAPACITANCE RANGE

DIELECTRIC		X7R
SIZE		0612
RATED VOLTAGE (VDC)		50
Capacitance	10nF (103)	B
	12nF (123)	B
	15nF (153)	B
	18nF (183)	B
	22nF (223)	B
	27nF (273)	B
	33nF (333)	B
	39nF (393)	B
	47nF (473)	B
	56nF (563)	B
	68nF (683)	B
	82nF (823)	B
	100nF (104)	B
	120nF (124)	B
	150nF (154)	B

1. The letter in cell is expressed the symbol of product thickness.
2. For more information about products with special capacitance or other data, please contact WTC local representative.

■ FEATURES

* High voltage in a given case size.
* High stability and reliability.
* RoHS compliant.

■ GENERAL ELECTRICAL DATA

Dielectric	NP0	X7R
Size	1808	1808, 1812,2211
Capacitance	10pF to 150pF	100pF to 2200pF
Capacitance tolerance	J (±5%), K (±10%)	
Rated voltage (WVAC)	250Vrms	
Q	Cap<30pF: Q≥400+20C	Tan δ≤2.5%
Insulation resistance at Ur	≥10GΩ	
Dielectric withstanding strength	1500VAC	
Peak impulse voltage	5000V	
Operating temperature	-55 to +125°C	
Capacitance characteristic	±60ppm	±15%
Termination	Ni/Sn (lead-free termination)	
Certified number	TUV: R50118359, UL: E250427, E82369	
Test standard	EN 132400, 1994+A2+A3+A4; IEC 60384-14, 1993+A1, Class X1Y2, UL 60950,UL 60384-14	

■ EXPLANATION OF PART NUMBERS

S2	42	N	100	J	302	L	T
Series S2=X1/Y2	Size (Inch (mm)) 42=1808 (4520)	Dielectric N=NP0	Capacitance $100=10x10^0=10pF$	Tolerance J=±5%	Rated voltage 302=3000 VDC 502=5000 Impulse Voltage	Termination L=Ag/Ni/Sn	Packaging T=7" reeled

* Please refer to page 2 " How to order" for more information.

■ CAPACITANCE RANGE

DIELECTRIC		NP0
SIZE		1808
RATED VOLTAGE (VDC)		3000
PEAK IMPULSE VOLTAGE		5000
Capacitance	10pF (100)	F
	12pF (120)	F
	15pF (150)	F
	18pF (180)	F
	22pF (220)	F
	27pF (270)	F
	33pF (330)	F
	39pF (390)	G
	47pF (470)	G
	56pF (560)	G
	68pF (680)	G
	82pF (820)	G
	100pF (101)	K
	120pF (121)	K
	150pF (151)	K
	180pF (181)	
	220pF (221)	
	270pF (271)	
	330pF (331)	
	390pF (391)	
	470pF (471)	

DIELECTRIC		X7R		
SIZE		1808	1812	2211
RATED VOLTAGE (VDC)		3000	3000	3000
PEAK IMPULSE VOLTAGE		5000	5000	5000
Capacitance	56pF (560)			
	68pF (680)			
	82pF (820)			
	100pF (101)	G		
	120pF (121)	G		
	150pF (151)	G	G	G
	180pF (181)	G	G	G
	220pF (221)	G	G	G
	270pF (271)	K	G	G
	330pF (331)	K	G	G
	390pF (391)	K	G	G
	470pF (471)	K	G	K
	560pF (561)	K	G	K
	680pF (681)	K	K	K
	820pF (821)	K	K	K
	1,000pF (102)	K	M	M
	1,200pF (122)			M
	1,500pF (152)			M
	1,800pF (182)			M
	2,200pF (222)			M

1. The letter in cell is expressed the symbol of product thickness.
2. For more information about products with special capacitance or other data, please contact WTC local representative.

■ PACKAGING DIMENSION AND QUANTITY (X1/Y2 & X2/Y3 Series)

Size Inch (mm)	L (mm)	W (mm)	MB (mm)	T (mm)/Symbol		7" Plastic tape
1808 (4520)	4.50+0.5/-0.3	2.03±0.25	0.50±0.25	1.25±0.10	D	2,000
				1.40±0.15	F	2,000
				1.60±0.20	G	1,000
				2.00±0.20	K	1,000
1812 (4532)	4.50+0.5/-0.3	3.20±0.30	0.50±0.25	1.25±0.10	D	1,000
				1.60±0.20	G	1,000
				2.00±0.20	K	1,000
				2.50±0.30	M	500
2211 (5728)	5.70±0.40	2.80±0.30	0.85±0.55	1.60±0.20	G	1,000
				2.00±0.20	K	1,000
				2.50±0.30	M	500

Safety Certificated Capacitors X2/Y3
S3 Series

■ FEATURES

* High voltage in a given case size.
* High stability and reliability.
* RoHS compliant.

■ GENERAL ELECTRICAL DATA

Dielectric	NP0	X7R
Size	1808, 1812	
Capacitance*	3.9pF to 680pF	180pF to 2700pF
Capacitance tolerance	J (±5%), K (±10%)	K (±10%), M (±20%)
Rated voltage (WVDC)	2000V, 3000V	
Rated voltage (WVAC)	250Vrms	
Q/Tan δ	Cap<30pF: Q≥400+20C Cap≥30pF: Q≥1000	Tan δ≤2.5%
Insulation resistance at Ur	≥10GΩ	
Dielectric withstanding strength	1500VAC	
Peak impulse voltage (X2)	2500V	
Operating temperature	-55 to +125°C	
Capacitance characteristic	±60ppm	±15%
Termination	Ni/Sn (lead-free termination)	
Certified number	TUV: R50118359, UL: E250427, E82369	
Test standard	EN 132400, 1994+A2+A3+A4; IEC 60384-14, 1993+A1, Class X2Y3 EN 60950, Third Edition (2000), UL 60950,UL 60384-14	

■ EXPLANATION OF PART NUMBERS

S3	42	N	100	J	202	L	T
Series	Size (Inch (mm))	Dielectric	Capacitance	Tolerance	Rated voltage	Termination	Packaging
S3=X2/Y3	42=1808 (4520)	N=NP0	100=10x10^0 =10pF	J=±5%	202=2000 VDC	L=Ag/Ni/Sn	T=7" reeled

* Please refer to page 2 " How to order" for more information.

■ CAPACITANCE RANGE

DIELECTRIC		NP0	
SIZE		1808	
RATED VOLTAGE (VDC)		2000	3000
Capacitance	3.9pF (3R9)		F
	4.7pF (4R7)		F
	5.0pF (5R0)		F
	5.6pF (5R6)		F
	6.8pF (6R8)		F
	8.2pF (8R2)		F
	10pF (100)	F	F
	12pF (120)	F	F
	15pF (150)	F	F
	18pF (180)	F	F
	22pF (220)	F	F
	27pF (270)	F	F
	33pF (330)	F	F
	39pF (390)	G	G
	47pF (470)	G	G
	56pF (560)	G	G
	68pF (680)	G	G
	82pF (820)	G	G
	100pF (101)	K	K
	120pF (121)	K	K
	150pF (151)	K	K
	180pF (181)	K	K
	220pF (221)	K	K
	270pF (271)	K	K
	330pF (331)	K	
	390pF (391)	K	
	470pF (471)	K	
	560pF (561)	K	
	680pF (681)	K	
	820pF (821)		
	1,000pF (102)		

DIELECTRIC		X7R			
SIZE		1808		1812	
RATED VOLTAGE (VDC)		2000	3000	2000	3000
Capacitance	150pF (151)				
	180pF (181)	G			
	220pF (221)	G			
	270pF (271)	G			
	330pF (331)	G	G	G	
	390pF (391)	G	G	G	
	470pF (471)	G	G	G	
	560pF (561)	G	G	G	
	680pF (681)	G	G	G	G
	820pF (821)	G	G	G	G
	1,000pF (102)	K	K	G	G
	1,200pF (122)	K		G	
	1,500pF (152)	K		K	
	1,800pF (182)	K		K	
	2,200pF (222)			M	
	2,700pF (272)			M	
	3,300pF (332)				
	3,900pF (392)				
	4,700pF (472)				

1. The letter in cell is expressed the symbol of product thickness.
2. For more information about products with special capacitance or other data, please contact WTC local representative.

■ FEATURES

* High voltage in a given case size.
* Low DF value.
* Low power consumption in AC voltage application.

■ GENERAL ELECTRICAL DATA

Dielectric	X7R/ X7E
Size	1206
Capacitance	150pF to 0.1μF
Capacitance tolerance	K (±10%), M (±20%)
Rated voltage (WVDC)	100V, 200V, 250V, 350V, 500V, 630V
Tan δ*	100V : ≤1.4% ≥200V : ≤1.0%
Insulation resistance at Ur	≥10GΩ or RxC≥500Ω-F whichever is smaller
Dielectric strength	100 to 350V: ≥2 x WVDC 500V & 630V: ≥1.5 x WVDC
Operating temperature	-55 to +125°C
Capacitance characteristic	X7R: ±15% ; X7E: ±4.7%
Termination	Ni/Sn (lead-free termination)

■ EXPLANATION OF PART NUMBERS

LD	31	B	102	K	201	L	T
Series	Size (Inch (mm))	Dielectric	Capacitance	Tolerance	Rated voltage	Termination	Packaging
LD=Low distortion	31=1206 (3216)	B=X7R D=X7E	102=10x10^2 =1000pF	K=±10%	201=200 VDC	L=Cu/Ni/Sn	T=7" reeled

* Please refer to page 2 " How to order" for more information.
* All LD series products with Ag/Ni/Sn terminations.

■ CAPACITANCE RANGE

DIELECTRIC		X7R / X7E					
SIZE		1206					
RATED VOLTAGE (VDC)		100	200	250	350	500	630
Capacitance	100pF (101)						
	120pF (121)						
	150pF (151)	D	D	D	D	D	D
	180pF (181)	D	D	D	D	D	D
	220pF (221)	D	D	D	D	D	D
	270pF (271)	D	D	D	D	D	D
	330pF (331)	D	D	D	D	D	D
	390pF (391)	D	D	D	D	D	D
	470pF (471)	D	D	D	D	D	D
	560pF (561)	D	D	D	D	D	D
	680pF (681)	D	D	D	D	D	D
	820pF (821)	D	D	D	D	D	D
	1,000pF (102)	D	D	D	D	D	D
	1,200pF (122)	D	D	D	D	D	D
	1,500pF (152)	D	D	D	D	D	D
	1,800pF (182)	D	D	D	D	D	D
	2,200pF (222)	D	D	D	D	D	D
	2,700pF (272)	D	D	D	D	D	D
	3,300pF (332)	D	D	D	D	D	D
	3,900pF (392)	D	D	D	D	D	D
	4,700pF (472)	D	D	D	D	D	D
	5,600pF (562)	D	D	D	D	D	D
	6,800pF (682)	D	D	D	D	D	D
	8,200pF (822)	D	D	D	D	D	D
	0.010μF (103)	D	D	D	D	D	D
	0.012μF (123)	D	D	D	D	D	D
	0.015μF (153)	D	D	D	D	D	D
	0.018μF (183)	D	D	D	D	G	G
	0.022μF (223)	D	D	D	D	G	G
	0.027μF (273)	D	D	D	D	G	G
	0.033μF (333)	D	D	D	D	G	G
	0.039μF (393)	D	D	D	D		
	0.047μF (473)	D	D	D	D		
	0.056μF (563)	D					
	0.068μF (683)	D					
	0.082μF (823)	D					
	0.1.μF (104)	D					

1. The letter in cell is expressed the symbol of product thickness.
2. For more information about products with special capacitance or other data, please contact WTC local representative.

Automotive Capacitors without AEC-Q200
MG Series

■ FEATURES

* A wide selection of sizes is available (0402 to 1812).
* High capacitance in given case size.
* Capacitor with lead-free termination (pure Tin).
* High reliability design with severe quality controls.

■ GENERAL ELECTRICAL DATA

Dielectric	NP0	X7R	X5R
Size	0402, 0603, 0805, 1206, 1210, 1812		
Capacitance range*	0.5pF to 0.033μF	100pF to 2.2μF	0.056μF to 10μF
Capacitance tolerance**	Cap≤5pF: B (±0.1pF), C (±0.25pF) 5pF<Cap<10pF: C (±0.25pF), D (±0.5pF) Cap≥10pF: F (±1%), G (±2%), J (±5%)	J (±5%), K (±10%), M (±20%)	
Rated voltage (WVDC)	16V, 25V, 50V, 100V	10V, 16V, 25V, 50V, 100V, 200V, 250V	6.3V, 10V, 16V, 25V
Insulation resistance at Ur	≥10GΩ or RxC≥500Ω-F whichever is less		
Operating temperature	-55 to +125°C		-55 to +85°C
Capacitance characteristic	±30ppm/°C		±15%
Termination	Ni/Sn (lead-free termination)		

■ EXPLANATION OF PART NUMBERS

MG	31	B	104	K	500	C	T
Series MG= Automotive (without AEC-Q200 certification)	**Size (Inch (mm))** 31=1206 (3216)	**Dielectric** B=X7R	**Capacitance** 102=10x10^4 =0.1uF	**Tolerance** K=±10%	**Rated voltage** 500=50 VDC	**Termination** C=Cu/Ni/Sn	**Packaging** T=7" reeled

* Please refer to page 2 " How to order" for more information.

■ CAPACITANCE RANGE

X5R Dielectric

Dielectric		X5R																
Size		0402			0603				0805				1206				1210	
Rated Voltage(VDC)		6.3	10	16	6.3	10	16	25	6.3	10	16	25	6.3	10	16	25	10	16
Capacitance	0.056μF (563)		N															
	0.068μF (683)		N															
	0.082μF (823)		N															
	0.10μF (104)		N	N														
	0.15μF (154)		N	N														
	0.22μF (224)	N	N	N				X										
	0.27uF (274)	N	N			X	X	X										
	0.33μF (334)	N	N			X	X	X										
	0.39μF (394)	N				X	X	X										
	0.47μF (474)	N				X	X	X										
	0.68μF (684)	N				X	X	X										
	0.82uF (824)	N			X	X	X	X										
	1.0μF (105)				X	X	X	X										
	1.5μF (155)								I	I				J	J	P	K	K
	2.2μF (225)								I	I	I	I		J	J	P	K	K
	3.3μF (335)										I	I	P	P	P	P	K	K
	4.7μF (475)										I	I	P	P	P	P	K	K
	6.8uF (685)												P	P				
	10μF (106)												P	P				

1. The letter in cell is expressed the symbol of product thickness.
2. For more information about products with special capacitance or other data, please contact WTC local representative.

NP0 Dielectric

Dielectric		NP0												
Size		0402	0603	0805				1206		1210			1812	
Rated Voltage (VDC)		10,16, 25,50, 100	10,16, 25,50, 100	10,16, 25,50, 100	200	250	500, 630	10,16, 25,50,	100	10,16	25,50	100	10,16, 25,50	100
Capacitance	0.1pF (0R1)													
	0.2pF (0R2)													
	0.3pF (0R3)													
	0.4pF (0R4)													
	0.5pF (0R5)	N	S	A	A	A	A							
	0.6pF (0R6)	N	S	A	A	A	A							
	0.7pF (0R7)	N	S	A	A	A	A							
	0.8pF (0R8)	N	S	A	A	A	A							
	0.9pF (0R9)	N	S	A	A	A	A							
	1.0pF (1R0)	N	S	A	A	A	A							
	1.2pF (1R2)	N	S	A	A	A	A							
	1.5pF (1R5)	N	S	A	A	A	A	B	B					
	1.8pF (1R8)	N	S	A	A	A	A	B	B					
	2.2pF (2R2)	N	S	A	A	A	A	B	B					
	2.7pF (2R7)	N	S	A	A	A	A	B	B					
	3.3pF (3R3)	N	S	A	A	A	A	B	B					
	3.9pF (3R9)	N	S	A	A	A	A	B	B					
	4.7pF (4R7)	N	S	A	A	A	A	B	B					
	5.6pF (5R6)	N	S	A	A	A	A	B	B					
	6.8pF (6R8)	N	S	A	A	A	A	B	B					
	8.2pF (8R2)	N	S	A	A	A	A	B	B					
	10pF (100)	N	S	A	A	A	A	B	B	C	C	C	D	D
	12pF (120)	N	S	A	A	A	A	B	B	C	C	C	D	D
	15pF (150)	N	S	A	A	A	A	B	B	C	C	C	D	D
	18pF (180)	N	S	A	A	A	A	B	B	C	C	C	D	D
	22pF (220)	N	S	A	A	A	A	B	B	C	C	C	D	D
	27pF (270)	N	S	A	A	A	A	B	B	C	C	C	D	D
	33pF (330)	N	S	A	A	A	A	B	B	C	C	C	D	D
	39pF (390)	N	S	A	A	A	A	B	B	C	C	C	D	D
	47pF (470)	N	S	A	A	A	A	B	B	C	C	C	D	D
	56pF (560)	N	S	A	A	A	A	B	B	C	C	C	D	D
	68pF (680)	N	S	A	A	A	A	B	B	C	C	C	D	D
	82pF (820)	N	S	A	A	A	B	B	B	C	C	C	D	D
	100pF (101)	N	S	A	A	B	B	B	B	C	C	C	D	D
	120pF (121)	N	S	A	A	B	D	B	B	C	C	C	D	D
	150pF (151)	N	S	A	B	D	D	B	B	C	C	C	D	D
	180pF (181)	N	S	A	B	D	D	B	B	C	C	C	D	D
	220pF (221)	N	S	A	D	D	D	B	B	C	C	C	D	D
	270pF (271)		S	A	D	D	D	B	B	C	C	C	D	D
	330pF (331)		S	A	D	D	D	B	B	C	C	C	D	D
	390pF (391)		S	B	D	D	D	B	B	C	C	C	D	D
	470pF (471)		S	B	D			B	B	C	C	C	D	D
	560pF (561)		S	B	D			B	B	C	C	C	D	D
	680pF (681)		S	B	D			B	B	C	C	C	D	D
	820pF (821)		S	B	D			B	B	C	C	C	D	D
	1,000pF (102)		S	B				B	B	C	C	C	D	D
	1,200pF (122)			B				B	B	C	C	C	D	D
	1,500pF (152)			B				B	B	C	C	C	D	D
	1,800pF (182)			B				B	B	C	C	C	D	D
	2,200pF (222)			B				B	B	C	C	C	D	D
	2,700pF (272)			D				B	B	C	C	C	D	D
	3,300pF (332)							B	B	C	C	C	D	D
	3,900pF (392)							B	B	C	C	C	D	D
	4,700pF (472)							B	B	C	C	C	D	D
	5,600pF (562)							B	B	C	C	C	D	D
	6,800pF (682)							C		C	C	C	D	D
	8,200pF (822)							D		C	C	C	D	D
	0.010uF (103)							D		C	C	C	D	D
	0.012uF (123)									C	D	D	D	D
	0.015uF (153)									C	D	D	D	D
	0.018uF (183)												D	D
	0.022uF (223)												D	D
	0.027uF (273)												D	D
	0.033uF (333)												D	D

1. The letter in cell is expressed the symbol of product thickness.
2. The letter in cell with "^" mark is expressed product with Ag/Ni/Sn terminations.
3. For more information about products with special capacitance or other data, please contact WTC local representative.

Automotive Capacitors without AEC-Q200
MG Series

X7R Dielectric

Dielectric		X7R																									
Size		0402			0603				0805					1206					1210					1812			
Rated Voltage (VDC)		10, 16	25	50	6.3, 10, 16	25	50	100	6.3	10, 16, 25	50	100	200, 250	10, 16	25	50	100	200, 250	10, 16	25	50	100	200, 250	10, 16, 25	50	100	200, 250
Capacitance	100pF (101)	N	N	N	S	S	S	S	B	B	B	B	B														
	120pF (121)	N	N	N	S	S	S	S	B	B	B	B	B														
	150pF (151)	N	N	N	S	S	S	S	B	B	B	B	B	B	B	B	B	B									
	180pF (181)	N	N	N	S	S	S	S	B	B	B	B	B	B	B	B	B	B									
	220pF (221)	N	N	N	S	S	S	S	B	B	B	B	B	B	B	B	B	B									
	270pF (271)	N	N	N	S	S	S	S	B	B	B	B	B	B	B	B	B	B									
	330pF (331)	N	N	N	S	S	S	S	B	B	B	B	B	B	B	B	B	B									
	390pF (391)	N	N	N	S	S	S	S	B	B	B	B	B	B	B	B	B	B									
	470pF (471)	N	N	N	S	S	S	S	B	B	B	B	B	B	B	B	B	B									
	560pF (561)	N	N	N	S	S	S	S	B	B	B	B	B	B	B	B	B	B									
	680pF (681)	N	N	N	S	S	S	S	B	B	B	B	B	B	B	B	B	B									
	820pF (821)	N	N	N	S	S	S	S	B	B	B	B	B	B	B	B	B	B									
	1,000pF (102)	N	N	N	S	S	S	S	B	B	B	B	B	B	B	B	B	B	C	C	C	C	C	D	D	D	D
	1,200pF (122)	N	N	N	S	S	S	S	B	B	B	B	B	B	B	B	B	B	C	C	C	C	C	D	D	D	D
	1,500pF (152)	N	N	N	S	S	S	S	B	B	B	B	B	B	B	B	B	B	C	C	C	C	C	D	D	D	D
	1,800pF (182)	N	N	N	S	S	S	S	B	B	B	B	B	B	B	B	B	B	C	C	C	C	C	D	D	D	D
	2,200pF (222)	N	N	N	S	S	S	S	B	B	B	B	B	B	B	B	B	B	C	C	C	C	C	D	D	D	D
	2,700pF (272)	N	N	N	S	S	S	S	B	B	B	B	B	B	B	B	B	B	C	C	C	C	C	D	D	D	D
	3,300pF (332)	N	N	N	S	S	S	S	B	B	B	B	B	B	B	B	B	B	C	C	C	C	C	D	D	D	D
	3,900pF (392)	N	N	N	S	S	S	S	B	B	B	B	B	B	B	B	B	B	C	C	C	C	C	D	D	D	D
	4,700pF (472)	N	N	N	S	S	S	S	B	B	B	B	B	B	B	B	B	B	C	C	C	C	C	D	D	D	D
	5,600pF (562)	N	N	N	S	S	S	S	B	B	B	B	D	B	B	B	B	B	C	C	C	C	C	D	D	D	D
	6,800pF (682)	N	N	N	S	S	S	S	B	B	B	B	D	B	B	B	B	B	C	C	C	C	C	D	D	D	D
	8,200pF (822)	N	N	N	S	S	S	S	B	B	B	B	D	B	B	B	B	B	C	C	C	C	C	D	D	D	D
	0.010uF (103)	N	N	N	S	S	S	S	B	B	B	B	D	B	B	B	B	B	C	C	C	C	C	D	D	D	D
	0.012uF (123)	N	N		S	S	S		B	B	B	B	D	B	B	B	B	B	C	C	C	C	C	D	D	D	D
	0.015uF (153)	N	N		S	S	S		B	B	B	B	D	B	B	B	B	C	C	C	C	C	C	D	D	D	D
	0.018uF (183)	N	N		S	S	S		B	B	B	B	D	B	B	B	B	C	C	C	C	C	C	D	D	D	D
	0.022uF (223)	N	N		S	S	S		B	B	B	B	D	B	B	B	B	C	C	C	C	C	C	D	D	D	D
	0.027uF (273)	N	N		S	S	S			B	B	D		B	B	B	B	C	C	C	C	C	C	D	D	D	D
	0.033uF (333)	N	N		S	S	X			B	B	D		B	B	B	B	G	C	C	C	C	C	D	D	D	D
	0.039uF (393)	N	N		S	S	X			B	B	D		B	B	B	B	G	C	C	C	C	C	D	D	D	D
	0.047uF (473)	N	N		S	S	X			B	B	D		B	B	B	B	G	C	C	C	C	D	D	D	D	D
	0.056uF (563)	N			S	S	X			B	B	D		B	B	B	B	G	C	C	C	C	D	D	D	D	D
	0.068uF (683)	N			S	S	X			B	B	D		B	B	B	B	G	C	C	C	C	G	D	D	D	D
	0.082uF (823)	N			S	S	X			B	B	D		B	B	B	D	G	C	C	C	C	G	D	D	D	D
	0.10uF (104)	N			S	S	X			B	B	D		B	B	B	D	G	C	C	C	C	G	D	D	D	D
	0.12uF (124)				S	X				D	D			B	B	B	D		C	C	C	C	G	D	D	D	D
	0.15uF (154)				S	X				D	D			C	C	C	G		C	C	C	D	M	D	D	D	K
	0.18uF (184)				S	X				D	D			C	C	C	G		C	C	C	D	M	D	D	D	K
	0.22uF (224)				S	X				D	D			C	C	C	G		C	C	C	D	M	D	D	D	K
	0.27uF (274)				X					D				C	C	D			C	C	C	G	M	D	D	D	K
	0.33uF (334)				X					D				C	C	D			C	C	D	G	M	D	D	D	K
	0.39uF (394)				X					D				C	J	P			C	C	D	M	M	D	D	D	K
	0.47uF (474)				X					D				J	J	P			C	C	D	M	M	D	D	K	K
	0.56uF (564)									D				J	J	P			D	D	D	M		D	D	K	
	0.68uF (684)									D				J	J	P			D	D	D	K		D	K	K	
	0.82uF (824)									D				J	J	P			D	D	D	K		D	K	K	
	1.0uF (105)									D				J	J	P			D	D	D	K		D	K	K	
	1.5uF (155)													J	P				K	G						K	
	2.2uF (225)													J	P				K	G						M	

1. The letter in cell is expressed the symbol of product thickness.
2. 0805 size, Cap.1.0uF_10V only.
3. For more information about products with special capacitance or other data, please contact WTC local representative.

* About Reliability Test Conditions and Requirements, please refer to Walsin MLCC approval sheet for more detail.

<table>
<tr><th>No</th><th>Item</th><th>Test Condition</th><th>Requirements</th></tr>
<tr><td>1.</td><td>Visual and Mechanical</td><td>---</td><td>* No remarkable defect.
* Dimensions to conform to individual specification sheet.</td></tr>
<tr><td>2.</td><td>Capacitance</td><td rowspan="2">Class I: NP0
Cap≤1000pF 1.0±0.2Vrms, 1MHz±10%
Cap>1000pF 1.0±0.2Vrms, 1KHz±10%

Class II: X7R,X7E, X5R,Y5V
Cap≤10μF, 1.0±0.2Vrms, 1kHz±10% **
Cap>10μF, 0.5±0.2Vrms, 120Hz±20%

** Test condition: 0.5±0.2Vrms, 1KHz±10%
X7R: 0603≥225(10V),
0805=106(6.3V&10V)
X5R: 01R5≥103, 0201≥224 (6.3V),
0402≥475 (6.3V), 0402≥225(10V),
0603=106 (6.3V)
TT18X≥475(10V) , TT15X series</td><td>* Shall not exceed the limits given in the detailed spec.</td></tr>
<tr><td>3.</td><td>Q/ D.F. (Dissipation Factor)</td><td>NP0: Cap≥30pF, Q≥1000; Cap<30pF,Q≥400+20C
X7R, X5R:
<table>
<tr><th>Rated vol.</th><th>D.F.≤</th><th colspan="2">Exception of D.F. ≤</th></tr>
<tr><td rowspan="3">≥50V</td><td rowspan="3">≤2.5%</td><td>≤3%</td><td>0201(50V); 0603≥0.047μF;
0805≥0.18μF;1206≥0.47μF</td></tr>
<tr><td>≤5%</td><td>1210≥4.7μF</td></tr>
<tr><td>≤10%</td><td>0603≥1μF; 0805≥1μF;1206≥2.2μF; 1210≥10μF</td></tr>
<tr><td>35V</td><td>≤3.5%</td><td>≤10%</td><td>0805≥2.2μF; 1210≥10μF</td></tr>
<tr><td rowspan="3">25V</td><td rowspan="3">≤3.5%</td><td>≤5%</td><td>0201≥0.01μF;0805≥1μF; 1210≥10μF</td></tr>
<tr><td>≤7%</td><td>0603≥0.33μF; 1206≥4.7μF</td></tr>
<tr><td>≤10%</td><td>0402≥0.10μF;0603≥0.47μF; 0805≥2.2μF;
1206≥6.8μF; 1210≥22μF ; TT series</td></tr>
<tr><td rowspan="2">16V</td><td rowspan="2">≤3.5%</td><td>≤5%</td><td>0201≥0.01μF; 0402≥0.033μF; 0603≥0.15μF;
0805≥0.68μF; 1206≥2.2μF; 1210≥4.7μF</td></tr>
<tr><td>≤10%</td><td>0402≥0.22uF; 0603≥0.68μF;0805≥2.2μF;
1206≥4.7μF; 1210≥22μF; TT series</td></tr>
<tr><td rowspan="2">10V</td><td rowspan="2">≤5%</td><td>≤10%</td><td>0201≥0.012μF;0402≥0.33μF;0603≥0.33μF;
0805≥2.2μF;1206≥2.2μF;1210≥22μF; TT series</td></tr>
<tr><td>≤15%</td><td>0201≥0.1μF; 0402≥1μF</td></tr>
<tr><td rowspan="2">6.3V</td><td rowspan="2">≤10%</td><td>≤15%</td><td>0201≥0.1μF;0402≥1μF;0603≥10μF; 0805≥4.7μF;
1206≥47μF :1210≥100μF; TT series</td></tr>
<tr><td>≤20%</td><td>0402≥2.2μF</td></tr>
<tr><td>4V</td><td>≤15%</td><td>---</td><td>---</td></tr>
</table>
X7R/X7E, LD series : 100V: DF≤1.4%; ≤200V:DF≤1.0%
Y5V:
<table>
<tr><th>Rated vol.</th><th>D.F. ≤</th><th colspan="2">Exception of D.F.≤</th></tr>
<tr><td>≥50V</td><td>≤5%</td><td>≤7%</td><td>0603≥0.1μF; 0805≥0.47μF; 1206≥4.7μF; TT series & Cap≥1μF</td></tr>
<tr><td>35V</td><td>≤7%</td><td>---</td><td>---</td></tr>
<tr><td rowspan="2">25V</td><td rowspan="2">≤5%</td><td>≤7%</td><td>0402≥0.047μF;0603≥0.1μF; 0805≥0.33μF;1206≥1μF;
1210≥4.7μF</td></tr>
<tr><td>≤9%</td><td>0402≥0.068μF;0603≥0.47μF; 1206≥4.7μF;
1210≥22μF; TT series & Cap≥1μF</td></tr>
<tr><td rowspan="2">16V
(C<1.0μF)</td><td rowspan="2">≤7%</td><td>≤9%</td><td>0402≥0.068μF; 0603≥0.68μF</td></tr>
<tr><td>≤12.5%</td><td>0402≥0.22μF</td></tr>
<tr><td>16V
(C≥1.0μF)</td><td>≤9%</td><td>≤12.5%</td><td>0603≥2.2μF; 0805≥3.3μF;1206≥10μF; 1210≥22μF;
1812≥47μF; TT series & Cap≥1μF</td></tr>
<tr><td>10V</td><td>≤12.5%</td><td>≤20%</td><td>0402≥0.47μF</td></tr>
<tr><td>6.3V</td><td>≤20%</td><td>---</td><td>---</td></tr>
</table></td></tr>
<tr><td>4a.</td><td>Dielectric Strength</td><td>*To apply voltage(≤100V) 250%.
*Duration: 1 to 5 sec.
*Charge & discharge current less than 50mA.

*To apply voltage:
200V ~300V & LD series ≥2 times V DC
500V ~ 999V ≥1.5 times V DC
1000V ~ 3000V ≥1.2 times V DC
*Cut-off, set at 10mA
*TEST= 15 sec. *RAMP=0</td><td>*No evidence of damage or flash over during test.</td></tr>
<tr><td>4b.</td><td>Dielectric Strength (for X1/Y2 & X2/Y3)</td><td>* To apply 1500 VAC voltage.
* Duration: 60 sec.</td><td>* No evidence of damage or flash over during test.</td></tr>
<tr><td>5.</td><td>Insulation Resistance</td><td>To apply rated voltage for max. 120 sec.</td><td>10GΩ or RxC≥500Ω-F whichever is smaller.
Class II (X7R, X7E, X5R, Y5V)
<table>
<tr><th>Rated voltage</th><th>Insulation Resistance</th></tr>
<tr><td>100V: X7R</td><td rowspan="7">10GΩ or RxC≥100 Ω-F whichever is smaller.</td></tr>
<tr><td>50V:0603≥1μF;0805≥1μF;1206≥2.2μF;1210≥4.7μF</td></tr>
<tr><td>35V:0805≥2.2μF;1210≥10μF</td></tr>
<tr><td>25V:0402≥1μF;0603≥2.2μF;0805≥2.2μF;1206≥10μF;1210≥10μF</td></tr>
<tr><td>16V:0402≥0.22μF;0603≥1μF;0805≥2.2μF;1206≥10μF;1210≥47μF</td></tr>
<tr><td>10V:0201≥47nF;0402≥0.47μF;0603≥0.47μF; 0805≥2.2μF;
1206≥4.7μF;1210≥47μF</td></tr>
<tr><td>6.3V ; 4V ; TT series</td></tr>
</table></td></tr>
<tr><td></td><td></td><td>Rated Voltage:
200V ~ 630V
To apply rated voltage (500V max.) for 60 sec.</td><td>>10GΩ or 100Ω-F whichever is smaller.</td></tr>
<tr><td></td><td></td><td>Rated Voltage: >630V
To apply 500V for 60sec.</td><td>>10GΩ</td></tr>
<tr><td>6.</td><td>Temperature Coefficient</td><td>With no electrical load.
<table>
<tr><th>T.C.</th><th>Operating Temp</th></tr>
<tr><td>NPO (C0G)</td><td>-55~125°C at 25°C</td></tr>
<tr><td>NPO (C0H)</td><td>-55~125°C at 25°C</td></tr>
<tr><td>NPO (C0J)</td><td>-55~125°C at 25°C</td></tr>
<tr><td>X7R</td><td>-55~125°C at 25°C</td></tr>
<tr><td>X7E</td><td>-55~125°C at 25°C</td></tr>
<tr><td>X5R</td><td>-55~ 85°C at 25°C</td></tr>
<tr><td>Y5V</td><td>-25~ 85°C at 20°C</td></tr>
</table></td><td>
<table>
<tr><th>T.C.</th><th>Capacitance Change</th></tr>
<tr><td>NPO (C0G)</td><td>Within ±30ppm/°C</td></tr>
<tr><td>NPO (C0H)</td><td>Within ±60ppm/°C</td></tr>
<tr><td>NPO (C0J)</td><td>Within ±120ppm/°C</td></tr>
<tr><td>X7R</td><td>Within ±15%</td></tr>
<tr><td>X7E</td><td>Within ±4.7%</td></tr>
<tr><td>X5R</td><td>Within ±15%</td></tr>
<tr><td>Y5V</td><td>Within +30%/-80%</td></tr>
</table></td></tr>
<tr><td>7.</td><td>Adhesive Strength of Termination</td><td>*Pressurizing force:
0201: 2N
0402 & 0603: 5N
>0603: 10N
Test time:10 ±1 sec</td><td> No remarkable damage or removal of the terminations.</td></tr>
</table>

Appendix I : Reliability Test Conditions and Requirements

<table>
<tr><th>No</th><th>Item</th><th>Test Condition</th><th>Requirements</th></tr>
<tr><td>8.</td><td>Vibration Resistance</td><td>* Vibration frequency: 10~55 Hz/min.
* Total amplitude: 1.5mm
* Test time: 6 hrs.
(Two hrs each in three mutually perpendicular directions.)
* Measurement to be made after keeping at room temp. for 24±2 hrs.</td><td>* No remarkable defect.
* Dimensions to conform to individual specification sheet.</td></tr>
<tr><td>9.</td><td>Solderability</td><td>* Solder temperature: 235±5°C
* Dipping time: 2±0.5 sec.</td><td>95% min. coverage of all metalized area.</td></tr>
<tr><td>10.</td><td>Bending Test</td><td>*The middle part of substrate shall be pressurized by means of the pressurizing rod at a rate of about 1 mm per second until the deflection becomes 1 mm / SH series: 5 mm** & 3 mm*** and then the pressure shall be maintained for 5±1 sec.
*Measurement to be made after keeping at room temp. for 24±2 hrs.
(** Thickness >1.0mm; *** Thickness≤1.0mm)</td><td>* No remarkable damage.
* Cap change:
NP0: within ±5% or 0.5pF whichever is larger
X7R, X7E, X5R: within ±12.5% , Y5V: within ±30%
(This capacitance change means the change of capacitance under specified flexure of substrate from the capacitance measured before the test.)</td></tr>
<tr><td>11.</td><td>Resistance to Soldering Heat</td><td>* Solder temperature: 260±5°C
* Dipping time: 10±1 sec
* Preheating: 120 to 150°C for 1 minute before immerse the capacitor in a eutectic solder.
* Before initial measurement (Class II only): Perform 150+0/-10°C for 1 hr and then set for 24±2 hrs at room temp.
* Measurement to be made after keeping at room temp. for 24±2 hrs.</td><td>* No remarkable damage.
* Cap change:
NP0: within ±2.5% or 0.25pF whichever is larger
X7R, X7E, X5R: within ±7.5%
Y5V: within ±20%
* Q/D.F., I.R. and dielectric strength: To meet initial requirements.
* 25% max. leaching on each edge.</td></tr>
<tr><td>12.</td><td>Temperature Cycle</td><td>* Conduct the five cycles according to the temperatures and time.
<table>
<tr><th>Step</th><th>Temp. (°C)</th><th>Time (min.)</th></tr>
<tr><td>1</td><td>Min. operating temp. +0/-3</td><td>30±3</td></tr>
<tr><td>2</td><td>Room temp.</td><td>2~3</td></tr>
<tr><td>3</td><td>Max. operating temp. +3/-0</td><td>30±3</td></tr>
<tr><td>4</td><td>Room temp.</td><td>2~3</td></tr>
</table>
* Before initial measurement (Class II only): Perform 150+0/-10°C for 1 hr and then set for 24±2 hrs at room temp.
* Measurement to be made after keeping at room temp. for 24±2 hrs.</td><td>* No remarkable damage.
* Cap change:
NP0: within ±2.5% or 0.25pF whichever is larger
X7R, X7E, X5R: within ±7.5%
Y5V: within ±20%
* Q/D.F., I.R. and dielectric strength: To meet initial requirements.</td></tr>
<tr><td>13.</td><td>Humidity (Damp Heat) Steady State</td><td>* Test temp.: 40±2°C
* Humidity: 90~95% RH
* Test time: 500+24/-0hrs.
*Before initial measurement (Class II only): Perform 150+0/-10°C for 1 hr and then set for 24±2 hrs at room temp.
* Measurement to be made after keeping at room temp. for 24±2 hrs.</td><td>* No remarkable damage.
* Cap change: NP0: within ±5% or 0.5pF whichever is larger
X7R, X7E, X5R: ≥10V**,within ±12.5%;6.3V within ±25%;TT series, within ±25%
**10V:0603≥4.7μF;0402≥1μF;0201≥0.1μF, within ±25%;
Y5V: ≥10V, within ±30%; 6.3V, within +30/-40%
* Q/D.F. value:
NP0: More than 30pF Q≥350, 10pF≤C≤30pF, Q≥275+2.5C,Less than 10pF Q≥200+10C
X7R, X5R:
<table>
<tr><th>Rated vol.</th><th>D.F.≤</th><th colspan="2">Exception of D.F. ≤</th></tr>
<tr><td rowspan="3">≥50V</td><td rowspan="3">≤3%</td><td>≤6%</td><td>0201(50V);0603≥0.047μF; 0805≥0.18μF; 1206≥0.47μF</td></tr>
<tr><td>≤10%</td><td>1210≥4.7μF</td></tr>
<tr><td>≤20%</td><td>0603≥1μF; 0805≥1μF;1206≥2.2μF; 1210≥10μF</td></tr>
<tr><td>35V</td><td>≤5%</td><td>≤20%</td><td>0805≥2.2μF;1210≥10μF</td></tr>
<tr><td rowspan="3">25V</td><td rowspan="3">≤5%</td><td>≤10%</td><td>0201≥0.01μF;0805≥1μF; 1210≥10μF</td></tr>
<tr><td>≤14%</td><td>0603≥0.33μF;1206≥4.7μF</td></tr>
<tr><td>≤15%</td><td>0402≥0.10μF;0603≥0.47μF;0805≥2.2μF;1206≥6.8μF; 1210≥22μF; TT series</td></tr>
<tr><td rowspan="2">16V</td><td rowspan="2">≤5%</td><td>≤10%</td><td>0603≥0.15μF;0805≥0.68μF;1206≥2.2μF;1210≥4.7μF</td></tr>
<tr><td>≤15%</td><td>0201≥0.01μF;0402≥0.033μF;0603≥0.68μF;0805≥2.2μF; 1206≥4.7μF; 1210≥22μF; TT series</td></tr>
<tr><td rowspan="2">10V</td><td rowspan="2">≤7.5%</td><td>≤15%</td><td>0201≥0.012μF;0402≥0.33μF; 0603≥0.33μF;0805≥2.2μF 1206≥2.2μF; 1210≥22μF</td></tr>
<tr><td>≤20%</td><td>0201≥0.1μF ;0402≥1μF; TT series</td></tr>
<tr><td>6.3V</td><td>≤15%</td><td>≤30%</td><td>0201≥0.1μF;0402≥1μF;0603≥10μF; 0805≥4.7μF;1206≥47μF;1210≥100μF;TT series</td></tr>
<tr><td>4V</td><td>≤20%</td><td>---</td><td>---</td></tr>
</table>
X7R/X7E, LD series : DF≤3%
Y5V:
<table>
<tr><th>Rated vol.</th><th>D.F.≤</th><th colspan="2">Exception of D.F.≤</th></tr>
<tr><td>≥50V</td><td>≤7.5%</td><td>≤10%</td><td>0603≥0.1μF;0805≥0.47μF;1206≥4.7μF</td></tr>
<tr><td>35V</td><td>≤10%</td><td>---</td><td>---</td></tr>
<tr><td rowspan="2">25V</td><td rowspan="2">≤7.5%</td><td>≤10%</td><td>0402≥0.047μF;0603≥0.1μF;0805≥0.33μF ;1206≥1μF; 1210≥4.7μF</td></tr>
<tr><td>≤15%</td><td>0402≥0.068μF;0603≥0.47μF;1206≥4.7 μF; 1210≥22μF; TT series & Cap≥1μF</td></tr>
<tr><td rowspan="2">16V(C<1.0μF)</td><td rowspan="2">≤10%</td><td>≤12.5%</td><td>0402≥0.068μF; 0603≥0.68μF</td></tr>
<tr><td>≤20%</td><td>0402≥0.22μF</td></tr>
<tr><td>16V(C≥1.0μF)</td><td>≤12.5%</td><td>≤20%</td><td>0603≥2.2μF;0805≥3.3μF;1206≥10μF ;1210≥22μF;1812≥47μF; TT series & Cap≥1μF</td></tr>
<tr><td>10V</td><td>≤20%</td><td>≤30%</td><td>0402≥0.47μF</td></tr>
<tr><td>6.3V</td><td>≤30%</td><td>---</td><td>---</td></tr>
</table>
*I.R.: ≥10V, 1GΩ or 50 Ω-F whichever is smaller.
Class II (X7R, X7E, X5R, Y5V)
<table>
<tr><th>Rated voltage</th><th>Insulation Resistance</th></tr>
<tr><td>100V: X7R</td><td rowspan="7">1GΩ or RxC≥10 Ω-F whichever is smaller.</td></tr>
<tr><td>50V:0603≥1μF;0805≥1μF;1206≥2.2μF;1210≥4.7μF</td></tr>
<tr><td>35V:0805≥2.2μF;1210≥10μF</td></tr>
<tr><td>25V:0402≥1μF;0603≥2.2μF;0805≥2.2μF;1206≥10μF;1210≥10μF</td></tr>
<tr><td>16V:0402≥0.22μF;0603≥1μF;0805≥2.2μF;1206≥10μF;1210≥47μF</td></tr>
<tr><td>10V:0201≥47nF;0402≥0.47μF;0603≥0.47μF; 0805≥2.2μF;1206≥4.7μF;1210≥47μF</td></tr>
<tr><td>6.3V ; 4V ; TT series</td></tr>
</table>
</td></tr>
</table>

No	Item	Test Condition	Requirements
14.	Humidity (Damp Heat) Load	* Test temp.: 40±2°C * Humidity: 90~95%RH * Test time: 500+24/-0 hrs. * To apply voltage: Rated voltage.(Max.500V) * Before initial measurement(Class II only): To apply test voltage for 1hr at 40°C and then set for 24±2 hrs at room temp. * Measurement to be made after keeping at room temp. for 24±2 hrs.	* No remarkable damage. Cap change: NP0: ±7.5% or 0.75pF whichever is larger. X7R, X7E, X5R: ≥10V**,within ±12.5%;6.3V within ±25%;TT series, within ±25% **10V:0603≥4.7μF;0402≥1μF;0201≥0.1μF, within ±25%; Y5V: ≥10V, within ±30%; 6.3V, within +30/-40% Q/D.F. value: NP0: C≥30pF,Q≥200;C<30pF, Q≥100+10/3C X7R, X5R:

Rated vol.	D.F.≤	Exception of D.F. ≤	
≥50V	≤3%	≤6%	0201(50V);0603≥0.047μF; 0805≥0.18μF; 1206≥0.47μF
		≤10%	1210≥4.7μF
		≤20%	0603≥1μF; 0805≥1μF;1206≥2.2μF; 1210≥10μF
35V	≤5%	≤20%	0805≥2.2μF;1210≥10μF
25V	≤5%	≤10%	0201≥0.01μF;0805≥1μF; 1210≥10μF
		≤14%	0603≥0.33μF;1206≥4.7μF
		≤15%	0402≥0.10μF;0603≥0.47μF;0805≥2.2μF;1206≥6.8μF;1210≥22μF; TT series
16V	≤5%	≤10%	0603≥0.15μF;0805≥0.68μF;1206≥2.2μF;1210≥4.7μF
		≤15%	0201≥0.01μF;0402≥0.033μF;0603≥0.68μF;0805≥2.2μF; 1206≥4.7μF; 1210≥22μF; TT series
10V	≤7.5%	≤15%	0201≥0.012μF; 0402≥0.33μF; 0603≥0.33μF;0805≥2.2μF;1206≥2.2 μF; 1210≥22μF
		≤20%	0201≥0.1μF ;0402≥1μF; TT series
6.3V	≤15%	≤30%	0201≥0.1μF;0402≥1μF;0603≥10μF; 0805≥4.7μF;1206≥47μF;1210≥100μF;TT series
4V	≤20%	---	---

X7R/X7E, LD series : DF≤3%
Y5V:

Rated vol.	D.F.≤	Exception of D.F.≤	
≥50V	≤7.5%	≤10%	0603≥0.1μF; 0805≥0.47μF;1206≥4.7μF; TT series & Cap≥1μF
35V	≤10%	---	---
25V	≤7.5%	≤10%	0402≥0.047μF;0603≥0.1μF;0805≥0.33μF;1206≥1μF; 1210≥4.7μF
		≤15%	0402≥0.068μF;0603≥0.47μF;1206≥4.7μF;1210≥22μF; TT series & Cap≥1μF
16V (C<1.0μF)	≤10%	≤12.5%	0402≥0.068μF; 0603≥0.68μF
		≤20%	0402≥0.22μF
16V (C≥1.0μF)	≤12.5%	≤20%	0603≥2.2μF;0805≥3.3μF;1206≥10μF;1210≥22μF;1812≥47μF; TT series & Cap≥1μF
10V	≤20%	≤30%	0402≥0.47μF
6.3V	≤30%	---	---

*I.R.: ≥10V, 500MΩ or 25 Ω-F whichever is smaller.Class II (X7R, X7E, X5R, Y5V)

Rated voltage	Insulation Resistance
100V: X7R	500MΩ or RxC≥5 Ω-F whichever is smaller.
50V:0603≥1μF;0805≥1μF;1206≥2.2μF;1210≥4.7μF	
35V:0805≥2.2μF;1210≥10μF	
25V:0402≥1μF;0603≥2.2μF;0805≥2.2μF;1206≥10μF;1210≥10μF	
16V:0402≥0.22μF;0603≥1μF;0805≥2.2μF;1206≥10μF;1210≥47μF	
10V:0201≥47nF;0402≥0.47μF;0603≥0.47μF ;0805≥2.2μF;1206≥4.7μF;1210≥47μF	
6.3V ; 4V ; TT series	

No	Item	Test Condition	Requirements
15.	High Temperature Load (Endurance)	*Test temp.: NP0, X7R/X7E: 125±3°C X5R, Y5V: 85±3°C *Test time: 1000+24/-0 hrs. *To apply voltage: (1) 6.3V or C≥10μF or TT series: 150% of rated voltage. (2) 10V≥Ur<500V: 200% of rated voltage. (3) 500V: 150% of rated voltage. (4) Ur≥630V: 120% of rated voltage. (5) 100% of rated voltage for below range.	* No remarkable damage. Cap change: NP0: ±3.0% or ±0.3pF whichever is larger X7R, X7E, X5R: ≥10V**,within ±12.5%;6.3V within ±25%;TT series,within ±25% **10V:0603≥4.7μF;0402≥1μF;0201≥0.1μF, within ±25%; Y5V: ≥10V, within ±30%; 6.3V, within +30/-40% Q/D.F. value: NP0: More than 30pF, Q≥350; 10pF≤C<30pF, Q≥275+2.5C; Less than 10pF, Q≥200+10C X7R, X5R:

Size	Dielectric	Rated voltage	Capacitance range
0201	X5R/X7R	6.3V,10V	C≥0.1μF
0402	X5R/X7R	6.3V,10V	C≥1.0μF
0603	X5R/X7R	6.3V,10V	C≥4.7μF
0805	X5R/X7R	6.3V	C≥22μF
1206	X5R/X7R	6.3V	C≥47μF
	NP0	3000V	C≥1.5pF
TT18	Y5V	6.3V,10V	C≥2.2μF
TT21	Y5V	6.3V	C≥10μF
TT31	Y5V	6.3V	C≥22μF

(6)150% of rated voltage for below range.

Size	Dielectric	Rated voltage	Capacitance range
0402	X5R/X7R	10V,16V,25V	C≥0.22μF
	Y5V	16V	C≥0.47μF
0603	X5R/X7R	10V,16V	C≥1.0μF
	Y5V	16V	C≥2.2μF
0805	X5R/X7R	10V	C≥4.7μF
	Y5V	16V	C≥4.7μF

*Before initial measurement (Class II only): To apply test voltage for 1hr at test temp. and then set for 24±2 hrs at room temp.
*Measurement to be made after keeping at room temp. for 24±2 hrs

Rated vol.	D.F.≤	Exception of D.F. ≤	
≥50V	≤3%	≤6%	0201(50V);0603≥0.047μF; 0805≥0.18μF; 1206≥0.47μF
		≤10%	1210≥4.7μF
		≤20%	0603≥1μF; 0805≥1μF;1206≥2.2μF; 1210≥10μF
35V	≤5%	≤20%	0805≥2.2μF;1210≥10μF
25V	≤5%	≤10%	0201≥0.01μF;0805≥1μF; 1210≥10μF
		≤14%	0603≥0.33μF;1206≥4.7μF
		≤15%	0402≥0.10μF;0603≥0.47μF;0805≥2.2μF;1206≥6.8μF;1210≥22μF; TT series
16V	≤5%	≤10%	0603≥0.15μF;0805≥0.68μF;1206≥2.2μF;1210≥4.7μF
		≤15%	0201≥0.01μF;0402≥0.033μF;0603≥0.68μF;0805≥2.2μF; 1206≥4.7μF; 1210≥22μF; TT series
10V	≤7.5%	≤15%	0201≥0.012μF; 0402≥0.33μF; 0603≥0.33μF;0805≥2.2μF;1206≥2.2μF; 1210≥22μF
		≤20%	0201≥0.1μF ;0402≥1μF; TT series
6.3V	≤15%	≤30%	0201≥0.1μF;0402≥1μF;0603≥10μF; 0805≥4.7μF;1206≥47μF;1210≥100μF;TT series
4V	≤20%	---	---

X7R/X7E, LD series : DF≤3%
Y5V:

Rated vol.	D.F.≤	Exception of D.F.≤	
≥50V	≤7.5%	≤10%	0603≥0.1μF; 0805≥0.47μF;1206≥4.7μF; TT series & Cap≥1μF
35V	≤10%	---	---
25V	≤7.5%	≤10%	0402≥0.047μF;0603≥0.1μF;0805≥0.33μF;1206≥1μF; 1210≥4.7μF
		≤15%	0402≥0.068μF;0603≥0.47μF;1206≥4.7μF;1210≥22μF; TT series & Cap≥1μF
16V(C<1.0μF)	≤10%	≤12.5%	0402≥0.068μF; 0603≥0.68μF
		≤20%	0402≥0.22μF
16V(C≥1.0μF)	≤12.5%	≤20%	0603≥2.2μF;0805≥3.3μF;1206≥10μF;1210≥22μF;1812≥47μF;TT series & Cap≥1μF
10V	≤20%	≤30%	0402≥0.47μF
6.3V	≤30%	---	---

*I.R.: ≥10V, 1GΩ or 50 Ω-F whichever is smaller.Class II (X7R, X7E, X5R, Y5V)

Rated voltage	Insulation Resistance
100V: X7R	1GΩ or RxC≥10 Ω-F whichever is smaller.
50V:0603≥1μF;0805≥1μF;1206≥2.2μF;1210≥4.7μF	
35V:0805≥2.2μF;1210≥10μF	
25V:0402≥1μF;0603≥2.2μF;0805≥2.2μF;1206≥10μF;1210≥10μF	
16V:0402≥0.22μF;0603≥1μF;0805≥2.2μF;1206≥10μF;1210≥47μF	
10V:0201≥47nF;0402≥0.47μF;0603≥0.47μF;0805≥2.2μF; 1206≥4.7μF;1210≥47μF	
6.3V ; 4V ; TT series	

No	Item	Test Condition	Requirements
16.	ESR	For RF Series only, refer to data sheet.	---

Appendix II : General Information

■ Constructions

No.	Name		NP0/X7R/X7E	NPO/X7R/X5R/Y5V
①	Ceramic material		BaTiO3 based	
②	Inner electrode		AgPd alloy	Ni
③	Termination	Inner layer	Ag	Cu
④		Middle layer	Ni	
⑤		Outer layer	Sn	

Fig. 1 The construction of MLCC

■ Storage and handling conditions

(1)To store products at 5 to 40°C ambient temperature and 20 to 70%. related humidity conditions.

(2)The product is recommended to be used within one year after shipment. Check solderability in case of shelf life extension is needed.

Cautions:

a. The corrosive gas reacts on the terminal electrodes of capacitors, and results in the poor solderability. Do not store the capacitors in the ambience of corrosive gas (e.g., hydrogen sulfide, sulfur dioxide, chlorine, ammonia gas etc.)

b. In corrosive atmosphere, solderability might be degraded, and silver migration might occur to cause low reliability.

c. Due to the dewing by rapid humidity change, or the photochemical change of the terminal electrode by direct sunlight,the solderability and electrical performance may deteriorate. Do not store capacitors under direct sunlight or dewing condition. To store products on the shelf and avoid exposure to moisture.

■ Recommended soldering conditions

The lead-free termination MLCCs are not only to be used on SMT against lead-free solder paste, but also suitable against lead-containing solder paste. If the optimized solder joint is requested, increasing soldering time, temperature and concentration of N2 within oven are recommended.

Fig. 2 Recommended reflow soldering profile for SMT process with SnAgCu series solder paste.

Fig. 3 Recommended wave soldering profile for SMT process with SnAgCu series solder.

華新科技股份有限公司
Walsin Technology Corporation

Taiwan - Yang-Mei Plant / Sales Office
Walsin Technology Corporation
566-1, Kao-Shi Road, Yang-Mei,
Tao-Yuan, Taiwan
Tel: +886-3-475-8711
Fax: +886-3-475-7130
Email: info@passivecomponent.com

Taiwan - Kaohsiung Plant
Walsin Technology Corporation
1st, West 13 Street, K.E.P.Z.
Kaohsiung, Taiwan
Tel: +886-7-821-8171
Fax: +886-7-813-1661
Email: info@passivecomponent.com

China - Dalang Plant / Sales Office
Dongguan Walsin Tech. Electronics CO., Ltd.
Xiniupo Administrative Zone,
Dalang Town, Dongguan City,
Guangdong Province 523799
Tel: +86-769-831-15168
Fax: +86-769-831-15188
Email: stlin@passivecomponent.com

China - Suzhou Plant / Sales Office
Suzhou Walsin Technology Electronics Co., Ltd.
No. 369, Changyan Street,
Suzhou Industrial Park,
Jiangsu Province 215126
Tel: +86-512-628-36888
Fax: +86-512-628-37888
Email: davidcheng@passivecomponent.com

China - Guangzhou Plant / Sales Office
Pan Overseas (Guangzhou) Electronic Co., Ltd.
No. 277, Hong Ming Road, Eastern Section,
Guangzhou Economic and Technology
Development Zone, China
Tel: +86-20-8223-7476
Fax: +86-20-8223-7475
Email: info@passivecomponent.com

China - Chongqing Sales Office
Avenue of Stars Yongchuan District No.999
Chongqing , China
Tel: +86-769-831-15168 Ext:8509
Fax: +86-769-831-15188
Email: jimmylin@passivecomponent.com

Germany - Munich Sales Office
Walsin Technology Corporation Europe
Stefan-George-Ring 29, 81929 Munich,Germany
Tel: +49-(0)89-9308-6475
Fax: +49-(0)89-9308-6464
Email: aw@passivecomponent.com

Singapore - Sales Office
WTC Singapore Sales Office, Singapore
8 Ubi View #04-01 Serial System Building
Singapore 408554
Tel: +65-6896-3877
Fax: +65-6861-3381
Email: michaelchee@sg.passivecomponent.com

United States - West Coast Sales Office
Walsin Technology Corporation, USA
39500 Stevenson Place Suite 101,
Fremont, CA 94539, USA
Tel: +1-214-708-5182
E-mail: fctseng@passivecomponent.com

JAPAN - Sales Office
WTC Japan Sales Office, Japan
8-4-17, Fukayanaka, Ayase-shi,
Kanagawa, 252-1107, Japan.
Tel: +81-467-71-0884
Fax: +81-467-71-0910
Email: tsakano@kamaya.co.jp

PSA
PASSIVE SYSTEM ALLIANCE
Walsin Technology Corporation

TAIWAN - WTC Yang-Mei Plant / Sales Office
Walsin Technology Corporation
566-1, Kao-Shi Road, Yang-Mei, Tao-Yuan, Taiwan
Tel: +886-3-475-8711
Fax: +886-3-475-7130
Email: info@passivecomponent.com

Kaohsiung Plant, Taiwan
Walsin Technology Corporation
1st, West 13 Street, K.E.P.Z. Kaohsiung, Taiwan
Tel: +886-7-821-8171
Fax: +886-7-813-1661
Email: info@passivecomponent.com

國家品質獎 NATIONAL QUALITY AWARD

January 2013