

**Micro Commercial Components** 



**Micro Commercial Components** 20736 Marilla Street Chatsworth CA 91311 Phone: (818) 701-4933 (818) 701-4939 Fax:

## Features

- Lead Free Finish/RoHS Compliant ("P" Suffix designates RoHS Compliant. See ordering information) Epoxy meets UL 94 V-0 flammability rating
- Moisure Sensitivity Level 1
- Power Dissipation: 0.2W
- Ultra-small surface mount package
- Marking: K3P
- Halogen free available upon request by adding suffix "-HF"

## **Maximum Ratings**

Symbol	Rating	Rating	Unit		
V <sub>CEO</sub>	Collector-Emitter Voltage	40	V		
V <sub>CBO</sub>	Collector-Base Voltage	75	V		
V <sub>EBO</sub>	Emitter-Base Voltage	6.0	V		
I <sub>CBO</sub>	Collector Cut-off Current (V <sub>CB</sub> =70V, I <sub>E</sub> =0)	100	mA		
I <sub>CEO</sub>	Collector Cut-off Current (V <sub>CE</sub> =35V, I <sub>B</sub> =0)	100	mA		
I <sub>EBO</sub>	Emitter Cut-off Current (V <sub>EB</sub> =3V, I <sub>C</sub> =0)	100	mA		
Pc	Power dissipation (1)	200	200 mW		
TJ	Junction Temperature	-55 to +150	°C		
T <sub>STG</sub>	Storage Temperature	-55 to +150	°C		

#### Electrical Characteristics @ 25°C Unless Otherwise Specified Symbol

Parameter Min Max Units **OFF CHARACTERISTICS**<sup>(2)</sup>


UTT GRANAGTENISTIGS				
V <sub>(BR)CEO</sub>	Collector-Emitter Breakdown Voltage $(I_C=1.0mAdc, I_B=0)$	40		Vdc
V <sub>(BR)CBO</sub>	Collector-Base Breakdown Voltage (I <sub>c</sub> =10mAdc, I <sub>E</sub> =0)	75		Vdc
V <sub>(BR)EBO</sub>	Collector-Emitter Breakdown Voltage $(I_E=10\mu Adc, I_C=0)$	6.0		Vdc


## **ON CHARACTERISTICS**<sup>(2)</sup>

h <sub>FE</sub>	DC Current Gain (I <sub>c</sub> =150mAdc, V <sub>cE</sub> =10Vdc) (I <sub>c</sub> =1.0mAdc, V <sub>cE</sub> =10Vdc)	100 50	300	
V <sub>CE(sat)</sub>	Collector-Emitter Saturation Voltage (I <sub>c</sub> =500mAdc, I <sub>B</sub> =50mAdc)		0.6	Vdc
V <sub>BE(sat)</sub>	Base-Emitter Saturation Voltage (I <sub>c</sub> =500mAdc, I <sub>B</sub> =50mAdc)		1.2	Vdc
f <sub>T</sub>	Transition Frequency (V <sub>CE</sub> =20V, I <sub>C</sub> =20mA, f=100MHz)	300		Hz
C <sub>ob</sub>	Output Capacitance (V <sub>CB</sub> =10V, I <sub>E</sub> =0mA, f=1MHz)		8	pF
t <sub>d</sub>	Delay Time ( $V_{CC}$ =30V , $I_{cc}$ =150mA , $V_{BE(off)}$ =0.5V, $I_{B1}$ =15mA)		10	ns
tr	Rise Time (V <sub>CC</sub> =30V , I <sub>cc</sub> =150mA ,V <sub>BE(off)</sub> =0.5V, I <sub>B1</sub> =15mA)		25	ns
ts	Storage Time ( $V_{CC}$ =30V , $I_{cc}$ =150mA , $I_{B1}$ = $I_{B2}$ =15mA)		225	ns
t <sub>f</sub>	Fall Time ( $V_{CC}$ =30V , $I_{cc}$ =150mA , $I_{B1}$ = $I_{B2}$ =15mA)		60	ns

## **MMST2222A**

## NPN **Plastic-Encapsulate Transistors**





# www.mccsemi.com



## **Ordering Information :**

Device	Packing
Part Number-TP	Tape&Reel 3Kpcs/Reel

Note : Adding "-HF" suffix for halogen free, eg. Part Number-TP-HF

## **\*\*\*IMPORTANT NOTICE\*\*\***

*Micro Commercial Components Corp.* reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes. *Micro Commercial Components Corp*. does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold *Micro Commercial Components Corp*. and all the companies whose products are represented on our website, harmless against all damages.

#### \*\*\*LIFE SUPPORT\*\*\*

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

## \*\*\*CUSTOMER AWARENESS\*\*\*

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. **MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources.** MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.

# www.mccsemi.com

# **Mouser Electronics**

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Micro Commercial Components (MCC): MMST2222A-TP