

Humidity/temperature measuring instrument

testo 610 - Pocket-sized air humidity measurements

| Measureme | nt of ai | r humidity | and tem | perature |
|-----------|----------|------------|---------|----------|
| | | | | |

Incl. dewpoint calculation and Wet Bulb

Long-term stable Testo humidity sensor

Hold-function and max./min. values

Display illumination



The testo 610 simultaneously measures relative air humidity and temperature. It is thus ideally suitable for fast checks on ambient conditions, e.g. in offices, production rooms or in warehouses.

The patented humidity sensor developed by Testo guarantees reliable measurement resulty. The accuracy of ± 2.5 %RH is confirmed by a calibration protocol which is included in delivery. Dewpoint calculation and the calculation of Wet Bulb as well as a hold-function and the display of max. and min. values are possible with the testo 610.

The clip-on protective cap, wrist strap and belt holder ensure safekeeping of the instrument. testo 610 is very handy, small and easy to operate.

Technical data / Accessories

testo 610

testo 610 handy humidity/temperature meter incl. protection cap, batteries, belt holder and calibration protocol



Part no. 0560 0610

General technical data

| Measuring rate | 1 s |
|-----------------------|---|
| Weight | 90 g (batteries and protective cap included) |
| Operating temperature | -10 to +50 °C |
| Storage temperature | -40 to +70 °C |
| Battery type | 2 AAA micro batteries |
| Battery life | 200 h (average, without display illumination) |
| Dimensions | 119 x 46 x 25 mm (incl. protective cap) |
| Protection class | IP20 |
| | |

0981 9734/msp/A/10.2013

Sensor types

| | NTC | Testo humid. sensor, cap. |
|----------------------|---------------|---------------------------|
| Measuring range | -10 to +50 °C | 0 to 100 %RH |
| Accuracy ±1 digit | ±0.5 °C | ±2.5 %RH (5 to 95 %RH) |
| Resolution | 0.1 °C | 0.1 %RH |

| Accessories | Part no. | |
|---|-----------|--|
| Accessories for measuring instrument | | |
| Belt holder | 0516 4007 | |
| ISO calibration certificate humidity calibration points 11.3 %RH and 75.3 %RH at +25 °C/+77 °F; per channel/instrument | 0520 0076 | |
| ISO calibration certificate/temperature temp. data logger; calibration points -8°C; 0°C; +40°C per channel/instrument | 0520 0171 | |

Head Office:

Plot No. 23, Sindh Society, Baner Road, Aundh, Pune - 411007, Maharashtra, India Tel: +91 20 6560 0203 | Fax: +91 20 2585 0080 Email: info@testoindia.com | Web: www.testo.in

Regional Offices / Representatives: Ahmedabad | Baroda | Bengaluru | Chandigarh | Chennai | Guwahati

Hyderabad | Indore | Kolkata | Lucknow | Mumbai | New Delhi | Raipur

| Authorized Channel Partner | | | | | |
|----------------------------|--|--|--|--|--|
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |